

# Safety Data Sheet

## Log Guard – Interior Clear Coat 1040

Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

Effective Date: December 1, 2016



### 1. SUBSTANCE/PREPARATION AND COMPANY IDENTIFICATION

**Name of Product:** Log Guard Interior Clear Coat

**Product Code:** 1040

**Other Means of Identification:** Clear Liquid

**Recommended Use:** Coating

**Supplier Information:**

**Company:** Weatherall Company, Inc.  
106 Industrial Way  
Charlestown, IN 47111

**Company Phone Number:** 800-367-7068 (8:00 a.m. - 4:30 p.m. EST)

**Emergency Phone Number:** 812-256-3378

### 2. HAZARDS IDENTIFICATION

#### GHS Classifications

HAZARD	CATEGORY	SIGNAL WORD	HAZARD STATEMENT	SYMBOL
Physical Hazards	None, not flammable	None	None	None
Health Hazards Acute Toxicity	5	Warning	H303, May be harmful if swallowed	None
Skin Corrosion/ Irritation	2	Warning	H315, Causes skin irritation	Exclamation Mark
Eye Irritation	2A	Warning	H319, Causes serious eye irritation	Exclamation Mark
Aspiration Hazard	1	Danger	H304, May be fatal if swallowed and enters airways	Health Hazard

# Safety Data Sheet – Log Guard – Interior Clear Coat 1040

Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

Effective Date: December 1, 2016

## 2. HAZARDS IDENTIFICATION, continued

**Emergency Overview:** Warning! Contains petroleum distillates which can solubilize skin oils, causing dry skin and eventually dermatitis with repeated exposure.

**Route of Entry:** Inhalation: yes. Skin: yes. Ingestion: yes.

**Carcinogenicity:** NTP: no. IARC: no. OSHA: no.

**Reproductive Toxicity:** No reproductive toxicants over 1% in formula.

**Specific Target Organ Systemic Toxicity (TOST):** Single Exposure: Irritating to the skin and eyes and respiratory tract. Prolonged exposure will affect the nervous system, causing nervous system depression.

### Effects of Exposure:

**Acute: Eye:** H319: Causes serious eye irritation.

**Skin:** Category 2. Causes skin irritation. Reversible adverse effects in dermal tissue within the observation period, usually 14 days.

**Inhalation:** Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, and headache. High concentrations may result in narcosis (central nervous system depression). Intentional inhalation in concentrated form (huffing) may lead to brain damage and death.

**Ingestion:** Can cause gastrointestinal irritation, nausea, vomiting, and effects of overexposure.

### Signs and Symptoms of Overexposure:

**Health Hazard:** Diarrhea. Dermatitis.

**Medical Conditions Aggravated by Exposure:** Asthma.

### LABELING:

**Product Identifier:** Log Guard Interior Clear Coat

**Signal Word:** Danger

**Hazard Statements:** H304, May be fatal if swallowed and enters airways. H315, Causes skin irritation. H319, Causes Serious Eye irritation.

**Causes Skin and Eye Irritation.** Do not breathe vapors or mist. Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

### FIRST AID:

**Eyes:** Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

**Skin:** In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothes before reuse. Get medical attention if irritation develops and persists.

# Safety Data Sheet – Log Guard – Interior Clear Coat 1040

Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

Effective Date: December 1, 2016

## 2. HAZARDS IDENTIFICATION, continued

**Company Name:** Weatherall Company, Inc.

**Address:** 106 Industrial Way  
Charlestown, IN 47111

**Phone Number:** 800-367-7068

**HAZARDS:** (Liquid) Serious skin and eye irritant.

**Pictograms on the label:**



**WARNING:** May cause damage to central nervous system through prolonged or repeated inhalation.

**WARNING:** May cause respiratory irritation when inhaled.

**Hazard Statements:**

**H304** May be fatal if swallowed and enters airways.

**H315** Causes skin irritation.

**H319** Causes serious eye irritation.

**Precautionary Statements:**

**P261** Avoid breathing dust/fume/gas/mist/vapors/spray.

**P305+P351+P338** IF IN EYES: Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.

## 3. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Hazardous Ingredients	CAS#	Percent w/w	OSHA PEL
Propylene Glycol	57-55-6	<2	Not Established
Diethylene glycol monobutyl ether	112-34-5	<2	10ppm ACGIH TLV

Note: Further safety information can be found in subsequent sections.

# Safety Data Sheet – Log Guard – Interior Clear Coat 1040

Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

Effective Date: December 1, 2016

## 4. FIRST AID MEASURES

**General Information:** Discard contaminated clothing immediately.

**Eye:** Flush with clean, lukewarm water for at least 15 minutes, occasionally lifting eyelids.  
Obtain medical attention.

**Skin:** Remove contaminated clothing. Wash affected skin areas thoroughly with soap and water.  
Wash contaminated clothing thoroughly before reuse.

**Inhalation:** Remove to fresh air. Apply artificial respiration/administer oxygen if necessary. Call physician immediately. If person is unconscious, transport affected person in reclined position.

**Ingestion:** Keep person warm and quiet. Get immediate medical attention. Do not induce vomiting.  
Never give anything orally to an unconscious person. Drink several glasses of water to dilute the product in the stomach.

## 5. FIRE FIGHTING MEASURES

**Flammability Summary (OSHA):** Not Flammable (Waterborne)

**Flash Point Method:** Setaflash.

**Flash Point:** Greater than 200°F (93°C) (Setaflash)

**Upper Flammable/Explosive Limit, % in air:** Not Found

**Lower Flammable/Explosive Limit, % in air:** Not Found

When dry the product can be made to burn:

**Upper Flammable/Explosive Limit, % in air:** NA

**Lower Flammable/Explosive Limit, % in air:** NA

**Unusual Fire/Explosion Hazards:** Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Closed containers may explode when exposed to fire due to pressure buildup.

**Extinguishing Media:** Use water fog, foam, carbon dioxide or chemical fire fighting apparatus.

**Fire Fighting Instructions:** Product is not flammable. In case of fire in the area of the product, wear NIOSH/MSHA approved SCBA and full protective equipment. Do not use full pressure water jet. Water spray may be used for cooling containers to prevent possible pressure build up and auto ignition/explosion when exposed. Guard against toxic gases released by fire. If safe, remove containers from fire zone.

**Products of Combustion:** Carbon Dioxide, Carbon Monoxide, Water Vapor.

# Safety Data Sheet – Log Guard – Interior Clear Coat 1040

Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

Effective Date: December 1, 2016

## 6. ACCIDENTAL RELEASE MEASURES

**Large Spills:** Dike the spill with barriers to prevent it from spreading. Pump or scoop into containers.

**Small Spills:** Use mop and wash the residue with soap and water to keep slipping from happening.

**Waste Disposal Methods:** Waste material must be disposed of in accordance with federal, state and local environment regulatory controls.

## 7. HANDLING AND STORAGE

**Handling:** Use drum trucks and pallet jacks to move drums and cans.

**Drums:** Protect against physical damage.

**Bulk:** Storage should be in standard lidded storage tanks.

**Other Precautions:** Clean up spills quickly to prevent slipping on the wet surface.

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

**Respiratory Protection:** Use NIOSH/MSHA approved self-contained breathing apparatus where vapor concentration may be above TLV limits. Below TLV limits use NIOSH/MSHA approved vapor respirator or an airline respirator with escape bottle provisions. This product is not expected to produce high concentrations of vapors in the air. When in doubt, test the atmosphere during working conditions.

**Ventilation:** Local exhaust must be sufficient to keep airborne vapor concentrations below TLV limit. Exhaust air may need to be cleaned by scrubbers.

**Protective Gloves:** Chemical resistant gloves.

**Eye Protection:** Chemical workers' goggles.

**Other Protective Equipment:**

**Eye Bath and Safety Shower:** To prevent repeated or prolonged skin contact wear impervious clothing and boots.

**Work Hygiene Practices:** Wash hands and clothing after exposure.

**Supplemental Safety and Health:** First aid procedures: Vomit can cause chemical pneumonia which can be fatal.

**Ventilation:** Filters to reduce environmental contamination.

**Effects of Overexposure:** Irritating to respiratory system. Mild, reversible liver effects, liver abnormalities.

**Exposure Limits:**

Hazardous Ingredients	CAS#	Percent w/w	OSHA PEL
Propylene Glycol	57-55-6	<2	Not Established
Diethylene glycol monobutyl ether	112-34-5	<2	10ppm ACGIH TLV

# Safety Data Sheet – Log Guard – Interior Clear Coat 1040

Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

Effective Date: December 1, 2016

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical State:** Liquid.

**Color:** Milky white when wet, clear when dry.

**Odor:** Slight.

**Odor Threshold:** Not available.

**pH Value:** 8.5 to 9.4.

**Melting Point:** Not available.

**Evaporation Rate:** Slower than ether.

**Freezing Point:** 0°C (32°F)

**Initial Boiling Point:** 100°C (212°F)

**Auto Ignition Temperature:** 395°C (743°F).

**Bulk Density:** Approximately 8.66 pounds per gallon.

**Flash Point:** >200°F PMCC.

**Upper Explosion Limit:** Not established.

**Lower Explosion Limit:** Not established.

**Solubility in Water:** Miscible

**Specific Gravity:** 1.04 @20C(68F).

**Weight per Gallon:** 8.66 +/- 0.15 pounds

**VOC:** 0.84 pounds per gallon less water (101 g/l)

## 10. STABILITY AND REACTIVITY

**Stability and Reactivity Summary:** Stable under normal conditions.

**Reactive Properties:** Strong acids and bases will attack the polymer.

**Sensitivity to Mechanical Shock:** None.

**Hazardous Polymerization:** Will not occur.

**Conditions to Avoid:** Do not heat closed containers.

**Chemical Incompatibility:** Strong oxidizing agents.

**Hazardous Decomposition Products:** CO, CO<sub>2</sub>.

# Safety Data Sheet – Log Guard – Interior Clear Coat 1040

Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

Effective Date: December 1, 2016

## 11. TOXICOLOGICAL INFORMATION

Hazardous Ingredients	CAS#	Percent w/w	LD50 Oral Rat Mg/kg	LD50 Dermal Rabbit Mg/kg
Propylene Glycol	57-55-6	<2	20000	Not found
Diethylene glycol monobutyl ether	112-34-5	<2	4500	2764

## 12. ECOLOGICAL INFORMATION - TOXICITY TO FISH:

Hazardous Ingredients	CAS#	Percent w/w	LC50 Oncorhynchus mhykiss (rainbow trout)
Propylene Glycol	57-55-6	<2	Low toxicity to fish
Diethylene glycol monobutyl ether	112-34-5	<2	1300 mg/l

**Environmental Toxicity:** Some parts are not persistent in the environment. Ecotoxicity Classification criteria is between 1 and 100 for some of the ingredients. Most ingredients are carbon based and are eventually degraded by bacteria when placed in water or soil.

## 13. DISPOSAL CONSIDERATIONS

Care must be taken to avoid environmental contamination from the use of this material. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws.

**Waste Disposal Summary:** Dispose as a hazardous chemical.

**Disposal Methods:** Dispose of in accordance with local, state and federal regulations. Incineration is preferred.

## 14. TRANSPORT INFORMATION

**US Ground (DOT):** Not regulated for transportation.

**Canada (TDG):** Not regulated for transportation.

**IMO:** Not regulated for transportation.

**IATA/ICAO:** Not regulated for transportation.

# Safety Data Sheet – Log Guard – Interior Clear Coat 1040

Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

Effective Date: December 1, 2016

## 15. REGULATORY INFORMATION

### UNITED STATES:

**Toxic Substances Control Act (TSCA):** The components of this product are listed on the TSCA Inventory of Existing Chemical Substances.

**Superfund Amendments and Reauthorization Act (SARA) Title III:** Diethylene Glycol Monobutyl Ether (Glycol Ethers Category)

**Sections 311/312 Hazard Categories:** (40 CFR 370.2)

**Immediate/Acute Health Hazard:** Yes.

**Delayed/Chronic Health Hazard:** Yes.

**Fire Hazard:** No.

**Pressure Hazard:** No.

**Reactivity Hazard:** No.

### FEDERAL AND STATE REGULATIONS:

**California Prop 65:** The following chemicals have been determined by the State of California to cause cancer in laboratory animals and are available in trace amounts in this product:

Chemical	CAS Number	Notes
1,4-Dioxane	123-91-1	0.0001% which is below the Safe Harbor Level
Ethylene oxide	75-21-8	0.2529 ppm which is below the Safe Harbor Level

**California Prop 65:** The following chemicals have been determined by the State of California to cause birth defects in laboratory animals and are available in trace amounts in this product:

Chemical	CAS Number	Notes
Ethylene oxide	75-21-8	0.2529 ppm which is below the Safe Harbor Level

**CERCLA Reportable Quantities:** None

### HMIS (U.S.A.):

**Health Hazard:** 1

**Fire Hazard:** 0

**Reactivity:** 0

**Personal Protection:** A

### National Fire Protection Association (U.S.A.):

**Health:** 1

**Flammability:** 0

**Reactivity:** 0



# Safety Data Sheet – Log Guard – Interior Clear Coat 1040

Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

Effective Date: December 1, 2016

## 16. OTHER INFORMATION

This information should be provided to all who will use, handle, store, transport or otherwise be exposed to this product. While the descriptions, designs, data and information contained herein are presented in good faith and believed to be accurate, it is provided for your guidance only. Because many factors may affect processing or application/use, we recommend that you make tests to determine the suitability of a product for your particular purpose prior to its use. No warranties of any kind neither express nor implied, including warranties of merchantability or fitness for a particular purpose are made regarding products described or designs, data or information set forth, or that the products, designs, data or information may be used without infringing the intellectual property rights of others. In no case shall the descriptions, information, data or designs provided be considered part of our terms and conditions of sale. Further, you expressly understand and agree that the descriptions, information, data and designs furnished by WEATHERALL COMPANY, INC. hereunder are given gratis and WEATHERALL COMPANY, INC. assumes no obligation or liability for the description, information, data and designs given or results obtained, all such being given and accepted at your risk. We believe this information to be reliable and up to date as of its publication date, but make no warranty that it is. If this SDS is more than one year old you should contact WEATHERALL COMPANY, INC. to make sure the information is still current.

Prepared by V.C. Bud Jenkins, BS, MBA, JD, CHMM, CHWP  
Coatings Scientist Consulting Services, [www.coatingsscientist.com](http://www.coatingsscientist.com)