

# PC-Woody- Permanent Interior/Exterior Wood Repair

## Description:

PC-Woody® is an epoxy paste formulated to replace missing and rotted wood. It has structural strength greater than most wood. PC- Woody® is a permanent wood repair for interior and exterior applications. This epoxy is made from real wood and has many characteristics of wood. PC-Woody® formulation



provides extended working time, for large and critical jobs, which allows the user time to reposition work or make changes. High “wet grab” or tack of PC-Woody® makes overhead and sidewall work easy without drip or sag. PC- Woody® demonstrates excellent resistance to all weather elements, mildew dry rot, UV light, fresh and salt water, and also chemicals present in pressure-treated wood.

\*\*\*Note: PC-Woody® will not bond to wax paper, Teflon®, Polyethylene, and some other plastics. There are hundreds of plastics in thousands of combination. Test a small area when in doubt.

## Directions:

Using separate knives to remove amount needed, mix equal parts A (off white) and B (light brown) on a flat clean surface until a uniform color is achieved. Surfaces to be bonded must be free of dirt, oil, rust, etc. For best results, rough up the surface PC-Woody® will be bonding to. Normally, no vice or clamp is needed. Prop or tape heavy objects to a wall or ceiling.

Apply PC-Woody® in any thickness to both sides of surface and bring together firmly. Be careful to insure that ample amount of PC-Woody® remains between the contact surfaces. Use screen wire or fiberglass cloth to reinforce large voids and gaps.

Denatured alcohol is excellent for smoothing applied PC-Woody®. Also use Denatured alcohol to clean surfaces before applying.

**After cure:** Paint, Stain, Drill, Machine, Sand, File, Tap, or Saw.