Recommended Application

Make certain the surface to be coated is free from all dirt, oil, grease, grime, mildew, fungus or loose stain prior to finish application. UV Guard® Deck & Fence Wood Finish may be applied by brush, airless sprayer or pump sprayer. If spray application is used then back brushing is necessary. Do not stop in the middle of deck boards or lap marks will be created. A single coat application is sufficient for most wood surfaces but a second coat may be applied as a wet-on-wet application or a wet-on-dry application. No more than 2 coats should be applied. Each coat will be dry to the touch in 30 minutes to 1 hour and suitable for foot traffic within 24 to 72 hours depending on the ambient temperature and the relative humidity. Please inquire with us for a complete UV Guard® Deck & Fence Wood Finish application guide prior to the start of your next job.

Maintenance

Your wood surface should be rinsed clean and completely free from dust, dirt, oil or any other contaminants prior to re-stain application. Some areas may require sanding based upon the condition of the wood surface. Expect to re-apply the UV Guard[®] Deck & Fence Wood Finish every 2 to 4 years depending on the amount of exposure and foot traffic. If a commercial cleaner is used, follow directions and rinse solution completely from wood. Verify that the wood surface has a pH Neutral surface of between 6 and 8. Allow wood surface to dry completely (18% moisture content) before applying UV Guard[®] Deck & Fence Wood Finish. The overall success of your stain is dramatically affected by the preparation of your wood prior to staining and how good of a job you do during the stain application process. Aggressively back brushing your stain into the pores of your wood is highly recommended.

Packaging

Sample Jar, 1 Gallon Pail and 5 Gallon Pail

Coverage Rates

150-300 square feet per gallon on the first coat. 300-400 square feet per gallon on second or subsequent coats.

**The above coverage rates are highly dependent upon the porosity of the wood and the condition of the existing stain. Stain not recommended for high density, high oil content or exotic woods. Do not thin or dilute product.

Experience & Reputation

For over 30 years, the Weatherall Company has been making and delivering the best wood stains, chinking and caulking in the industry. *Some things need to be earned.*

Complete Wood Care System

We are proud to offer wood stains, chinking and caulking designed specifically for logs, wood siding or timbers. We believe that our system of products will not only enhance the beauty of your home, but also offer unsurpassed protection and longevity. *Let us take the worry out of compatibility issues.*

We are making it easy to GO GREEN.

In a world that moves at lightning speed it is sometimes easy to forget about being socially responsible. The Weatherall Company offers a full line of environmentally friendly products that protect you, the environment and your wood structure. No longer do you need to breathe harsh chemicals to get the results that you desire. *Mother Nature would like to take this opportunity to thank you.*

WE CARE Attitude

Whether you are looking to purchase more materials or simply need advice, our goal is to make sure that you get the best customer experience. *Let us show you that CUSTOMERS do matter.*

Try Before You Buy

You've waited this long to get your dream house; why not wait a couple more days to make sure you get the colors you want? We will send you a kit that includes stain samples, caulking color charts, chinking color charts and application guides. *Knowing exactly what you want is a good thing.*



UV GUARD® DECK & FENCE WOOD FINISH

Suitable for High Foot Traffic



DECK • FENCE • ACCENTS

Extreme Exterior Wood Protection



The Perfect Stain Solution

106 Industrial Way, Charlestown, IN 47111

Honey Bee

Golden Beige

Cedar

Redwood

UV GUARD[®] Deck & Fence

WOOD FINISH

Simple and Durable Protection for All Exterior Wood Surfaces

UV Guard[®] Deck & Fence Wood Finish is a semi-transparent stain that is designed to penetrate and seal your wood surfaces. It offers excellent protection for decks, fences, accents, railings, timbers, siding and wood shingles. UV Guard[®] Deck & Fence Wood Finish is ideal for use on most types of lumber including redwood, cedar, cypress, pine and fir. There is no better choice to help maintain and protect your wood surfaces while providing a beautiful, long lasting and natural looking finish. It is available in 6 standard colors.

Why it Works

Technically speaking, UV Guard[®] Deck & Fence Wood Finish is an alkyd resin suspended in water. This combination of properties allows the stain to penetrate into your wood while forming a tough, yet breathable finish that is suitable for high foot traffic.

Features

- Easy Application
- Long Term UV Protection
- Suitable for High Foot Traffic Areas
- Penetrates and Seals
- Repels Rain & Snow
- Quick Drying
- Modest or Natural Looking Sheen
- Low VOC Formula
- Eco-Friendly
- Low Odor
- Easy Maintenance System
- Soap & Water Clean-Up

Stain Application Tips

- Don't stain in direct sunlight.
- Thoroughly stir all containers.
- If rain is imminent, do not apply finish.
- Apply stain between 40 and 90 degrees.
- Always test a stain sample on your wood.
- Always back brush stain into the pores of the wood.
- Remove mold and mildew prior to stain application.
- Make certain wood is clean, sound and dry prior to stain application.

106 Industrial Way, Charlestown, IN 47111

800-367-7068

Samples shown were finished with one coat of UV Guard® Deck & Fence Wood Finish. Actual stain colors may vary depending on application technique, wood species or wood porosity. Please contact us for samples.



Coffee