

SAFETY DATA SHEET

GRAPHENE COATING



GLASSPARENCY PRODUCTS™

SECTION 1 : IDENTIFICATION

- 1.1 Product Identifier**
Trade Name Graphene Coating
- 1.2 Relevant Identified Uses Of The Substance Or Mixture And Uses Advised Against**
Relevant Identified Uses Vehicle Coating
- 1.3 Details Of The Supplier Of The Safety Data Sheet**
GlassParency Products Inc.
185 W. Montauk Hwy
Lindenhurst NY, 11757

866-529-5999
www.glassparency.com
- 1.4 Emergency Telephone Number**
Emergency Information Service 24 Hour Emergency Number
ChemTrec Toll Free: 1(800)-424-9300
Local: 1-703-527-3887

SECTION 2 : HAZARD(S) IDENTIFICATION

- 2.1 Classification Of The Substance Or Mixture**
CLASSIFICATION ACC. TO OSHA "HAZARD COMMUNICATION STANDARD" (29 CFR 1910.1200)

SECTION	HAZARD CLASS	CATEGORY	HAZARD CLASS AND CATEGORY	HAZARD STATEMENT
A.2	Skin Corrosion/Irritation	2	Skin Irrit. 2	H315
A.3	Serious Eye Damage/Eye Irritation	1	Eye Irrit. 2	H319
A.7	Reproductive Toxicity	2	Repr. 2	H361f
B.6	Flammable Liquid	3	Flam. Liq. 3	H226

*For full text of abbreviations: see SECTION 16

THE MOST IMPORTANT ADVERSE PHYSICOCHEMICAL, HUMAN HEALTH AND ENVIRONMENTAL EFFECTS

The product is combustible and can be ignited by potential ignition sources.
The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic).
The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

- 2.2 Label Elements**
LABELING ACC. TO OSHA "HAZARD COMMUNICATION STANDARD" (29 CFR 1910.1200)

- Signal word : Danger
- Pictograms
GHS02, GHS05, GHS08



- Hazard Statements
H226 Flammable liquid and vapor.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H361f Suspected of damaging fertility.

- Precautionary Statements

P202

P210

P233

P240

P241

P242

P243

P280

P302+P352

P303+P361+P353

P305+P351+P338

P310

P321

P362

P370+P378

P403+P235

P405

P501

Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

If on skin (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous Ingredients For Labeling

Octamethylcyclotetrasiloxane, Alkyl Polysilicate

2.3 Other Hazards

HAZARDS NOT OTHERWISE CLASSIFIED

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and/or chronic).

RESULTS OF PBT AND VPVB ASSESSMENT

Containing a PBT-/vPvB-substance in a concentration of $\geq 0,1\%$.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not Relevant (Mixture)

3.2 Mixtures

DESCRIPTION OF THE MIXTURE

NAME OF SUBSTANCE	IDENTIFIER	WT%	CLASSIFICATION ACC. TO GHS
Octamethylcyclotetrasiloxane	CAS No 556-67-2	20 – < 40	Repr. 2 / H361f Flam. Liq. 3 / H226
Decamethylcyclopentasiloxane	CAS No 541-02-6	12 – < 20	Flam. Liq. 4 / H227
Ambient Temperature Curable Refractory Resin B	CAS No Not Available	12 – < 20	Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Flam. Liq. 2 / H225

NAME OF SUBSTANCE	IDENTIFIER	WT%	CLASSIFICATION ACC. TO GHS
Distillates (Petroleum) Hydrotreated, Light	CAS No 64742-47-8	3 – < 12	Asp. Tox. 1 / H304
Alkyl Polysilicate	CAS No Not Available	3 – < 12	Eye Dam. 1 / H318

HAZARDOUS INGREDIENTS, CONSIDERATION OF OTHER ADVICE

This table, if present, includes all GHS classified ingredients present above their cut-off limits, even if the finished product is not classified as hazardous by GHS. Exact percentage of ingredients is withheld as a trade secret.

For full text of abbreviations: see SECTION 16.

SECTION 4 : FIRST-AID MEASURES

4.1 Description Of First-Aid Measures

GENERAL NOTES

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

FOLLOWING INHALATION

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

FOLLOWING SKIN CONTACT

Wash with plenty of soap and water.

FOLLOWING EYE CONTACT

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

FOLLOWING INGESTION

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most Important Symptoms And Effects, Both Acute And Delayed

Symptoms and effects are not known to date.

4.3 Indication Of Any Immediate Medical Attention And Special Treatment Needed

None

SECTION 5 : FIRE-FIGHTING MEASURES

5.1 Extinguishing Media

SUITABLE EXTINGUISHING MEDIA

Water Spray, BC-Powder, Carbon Dioxide (CO₂)

UNSUITABLE EXTINGUISHING MEDIA

Water Jet

5.2 Special Hazards Arising From The Substance Or Mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

HAZARDOUS COMBUSTION PRODUCTS

Carbon Monoxide (CO), Carbon Dioxide (CO₂)

5.3 Advice For Firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, Protective Equipment And Emergency Procedures

FOR NON-EMERGENCY PERSONNEL

Remove persons to safety.

FOR EMERGENCY RESPONDERS

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental Precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods And Material For Containment And Cleaning Up

ADVICE ON HOW TO CONTAIN A SPILL

Covering of drains.

ADVICE ON HOW TO CLEAN UP A SPILL

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder.

APPROPRIATE CONTAINMENT TECHNIQUES

Use of adsorbent materials.

OTHER INFORMATION RELATING TO SPILLS AND RELEASES

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference To Other Sections

Hazardous combustion products: see section 5.

Personal protective equipment: see section 8.

Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7 : HANDLING AND STORAGE

7.1 Precautions For Safe Handling

RECOMMENDATIONS

- Measures To Prevent Fire As Well As Aerosol And Dust Generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific Notes/Details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

ADVICE ON GENERAL OCCUPATIONAL HYGIENE

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions For Safe Storage, Including Any Incompatibilities

MANAGING OF ASSOCIATED RISKS

- Explosive Atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability Hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- **Ventilation Requirements**
Use local and general ventilation. Ground/bond container and receiving equipment.
- **Packaging Compatibilities**
Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific End Use(s)

See section 16 for a general overview.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control Parameters

This information is not available.

RELEVANT DNELs OF COMPONENTS OF THE MIXTURE						
NAME OF SUBSTANCE	CAS NO	ENDPOINT	THRESHOLD LEVEL	PROTECTION GOAL, ROUTE OF EXPOSURE	USED IN	EXPOSURE TIME
Octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m ³	Human, Inhalatory	Worker (Industry)	Chronic - Systemic Effects
Octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m ³	Human, Inhalatory	Worker (Industry)	Acute - Systemic Effects
Octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m ³	Human, Inhalatory	Worker (Industry)	Chronic - Local Effects
Octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m ³	Human, Inhalatory	Worker (Industry)	Acute - Local Effects
Decamethylcyclopentasiloxane	541-02-6	DNEL	97.3 mg/m ³	Human, Inhalatory	Worker (Industry)	Chronic - Systemic Effects
Decamethylcyclopentasiloxane	541-02-6	DNEL	97.3 mg/m ³	Human, Inhalatory	Worker (Industry)	Acute - Systemic Effects
Decamethylcyclopentasiloxane	541-02-6	DNEL	24.2 mg/m ³	Human, Inhalatory	Worker (Industry)	Chronic - Local Effects
Decamethylcyclopentasiloxane	541-02-6	DNEL	24.2 mg/m ³	Human, Inhalatory	Worker (Industry)	Acute - Local Effects

RELEVANT PNECs OF COMPONENTS OF THE MIXTURE						
NAME OF SUBSTANCE	CAS NO	ENDPOINT	THRESHOLD LEVEL	ORGANISM	ENVIRONMENTAL COMPARTMENT	EXPOSURE TIME
Octamethylcyclotetrasiloxane	556-67-2	PNEC	10 mg/l	Microorganisms	Sewage Treatment Plant (STP)	Short-Term (Single Instance)
Octamethylcyclotetrasiloxane	556-67-2	PNEC	0.059 mg/kg	Pelagic Organisms	Sediment	Short-Term (Single Instance)
Octamethylcyclotetrasiloxane	556-67-2	PNEC	1.7 mg/kg	(Top) Predators	Water	Short-Term (Single Instance)
Octamethylcyclotetrasiloxane	556-67-2	PNEC	0.44 µg/L	Aquatic Organisms	Freshwater	Short-Term (Single Instance)

NAME OF SUBSTANCE	CAS NO	ENDPOINT	THRESHOLD LEVEL	ORGANISM	ENVIRONMENTAL COMPARTMENT	EXPOSURE TIME
Octamethylcyclotetrasiloxane	556-67-2	PNEC	0.044 µg/l	Aquatic Organisms	Marine Water	Short-Term (Single Instance)
Octamethylcyclotetrasiloxane	556-67-2	PNEC	10 mg/l	Aquatic Organisms	Sewage Treatment Plant (STP)	Short-Term (Single Instance)
Octamethylcyclotetrasiloxane	556-67-2	PNEC	3 mg/kg	Aquatic Organisms	Freshwater Sediment	Short-Term (Single Instance)
Octamethylcyclotetrasiloxane	556-67-2	PNEC	0.3 mg/kg	Aquatic Organisms	Marine Sediment	Short-Term (Single Instance)
Octamethylcyclotetrasiloxane	556-67-2	PNEC	0.59 mg/kg	Benthic Organisms	Sediment	Short-Term (Single Instance)
Octamethylcyclotetrasiloxane	556-67-2	PNEC	0.16 mg/kg	Terrestrial Organisms	Soil	Short-Term (Single Instance)
Decamethylcyclopentasiloxane	556-67-2	PNEC	10 mg/l	Microorganisms	Sewage Treatment Plant (STP)	Short-Term (Single Instance)
Decamethylcyclopentasiloxane	556-67-2	PNEC	11 mg/kg	Benthic Organisms	Sediment	Short-Term (Single Instance)
Decamethylcyclopentasiloxane	556-67-2	PNEC	13 mg/kg	(Top) Predators	Water	Short-Term (Single Instance)
Decamethylcyclopentasiloxane	556-67-2	PNEC	1.1 mg/kg	Pelagic Organisms	Sediment	Short-Term (Single Instance)
Decamethylcyclopentasiloxane	556-67-2	PNEC	1.2 µg/l	Aquatic Organisms	Freshwater	Short-Term (Single Instance)
Decamethylcyclopentasiloxane	556-67-2	PNEC	0.12 µg/l	Aquatic Organisms	Marine Water	Short-Term (Single Instance)
Decamethylcyclopentasiloxane	556-67-2	PNEC	10 mg/l	Aquatic Organisms	Sewage Treatment Plant (STP)	Short-Term (Single Instance)
Decamethylcyclopentasiloxane	556-67-2	PNEC	11 mg/kg	Aquatic Organisms	Freshwater Sediment	Short-Term (Single Instance)
Decamethylcyclopentasiloxane	556-67-2	PNEC	1.1 mg/kg	Aquatic Organisms	Marine Sediment	Short-Term (Single Instance)
Decamethylcyclopentasiloxane	112-34-5	PNEC	1.27 mg/kg	Terrestrial Organisms	Soil	Short-Term (Single Instance)

8.2 Exposure Controls

APPROPRIATE ENGINEERING CONTROLS

General ventilation.

INDIVIDUAL PROTECTION MEASURES (PERSONAL PROTECTIVE EQUIPMENT)

Eye/Face Protection

Wear eye/face protection.

SKIN PROTECTION

• Hand Protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

• Other Protection Measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

RESPIRATORY PROTECTION

In case of inadequate ventilation wear respiratory protection.

ENVIRONMENTAL EXPOSURE CONTROLS

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information On Basic Physical And Chemical Properties

Appearance

PHYSICAL STATE	Liquid
COLOR	Grey
ODOR	Characteristic

Other Safety Parameters

PH (VALUE)	Not Determined
MELTING POINT/ FREEZING POINT	Not Determined
INITIAL BOILING POINT AND BOILING RANGE	>65 °C at 1 atm
FLASH POINT	55 °C at 101.3 kPa 131 °F at 760 mmHg Closed Cup
EVAPORATION RATE	Not Determined
FLAMMABILITY (SOLID, GAS)	Not Relevant, (Fluid)

Explosive Limits

LOWER EXPLOSION LIMIT (LEL)	0.6 vol%
UPPER EXPLOSION LIMIT (UEL)	4.9 vol%

Explosive Limits Continued

VAPOR PRESSURE	132 Pa at 25 °C
DENSITY	Not Determined
VAPOR DENSITY	This Information Is Not Available
RELATIVE DENSITY	Information On This Property Is Not Available
SOLUBILITY	Not Determined

Partition Coefficient

N-OCTANOL/WATER (LOG KOW)	This Information Is Not Available
AUTO-IGNITION TEMPERATURE	262 °C (Auto-Ignition Temperature (Liquids And Gases))
VISCOSITY	Not Determined
EXPLOSIVE PROPERTIES	None
OXIDIZING PROPERTIES	None
TEMPERATURE CLASS (USA, ACC. TO NEC 500)	T2B (Maximum Permissible Surface Temperature On The Equipment: 260°C)

SECTION 10 : STABILITY AND REACTIVITY

- 10.1 Reactivity**
Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.
If Heated : Risk Of Ignition
- 10.2 Chemical Stability**
See below "Conditions to avoid".
- 10.3 Possibility Of Hazardous Reactions**
No known hazardous reactions.
- 10.4 Conditions To Avoid**
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

HINTS TO PREVENT FIRE OR EXPLOSION
Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.
- 10.5 Incompatible Materials**
Oxidizers
- 10.6 Hazardous Decomposition Products**
Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11 : TOXICOLOGICAL INFORMATION

- 11.1 Information On Toxicological Effects**
Test data are not available for the complete mixture.

CLASSIFICATION PROCEDURE

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

ACUTE TOXICITY

Shall not be classified as acutely toxic.

ACUTE TOXICITY ESTIMATE (ATE) OF COMPONENTS OF THE MIXTURE

NAME OF SUBSTANCE	CAS NO	EXPOSURE ROUTE	ATE
Ambient Temperature Curable Refractory Resin B	Not Available	Oral	500 mg/kg

SKIN CORROSION/IRRITATION

Causes skin irritation.

SERIOUS EYE DAMAGE/EYE IRRITATION

Causes serious eye damage.

RESPIRATORY OR SKIN SENSITIZATION

Shall not be classified as a respiratory or skin sensitizer.

GERM CELL MUTAGENICITY

Shall not be classified as germ cell mutagenic.

CARCINOGENICITY

Shall not be classified as carcinogenic.

REPRODUCTIVE TOXICITY

Suspected of damaging fertility.

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE

Shall not be classified as a specific target organ toxicant (single exposure).

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE

Shall not be classified as a specific target organ toxicant (repeated exposure).

ASPIRATION HAZARD

Shall not be classified as presenting an aspiration hazard.

SECTION 12 : ECOLOGICAL INFORMATION

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

AQUATIC TOXICITY (ACUTE) OF COMPONENTS OF THE MIXTURE					
NAME OF SUBSTANCE	CAS NO	END POINT	VALUE	SPECIES	EXPOSURE TIME
Octamethylcyclotetrasiloxane	556-67-2	LC50	>22 µg/l	Fish	96 h
Octamethylcyclotetrasiloxane	556-67-2	EC50	>1,000 mg/l	Aquatic Invertebrates	96 h
Decamethylcyclopentasiloxane	541-02-6	LC50	>16 µg/l	Fish	96 h
Decamethylcyclopentasiloxane	541-02-6	EC50	>2.9 µg/l	Aquatic Invertebrates	48 h
AQUATIC TOXICITY (CHRONIC) OF COMPONENTS OF THE MIXTURE					
NAME OF SUBSTANCE	CAS NO	END POINT	VALUE	SPECIES	EXPOSURE TIME
Octamethylcyclotetrasiloxane	556-67-2	LC50	10 µg/l	Fish	14 d
Octamethylcyclotetrasiloxane	556-67-2	EC50	>500 mg/l	Aquatic Invertebrates	24 h
Decamethylcyclopentasiloxane	541-02-6	LC50	>16 µg/l	Fish	14 d
Decamethylcyclopentasiloxane	541-02-6	EC50	>15 µg/l	Aquatic Invertebrates	21 d

12.2 Persistence And Degradability

Data are not available.

12.3 Bioaccumulative Potential

The substance fulfills the very bioaccumulative criterion.

12.4 Mobility In Soil

Data are not available.

12.5 Results Of PBT And vPvB Assessment

The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic).

The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

12.6 Other Adverse Effects

ENDOCRINE DISRUPTING POTENTIAL

The mixture contains substance(s) with an endocrine disrupting potential.

SECTION 13 : DISPOSAL CONSIDERATIONS

13.1 Waste Treatment Methods

WASTE TREATMENT-RELEVANT INFORMATION

Solvent reclamation/regeneration.

SEWAGE DISPOSAL-RELEVANT INFORMATION

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

WASTE TREATMENT OF CONTAINERS/PACKAGES

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks



Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14 : TRANSPORT INFORMATION

14.1	UN Number	1993
14.2	UN Proper Shipping Name Technical Name (Hazardous Ingredients)	Flammable Liquid, n.o.s. Octamethylcyclotetrasiloxane, Ambient Temperature Curable Refractory Resin B
14.3	Transport Hazard Class(es) Class	3 (Flammable Liquids)
14.4	Packing Group	III (Substance Presenting Low Danger)
14.5	Environmental Hazards Environmentally Hazardous Substance (Aquatic Environment)	Hazardous To The Aquatic Environment Decamethylcyclopentasiloxane
14.6	Special Precautions For User There Is No Additional Information.	
14.7	Transport In Bulk According To Annex II Of MARPOL And The IBC Code The cargo is not intended to be carried in bulk.	

Information For Each Of The UN Model Regulations

Transport Of Dangerous Goods By Road Or Rail (49 CFR US DOT)

Index Number	1993
Proper Shipping Name	Flammable Liquid, n.o.s.
• Particulars In The Shipper's Declaration	UN1993, Flammable liquid, n.o.s., (contains: octamethylcyclotetrasiloxane, ambient temperature curable refractory resin B), 3, III, environmentally hazardous
• Reportable Quantity (RQ)	5,725,351 lbs (2,599,309 kg) (ethanol)
Class	3
Packing Group	III
Danger Label(s)	3, Fish And Tree
 	
Environmental Hazards	Yes (Hazardous To The Aquatic Environment)
Special Provisions (SP)	B1, B52, IB3, T4, TP1, TP29
ERG No	128

International Maritime Dangerous Goods Code (IMDG)

UN Number 1993
Proper Shipping Name Flammable Liquid, n.o.s.
Class 3
Marine Pollutant Yes (Hazardous To The Aquatic Environment)
Packing Group III
Danger Label(s) 3, Fish and Tree



Special Provisions (SP) 223, 274, 955
Excepted Quantities (EQ) E1
Limited Quantities (LQ) 5 L
EmS F-E, S-E
Stowage Category A

International Civil Aviation Organization (ICAO-IATA/DGR)

UN Number 1993
Proper Shipping Name Flammable Liquid, n.o.s.
Class 3
Environmental Hazards Yes (Hazardous To The Aquatic Environment)
Packing Group III
Danger Label(s) 3



Special Provisions (SP) A3
Excepted Quantities (EQ) E1
Limited Quantities (LQ) 10 L

SECTION 15 : REGULATORY INFORMATION

15.1 Safety, Health And Environmental Regulations Specific For The Product In Question

National Regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302,304)
None Of The Ingredients Are Listed

Clean Air Act

None Of The Ingredients Are Listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

NAME OF SUBSTANCE	CAS NO	FUNCTIONALITY	AUTHORITATIVE LISTS
Octamethylcyclotetrasiloxane	556-67-2	Solvents	Canada PBTs CECBP - Priority Chemicals EC PBTs
Ambient Temperature Curable Refractory Resin B	Not Available	Refractory Resin	
Decamethylcyclopentasiloxane	541-02-6	Solvents	Canada PBTs CECBP - Priority Chemicals EC PBTs
Distillates (Petroleum) Hydrotreated, Light	64742-47-8	Solvents	
Alkyl Polysilicate	Not Available	Resin	
Fluorine Modified Silicone Fluid	115361-68-7	Surface Modifier	

NAME OF SUBSTANCE	CAS NO	FUNCTIONALITY	AUTHORITATIVE LISTS
Trimethylsiloxysilicate	68988-56-7	Resin	
Polydimethylsiloxane	63148-62-9	Surface Modifier	
Polytrimethylhydrosilylsiloxane	68988-56-7	Surface Modifier	
Tetra(trimethylsiloxy)silane	3555-47-3	Surface Modifier	Canada PBiTs
Methanol	67-56-1	Alcohols	CA TACs NTP OHAT - Repr. or Dev. Toxicants OEHA RELS Prop 65

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

PROPOSITION 65 LIST OF CHEMICALS					
NAME OF SUBSTANCE	NAME ACC. TO INVENTORY	CAS NO	WT%	REMARKS	TYPE OF THE TOXICITY
Methanol	Methanol	67-56-1	0.08733		Developmental

VOC Content

- Regulated Volatile Organic Compounds (VOC-EPA) 0.08733 %
- Regulated Volatile Organic Compounds (VOC-Cal ARB) 0.08733 %

Industry Or Sector Specific Available Guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

CATEGORY	RATING	DESCRIPTION
Chronic	*	Chronic (Long-Term) Health Effects May Result From Repeated Overexposure
Health	3	Major Injury Likely Unless Prompt Action Is Taken And Medical Treatment Is Given
Flammability	2	Material That Must Be Moderately Heated Or Exposed To Relatively High Ambient Temperatures Before Ignition Can Occur
Physical Hazard	0	Material That Is Normally Stable, Even Under Fire Conditions, And Will Not React With Water, Polymerize, Decompose, Condense, Or Self-React. Non-Explosive
Personal Protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

CATEGORY	DEGREE OF HAZARD	DESCRIPTION
Flammability	2	Material That Must Be Moderately Heated Or Exposed To Relatively High Ambient Temperatures Before Ignition Can Occur
Health	3	Material That, Under Emergency Conditions, Can Cause Serious Or Permanent Injury
Instability	0	Material That Is Normally Stable, Even Under Fire Conditions
Special Hazard		

National Inventories

COUNTRY	INVENTORY	STATUS
CA	DSL	Not All Ingredients Are Listed
CA	NDSL	Not All Ingredients Are Listed
EU	REACH Reg.	Not All Ingredients Are Listed
US	TSCA	Not All Ingredients Are Listed

Legend

DSL	Domestic Substances List (DSL)
NDSL	Non-Domestic Substances List (NDSL)
REACH Reg.	REACH Registered Substances
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16 : OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Abbreviations And Acronyms

ABBR.	DESCRIPTIONS OF USED ABBREVIATIONS
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACUTE TOX	Acute Toxicity
ASP. TOX.	Aspiration Hazard
ATE	Acute Toxicity Estimate
CAL ARB	California Air Resources Board
CAS	Chemical Abstracts Service (Service That Maintains The Most Comprehensive List Of Chemical Substances)
DGR	Dangerous Goods Regulations (See IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50%. The EC50 Corresponds To The Concentration Of A Tested Substance Causing 50% Changes In Response (e.g. On Growth) During A Specified Time Interval
EMS	Emergency Schedule
EPA	Environmental Protection Agency. An Agency Of The Federal Government Of The United States Charged With Protecting Human Health And The Environment
ERG NO	Emergency Response Guidebook - Number
EYE DAM.	Seriously Damaging To The Eye
EYE IRRIT.	Irritant To The Eye
FLAM. LIQ.	Flammable Liquid
GHS	"Globally Harmonized System Of Classification And Labeling Of Chemicals" Developed By The United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) For The Air Transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: The Lc50 Corresponds To The Concentration Of A Tested Substance Causing 50% Lethality During A Specified Time Interval

MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative And Toxic
PNEC	Predicted No-Effect Concentration
REPR.	Reproductive Toxicity
RTECS	Registry Of Toxic Effects Of Chemical Substances (Database Of NIOSH With Toxicological Information)
SKIN CORR.	Corrosive To Skin
SKIN IRRIT.	Irritant To Skin
VOC	Volatile Organic Compounds
VPVB	Very Persistent And Very Bioaccumulative

Key Literature References And Sources For Data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT).

International Maritime Dangerous Goods Code (IMDG).

Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification Procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List Of Relevant Phrases (Code And Full Text As Stated In Chapter 2 And 3)

CODE	TEXT
H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H361F	Suspected of damaging fertility.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.