


INSTALLATION MANUAL

RIVAL

UP-TO-DATE
MANUAL



PRODUCT: FRONT CONTROL ARM SKID PLATES
APPLICATION: TESLA CYBERTRUCK (2023-PRESENT)
PART NO: 2333.4902.1.6



CAUTION!

To reduce the risk of serious injury or damage to property: Before you start installing and using this product, read the full instructions, pay special attention to the conditions of safe use and recommendations for installation! When installing or maintaining this product, it is necessary to use protective goggles. Check the integrity of the installed components and torque all hardware every 250 miles (400 kms). Discontinue use if there is any damage to the structure or fasteners!

NOTICE

Skid plates are supplemental protection. We cannot guarantee protection against all possible damage from impacts. When driving, be careful of objects and terrain that may damage sensitive parts of the vehicle.

FRONT CONTROL ARM SKID PLATES

RIVAL

Part number: 2333.4902.1.6

Suited to vehicle: Tesla Cybertruck AWD (2023-Present)
Tesla Cybertruck Cyberbeast AWD
(2023-Present)

Material: Aluminum



SAFETY NOTICE

- * The RIVAL skid plate is designed to complement the use and design of the specified vehicle under conditions underlined by the vehicle manufacturer.
- * While driving the vehicle at any speed, collision with another vehicle, animal or object must always be avoided.
- * Following any collision with another vehicle, animal or object, the RIVAL skid plate and the vehicle must be inspected by a specialized or suitably qualified vehicle technician for possible damage to the components and assemblies in order to confirm suitability for further use of the vehicle.
- * It is strongly recommended that you do not operate a vehicle with a damaged skid plate or its components. In the case of damage, please contact the nearest RIVAL dealer. A damaged vehicle or skid plate is extremely dangerous and should be avoided at all cost.
- * We recommend using a funnel when changing the oil to prevent spills and ensure a clean process.

INSTALLATION NOTICE


- * The RIVAL skid plate must be mounted to the vehicle according to this installation manual.
- * Personal safety during the installation process must be adhered to at all times.
- * Do not install this skid plate on vehicle models other than those listed in this manual.
- * Estimated time for installation: 1 hour.
- * It's good practice to use a tap on all included hardware and bracketry to ensure ease of final assembly.

REQUIRED TOOLS


- * Basic tool kit
- * Torque wrench

TORQUE SETTING

- * M6 - 9 Nm (6.6 lb/ft)



- 1. Left front control arm skid plate.....Qty 1
- 2. Right front control arm skid plate.....Qty 1



- A. Bolt M6x1x25.....Qty 6
- B. Washer M6.....Qty 6
- C. Washer M8.....Qty 6

INSTALLATION PROCEDURE

RIVAL

***If equipped, remove factory or any aftermarket skid plates that may interfere with installation.**




Fig. 1

1. Install the right front control arm skid plate (item 2) using M6x25 bolts with M6 & M8 washers (item A,B,C) as shown in fig.1.

***Tighten hardware.**




Fig. 2

2. Install the left front control arm skid plate (item 1) using M6x25 bolts with M6 & M8 washers (item A,B,C) as shown in in fig.2.

***Tighten hardware.**

Before operating a vehicle fitted with RIVAL Skid Plate:

- Make sure all hardware is torqued.
- Ensure the integrity of the structure and all its components.

