



# Trimble DiNi

## DIGITAL LEVEL

The Trimble® DiNi® Digital Level is a digital height measurement sensor from Trimble's Integrated Surveying™ portfolio of products. The Trimble DiNi is a field-proven tool designed for any job site where fast and accurate height determination is required. Use the Trimble DiNi for applications such as precise leveling of flat and sloping surfaces, establishing the vertical component of grade and ground profiles, subsidence monitoring, and establishing the vertical component of control networks.

### UNEQUALLED FOR PERFORMANCE IN THE FIELD

The Trimble DiNi is designed to perform optimally every day, whatever your surveying job. It is built rugged—with a dust- and waterproof rating of IP55—to take the tough conditions of the job site in its stride. A backlight in the screen and a light in the circular bubble keep you productive even when daylight gets low.

The DiNi will operate for three days without requiring a battery change, then when it does just recharge it as you would your Trimble GNSS system battery...the batteries are the same to ensure convenience and productivity.

When a job is complete, easily transfer data from the instrument to a computer by using a USB storage device; You don't have to carry your instrument in to the office.

### EASY TO LEARN, EASY TO USE

The Trimble DiNi Digital Level demands the industry's smallest measurement field—just 30 cm of code rod. So you can measure greater change in height between the level and the rod in one setup, and save time. Additionally, the small measurement area:

- ▶ reduces the number of stations needed by up to 20% because the Trimble DiNi is less impacted by a rod hidden by vegetation or hilly terrain.
- ▶ makes leveling in low light conditions, for example, in tunnels, easier because only a very small part of the staff needs to be illuminated.
- ▶ ensures greater accuracy through less influence of refraction near the ground.

The large graphical display of the Trimble DiNi is also unique, and is complemented by the latest Trimble keyboard for easy operation. Crew members used to operating other Trimble systems will easily adapt to the Trimble DiNi.

### TRIMBLE QUALITY AND ACCURACY FOR MEASURING WITH CONFIDENCE

The Trimble DiNi Digital Level is designed to support the rest of Trimble's Integrated Surveying portfolio. The Trimble DiNi interface is based on Trimble's other advanced and field-proven controllers for easy adoption of the instrument by your crews. Proven Optics by Carl Zeiss ensure the Trimble DiNi offers the highest precision and best resolution.

Measure with confidence, knowing that with the Trimble DiNi Digital Level, your crew will obtain the best quality results with the highest level of productivity.

### Key Features

- ▶ Determine accurate height information via a quick and easy key press
- ▶ Eliminate errors and reduce rework with digital readings
- ▶ Enjoy effortless data transfer between instrument and office
- ▶ Measure to a measurement field of just 30 cm
- ▶ Level 60% faster than with conventional automatic leveling



## PERFORMANCE SPECIFICATIONS

Accuracy..... ISO 17123-2, standard deviation height measuring per 1 km (3280.84 ft) of double leveling

### Trimble DiNi 0.3 mm per km

Electronic measurement  
 Invar precision bar code staff ..... 0.3 mm (0.001 ft)  
 Standard bar code staff ..... 1.0 mm (0.004 ft)  
 Visual measurement ..... 1.5 mm (0.005 ft)  
 Distance measurement ..... with a 20 m (65.62 ft) sighting distance  
 Invar precision bar code staff ..... 20 mm (0.066 ft)  
 Standard bar code staff ..... 25 mm (0.082 ft)  
 Visual measurements ..... 0.2 m (0.656 ft)

### Trimble DiNi 0.7 mm per km

Electronic measurement  
 Invar precision bar code staff ..... 0.7 mm (0.002 ft)  
 Standard bar code staff ..... 1.3 mm (0.004 ft)  
 Visual measurement ..... 2.0 mm (0.007 ft)  
 Distance measurement ..... with a 20 m (65.62 ft) sighting distance  
 Invar precision bar code staff ..... 25 mm (0.082 ft)  
 Standard bar code staff ..... 30 mm (0.098 ft)  
 Visual measurement ..... 0.3 m (0.984 ft)

### Range

Electronic measurement ..... 1.5 m–100 m (4.92 ft–328.08 ft)  
 Visual measurement ..... from 1.3 m (4.265 ft)

### Electronic measurement

**Trimble DiNi 0.3 mm per km**  
 Resolution height measurement ..... 0.01 mm / 0.0001 ft / 0.0001 in  
 Resolution distance measurement ..... 1 mm (0.003 ft)  
 Measurement time ..... 3 s

**Trimble DiNi 0.7 mm per km**  
 Resolution height measurement ..... 0.1 mm / 0.001 ft / 0.001 in  
 Resolution distance measurement ..... 10 mm (0.033 ft)  
 Measurement time ..... 2 s

### Horizontal Circle

Type of graduation ..... 400 grads and 360 deg  
 Graduation interval ..... 1 grad and 1 deg  
 Estimation to ..... 0.1 grad and 0.1 deg

### Measurement Programs

**Trimble DiNi 0.3 mm per km**  
 Standard programs ..... Single measurement with and without stationing, stakeout, line leveling with intermediate sight and stakeout, line adjustment  
 Leveling methods<sup>1</sup> ..... BF, BFFB, BFBF, BBFF, FBBF, aBF, aBFFB, aBFBF, aBBFF, aFBBF

**Trimble DiNi 0.7 mm per km**  
 Standard programs ..... Single measurement with and without stationing, stakeout, line leveling with intermediate sight and stakeout  
 Leveling methods ..... BF, BFFB, aBF, aBFFB

## ENVIRONMENTAL

Operating temperature ..... –20 °C to +50 °C (–4 °F to 122 °F)  
 Dust- and waterproofing ..... IP55

## GENERAL SPECIFICATION

**Telescope**  
 Aperture ..... 40 mm (0.131 ft)  
 Field of view at 100 m ..... 2.2 m (7.217 ft)  
 Electronic measurement field ..... 0.3 m (0.984 ft)  
**Magnification**  
 Trimble DiNi 0.3 mm per km ..... 32 x  
 Trimble DiNi 0.7 mm per km ..... 26 x

**Compensator**  
 Inclination range ..... ±15'  
 Setting accuracy  
 Trimble DiNi 0.3 mm per km ..... ±0.2"  
 Trimble DiNi 0.7 mm per km ..... ±0.5"  
 Circular level ..... 8/2 mm with illumination

Display ..... Graphical, 240 x 160 pixels, monochrome with illumination

Keyboard ..... 19-key alpha-numeric and 4-way arrow key for navigation\


**Recording**  
 Internal memory ..... up to 30 000 data lines  
 External memory ..... USB Flash Drive support  
 Data transfer ..... USB Interface for data transfer between DiNi and PC (means two way communication)

Real-time clock and temperature sensor  
 Trimble DiNi 0.3 mm per km ..... Recording of time or temperature  
 Trimble DiNi 0.7 mm per km ..... N.A.

**Power supply**  
 Internal battery ..... Li-Ion, 7.4 V / 2.4 Ah  
 Operating time ..... 3 days working time without illumination  
 Weight (including battery) ..... 3.5 kg (7.72 lb)

<sup>1</sup> F = Foresight, B = Backsight, a = alternating  
 Certified quality in accordance with DIN ISO 9001/EN 29001

Specifications subject to change without notice.



**Vectors Inc.**  
**VectorsInc.com**  
 Contact your local Trimble Authorized Distribution Partner for more information

Vectors Colorado - (303) 283-0343  
 10670 East Bethany Drive, Building 4  
 Aurora, CO 80014

Vectors New Mexico - (505) 821-0343  
 5640 Venice Avenue, Unit J  
 Albuquerque, NM 87113

**NORTH AMERICA**  
 Trimble Inc.  
 10368 Westmoor Dr  
 Westminster CO 80021  
 USA

**EUROPE**  
 Trimble Germany GmbH  
 Am Prime Parc 11  
 65479 Raunheim  
 GERMANY

**ASIA-PACIFIC**  
 Trimble Navigation  
 Singapore PTE Limited  
 3 HarbourFront Place  
 #13-02 HarbourFront Tower Two  
 Singapore 099254  
 SINGAPORE