Trimble Data Link Radio 2.4 GHz

Key Features

Compatible with multiple platforms: Android, Microsoft® Windows & Windows Mobile (WEHH)

IP54 environmental protection and MIL-STD-810G ruggedness

Bluetooth® connectivity



A BLUETOOTH TO RADIO SOLUTION FOR YOUR ROBOTIC ENABLED TOTAL STATIONS

The Trimble® Data Link Radio (TDL) 2.4 GHz is a rugged, lightweight, custom accessory designed to allow communication between Trimble robotic-enabled total stations and Bluetooth-enabled mobile devices. The TDL radio will connect via Bluetooth to a field controller and allow that controller to communicate with a Trimble total station—providing seamless integration to robotic total stations through a wider range of data collectors—without compromising range or robotic functionality.

POWER

Battery type	Field replaceable Lithium-Ion pack (rechargeable inside unit or on its own)
Battery capacity	5200 mAh Li-lor	1
Battery life	36 hours	;
Charging time	5 hours (typical, with supplied charger)

Temperature (MIL-STD-810G) Operation
Storage. —30 °C to +70 °C Drop shock — MIL-STD-810G Method 516.5 Procedure IV 1.2 m to plywood over concrete Functional shock — MIL-STD-810 Method 516.6 Procedure I Vibration — MIL-STD-810 Method 514.5 Procedure I, Category 24 Humidity — MIL-STD-810G Method 507.6 (95% non-condensing) Altitude rating (MIL-STD-810G Method 500.5)
Drop shock MIL-STD-810G Method 516.5 Procedure IV 1.2 m to plywood over concrete Functional shock MIL-STD-810 Method 516.6 Procedure I Vibration MIL-STD-810G Method 514.5 Procedure I, Category 24 Humidity MIL-STD-810G Method 507.6 (95% non-condensing) Altitude rating (MIL-STD-810G Method 500.5)
Drop shock MIL-STD-810G Method 516.5 Procedure IV 1.2 m to plywood over concrete Functional shock MIL-STD-810 Method 516.6 Procedure I Vibration MIL-STD-810G Method 514.5 Procedure I, Category 24 Humidity MIL-STD-810G Method 507.6 (95% non-condensing) Altitude rating (MIL-STD-810G Method 500.5)
Functional shock
Vibration
Humidity
Altitude rating (MIL-STD-810G Method 500.5)
Maximum storage altitude
Maximum storage attitude
Maximum operational altitude9,000 m
Chemical exposure MIL-STD-810 Method 504.1 Procedure I
Salt mist
Compliance

MECHANICAL

Ingress protection rating	
Weight	
Power connector	Micro-B USB female (charging and firmware update)
External antenna connector	SMB female

STANDARD ACCESSORIES

- USB cable
- International charging kit
- Antenna
- Pole clip
- Li-lon battery

OPTIONAL ACCESSORIES

- Belt pouch/clip
- Pole clip
- External battery charger

Specifications subject to change without notice



© 2015, Trimble Navigation Limited. All rights reserved. Trimble and the Globe & Triangle logo are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Navigation Limited is under license. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. All other trademarks are the property of their respective owners. PN 022516-208 (09/15)



Vectors Colorado - (303) 283-0343 10670 East Bethany Drive, Building 4 Aurora, CO 80014

Vectors New Mexico - (505) 821-0343 5640 Venice Avenue, Unit J Albuquerque, NM 87113

TRIMBLE AUTHORIZED DISTRIBUTION PARTNER

NORTH AMERICA

Trimble Navigation Limited 10368 Westmoor Dr Westminster CO 80021 USA

EUROPE

Trimble Germany GmbH Am Prime Parc 11 65479 Raunheim GERMANY

ASIA-PACIFIC

Trimble Navigation Singapore Pty Limited 80 Marine Parade Road #22-06, Parkway Parade Singapore 449269 SINGAPORE

