



Trimble R10 LT

GNSS SYSTEM

A NEW LEVEL OF PRODUCTIVITY NOW AND IN THE FUTURE

The Trimble® R10 LT GNSS System includes powerful technologies like Trimble HD-GNSS and Trimble 360 for remarkably fast convergence and positioning accuracy integrated into the Trimble R10 ergonomic and lightweight design, this unique system provides Surveyors with a powerful way to increase productivity in every job, every day.

The Trimble R10 LT offers upgrade options to scale up to provide Trimble SurePoint™, for tilt compensation; Trimble xFill™ for seamless RTK level accuracy even with correction stream interruptions; and Trimble CenterPoint™ RTX for satellite and internet corrections extended indefinitely.

Trimble HD-GNSS Processing Engine

The next generation of core positioning technology
The advanced Trimble HD-GNSS processing engine provides markedly reduced convergence times as well as high position and precision reliability while reducing measurement occupation time. Transcending traditional fixed/float techniques, it provides a more accurate assessment of error estimates than traditional GNSS technology.

Trimble 360 Receiver

Future Proof Your Investment

Powerful Trimble 360 receiver technology in the Trimble R10 supports signals from all existing and planned GNSS constellations and augmentation systems. With two integrated Trimble Maxwell™ 6 chips, the Trimble R10 offers an unparalleled 440 GNSS channels. Trimble delivers business confidence with a sound GNSS investment for today and long into the future.

Ergonomically Designed

As the smallest and lightest integrated receiver in its class, the Trimble R10 is ergonomically designed to provide the surveyor with effortless handling and operation. Designed for ease of use, the progressive design incorporates a more stable center of mass at the top of the range pole, while its sleeker, taller profile provides the durability and reliability for which Trimble is known.

The Trimble R10 receiver incorporates a quick release adaptor for simple and safe removal of the receiver from the range pole. Additionally the quick release adaptor ensures a solid, stable connection between the range pole and receiver.

An Intelligent Solution

A smart lithium-ion battery inside the Trimble R10 system delivers extended battery life and more reliable power. A built-in LED battery status indicator allows the user to quickly check remaining battery life.

Advanced Communication Capabilities

The Trimble R10 system provides a number of communications options to support any workflow. The latest mobile phone technology is built in to receive VRS corrections and connect to the Internet from the field. Access Trimble Connected Community to send or receive documents while away from the office. Using WiFi, easily connect to the Trimble R10 system using a laptop or smartphone to configure the receiver without a Trimble controller.

The Complete Solution: Trimble Hardware and Software

Bring the power and speed of the Trimble R10 system together with trusted Trimble software solutions, including Trimble Access™ and Trimble Business Center™. Trimble Access field software provides specialized and customized workflows to make surveying tasks quicker and easier while enabling teams to communicate vital information between field and office in real time. Back in the office, users can seamlessly process data with Trimble Business Center software.

The R10 LT GNSS system, providing scalability for professional surveyors.

Optional Upgrades

Trimble Surepoint - The system constantly monitors and compensates for pole tilt. If a point is measured with pole tilt beyond a user-defined setting, Trimble Access™ software will give an alert and prompt the surveyor to accept or discard the point. Also, the Trimble R10 will record the pole tilt information for measured points. These records include tilt and compass data for 100% data traceability.

Trimble Centerpoint RTX - Trimble CenterPoint RTX delivers RTK level precision anywhere in the world without the use of a local base station or Trimble VRS™ Network. Survey using satellite delivered, CenterPoint RTX corrections in areas where terrestrial based corrections are not available. When surveying over a great distance in a remote area, CenterPoint RTX eliminates the need to continuously move base station or maintain connection to a cellular network.

Trimble xFill - Leveraging a worldwide network of Trimble GNSS reference stations and satellite datalinks, Trimble xFill seamlessly fills in for gaps in your RTK or VRS connection stream. Extend xFill indefinitely with a subscription to CenterPoint RTX.

Key Features

- ▶ Cutting-edge Trimble HD-GNSS processing engine
- ▶ Advanced satellite tracking with Trimble 360 receiver technology
- ▶ A scalable Trimble R10 receiver that can grow with your business
- ▶ All the essential features for GNSS surveying are included
- ▶ Scale up the solution later with optional features that include: Trimble SurePoint, xFill, CenterPoint RTX Technologies
- ▶ Sleek ergonomic design for easier handling



Trimble R10 LT GNSS SYSTEM

PERFORMANCE SPECIFICATIONS

Measurements

- Measuring points sooner, faster and in harsh environments with Trimble HD-GNSS technology
- Increased measurement productivity and traceability with Trimble SurePoint electronic tilt compensation¹
- Advanced Trimble Maxwell 6 Custom Survey GNSS chips with 440 channels
- Future-proof your investment with Trimble 360 GNSS tracking
- Satellite signals tracked simultaneously:
 - GPS: L1C/A, L1C, L2C, L2E, L5
 - GLONASS: L1C/A, L1P, L2C/A, L2P, L3
 - SBAS: L1C/A, L5 (For SBAS satellites that support L5)
 - Galileo: E1, E5a, E5B
 - BeiDou (COMPASS): B1, B2
- OmniSTAR HP, XP, G2, VBS positioning¹
- QZSS, WAAS, EGNOS, GAGAN
- Positioning Rates: 1 Hz, 2 Hz, 5 Hz, 10 Hz, and 20 Hz

POSITIONING PERFORMANCE²

Code differential GNSS positioning

Horizontal	0.25 m + 1 ppm RMS
Vertical	0.50 m + 1 ppm RMS
SBAS differential positioning accuracy ³	typically <5 m 3DRMS

Static GNSS surveying

High-Precision Static

Horizontal	3 mm + 0.1 ppm RMS
Vertical	3.5 mm + 0.4 ppm RMS

Static and Fast Static

Horizontal	3 mm + 0.5 ppm RMS
Vertical	5 mm + 0.5 ppm RMS

Real Time Kinematic surveying

Single Baseline <30 km

Horizontal	8 mm + 1 ppm RMS
Vertical	15 mm + 1 ppm RMS

Network RTK⁴

Horizontal	8 mm + 0.5 ppm RMS
Vertical	15 mm + 0.5 ppm RMS

RTK start-up time for specified precisions⁵ 2 to 8 seconds

1 The default Trimble R10 LT configuration does not include this feature. It is available as an optional upgrade.
 2 Precision and reliability may be subject to anomalies due to multipath, obstructions, satellite geometry, and atmospheric conditions. The specifications stated recommend the use of stable mounts in an open sky view, EMI and multipath clean environment, optimal GNSS constellation configurations, along with the use of survey practices that are generally accepted for performing the highest-order surveys for the applicable application including occupation times appropriate for baseline length. Baselines longer than 30 km require precise ephemeris and occupations up to 24 hours may be required to achieve the high precision static specification.
 3 Depends on WAAS/EGNOS system performance.
 4 Network RTK PPM values are referenced to the closest physical base station.
 5 RTK refers to the last reported precision before the correction source was lost and xFill started.
 6 Receiver will operate normally to -40 °C, internal batteries are rated to -20 °C.
 7 Tracking GPS, GLONASS and SBAS satellites.
 8 Varies with temperature and wireless data rate. When using a receiver and internal radio in the transmit mode, it is recommended that an external 6 Ah or higher battery is used.
 9 Varies with terrain and operating conditions.
 10 Bluetooth type approvals are country specific.

HARDWARE

Physical

Dimensions (W×H)	11.9 cm x 13.6 cm (4.6 in x 5.4 in)
Weight	1.12 kg (2.49 lb) with internal battery, internal radio with UHF antenna, 3.57 kg (7.86 lb) items above plus range pole, controller & bracket
Temperature ⁶	
Operating	-40 °C to +65 °C (-40 °F to +149 °F)
Storage	-40 °C to +75 °C (-40 °F to +167 °F)
Humidity	100%, condensing
Ingress Protection	IP67 dustproof, protected from temporary immersion to depth of 1 m (3.28 ft)
Shock and vibration	Tested and meets the following environmental standards:
Shock	Non-operating: Designed to survive a 2 m (6.6 ft) pole drop onto concrete. Operating: to 40 G, 10 msec, sawtooth
Vibration	MIL-STD-810F, FIG.514.5C-1

Electrical

- Power 11 to 24 V DC external power input with over-voltage protection on Port 1 and Port 2 (7-pin Lemo)
- Rechargeable, removable 7.4 V, 3.7 Ah Lithium-ion smart battery with LED status indicators
- Power consumption is 5.1 W in RTK rover mode with internal radio⁷
- Operating times on internal battery⁸:
 - 450 MHz receive only option 5.5 hours
 - 450 MHz receive/transmit option (0.5 W) 4.5 hours
 - 450 MHz receive/transmit option (2.0 W) 3.7 hours
 - Cellular receive option 5.0 hours

COMMUNICATIONS AND DATA STORAGE

- Serial: 3-wire serial (7-pin Lemo)
- USB v2.0: supports data download and high speed communications
- Radio Modem: fully integrated, sealed 450 MHz wide band receiver/transmitter with frequency range of 403 MHz to 473 MHz, support of Trimble, Pacific Crest, and SATEL radio protocols:
 - Transmit power: 2 W
 - Range: 3–5 km typical / 10 km optimal⁹
- Cellular: integrated, 3.5 G modem, HSDPA 7.2 Mbps (download), GPRS multi-slot class 12, EDGE multi-slot class 12, UMTS/HSDPA (WCDMA/FDD) 850/1900/2100MHz, Quad-band EGSM 850/900/1800/1900 MHz, GSM CSD, 3GPP LTE
- Bluetooth: fully integrated, fully sealed 2.4 GHz communications port (Bluetooth®)¹⁰
- WiFi: 802.11 b,g, access point and client mode, WPA/WPA2/WEP64/WEP128 encryption
- External communication devices for corrections supported on – Serial, USB, Ethernet, and Bluetooth ports
- Data storage: 4 GB internal memory; over three years of raw observables (approx. 1.4 MB /day), based on recording every 15 seconds from an average of 14 satellites
- CMR+, CMRx, RTCM 2.1, RTCM 2.3, RTCM 3.0, RTCM 3.1 input and output
- 24 NMEA outputs, GSO, RT17 and RT27 outputs

WebUI

- Offers simple configuration, operation, status, and data transfer
- Accessible via WiFi, Serial, USB, and Bluetooth

Supported Trimble Controllers


- Trimble TSC3, Trimble Slate, Trimble CU, Trimble Tablet Rugged PC

CERTIFICATIONS

FCC Part 15 (Class B device), 22, 24; R&TTE CE Mark; C-Tick, A-Tick; PTCRB; WFA

Specifications subject to change without notice.





Vectors Inc.
VectorsInc.com
 Contact your local Trimble Authorized Distribution Partner for more information

Vectors Colorado - (303) 283-0343
 10670 East Bethany Drive, Building 4
 Aurora, CO 80014

Vectors New Mexico - (505) 821-0343
 5640 Venice Avenue, Unit J
 Albuquerque, NM 87113

NORTH AMERICA
 Trimble Inc.
 10368 Westmoor Drive
 Westminster CO 80021
 USA

EUROPE
 Trimble Germany GmbH
 Am Prime Parc 11
 65479 Raunheim
 GERMANY

ASIA-PACIFIC
 Trimble Navigation
 Singapore PTE Limited
 3 HarbourFront Place
 #13-02 HarbourFront Tower Two
 Singapore 099254
 SINGAPORE

