

zip'rTM Roo



- Easily disassembles into 5 pieces.
- Compact design maximizes maneuverability.
- Headlight, basket and non-marking, flat-free tires are standard on all scooters.



Roo disassembled



Specifications Zip'r Roo 3 & 4

Weight capacity	250 lbs.
Maximum speed*	3.5 mph
Per-charge range*	Up to 10 miles
Turning radius	31.5" / 39"
Ground clearance	2"
Headlight	LED
Overall length	41"
Overall width	19.5" / 20"
Overall height	32.4"
Weight w/ batteries	90.2 lbs. / 99.8 lbs.
Heaviest piece	32.5 lbs. (rear section)
Weight: Rear section	32.5 lbs.
Weight: Front section	22 lbs. / 31.6 lbs.
Weight: Seat	17 lbs.
Weight: Batteries	18.7 lbs. w/case
Battery	(2) 12 V, 12 Ah
Charger	Off-board, 2A
Drive	Rear
Motor specification	24 V, 180 W (.24 hp)
Brakes	Electromagnetic, regenerative
Seat type	Padded, foldable
Seat width	16.5"
Seat depth	14.5"
Seat back height	17"
Front wheel(s)	7.5" x 2" flat-free
Rear wheels	7.5" x 2.5" flat-free
Body colors	Red/Blue

Limited Warranty**

Frame	3 years
Drivetrain	1 year
Electronic Components	1 year
Batteries	6 months

All specifications are subject to change without notification.

*Specification may vary due to user weight, speed, battery condition and terrain.

**Exclusions apply. See owner's manual for more details.