








AZ3 HTE 2 Gravity Spray Gun

- **Fine finish polished body**
Smooth polished surface makes it easier to clean
- **Ergonomic gun design**
New trigger and ergonomic grip shape to relieve stress on painting
- **Light weight & well balanced body**
Gun head 20-50 g lighter than previous model
- **New air flow valve**
Increased control precision
- **Improved AKULON cup**
Improved paint cup with multi thread construction
- **Pressure assisted cup (new product)**
AirGunsa have added a pressure assisted paint cup system to the high viscosity paint application range
- **Spare parts compatible with previous AZ3 HTE**



Model							
	Ø mm	bar	N ₂ /min	ml/min	mm	No.	g
AZ3 HTE 2	1.0	2.0	200	80	180	-	517
	1.3			140	240	-	
	1.5			160	260	-	
	1.8			205	250	300	
	2.0			205	300	340	
	2.5	3.0	279	450	360	-	
	2.8			291	540	380	
	3.0			288	560	400	
	3.5			307	600	420	
AZ3 HTE HVLP	1.3	1.9	340	150	280	-	
	1.5			185	290	-	
	1.8			215	340	-	
	2.0			240	360	-	


Max. Working Pressure: 6.8 bar (98 PSI)

Noise Level (LAeqT) 77.6 dB (A)

Temperature range: 5~40° C

Air nipple: G 1/4" M

Fluid nipple: G 1/4" F

Model	AZ3 HTE 2	
Test	Transfer Efficiency according to EN 13966-1	
Authority	IPA Fraunhofer Institut	
Date	27/03/2008	
<i>Transfer efficiencies achieved with the materials detailed in the test report were:</i>		
2K Primer Coat	89 %	
Water based Base Coat	79 %	
2K Clear Coat	84 %	
		
Certification available on www.airguns.com		

CE  II 2 G X

declaration of ATEX conformity for use in zone 1 and in zone 2

Distributed by: