

BLOK2™ IP

AnyFi™



intelion
INTELLIGENT
LITHIUM-ION
BATTERY SYSTEM

IP65 Rated, RGBW+UV 25W LEDs, Battery Powered + Anyfi™ Wireless DMX

The perfect outdoor rated, battery powered lighting solution with built-in 2.4GHz AnyFi™ Wireless DMX!

Blok 2™ IP fixtures are packed with lots of goodies including 2* high output 25W RGBW+UV 5-in-1 COB LEDs with a 30° beam angle, built-in rechargeable Li-ion battery, built-in wireless AnyFi™ receiver (W-DMX™ and Skywire™ compatible), an easy-to-use 4-button LED control panel with touch sensitive electronic buttons, 3-pin DMX in/out connectors, and powerCON™ compatible power In/Out connectors.

They are highly efficient with natural convection cooling thanks to their attractive cast aluminum housing with heat sink design. There are no internal cooling fans in these fixtures, which mean absolutely zero noise. Blok 2™ IP fixtures are a great choice for any “sound sensitive” environment!

You can use it freestanding just about anywhere wirelessly and without power cords as an upright, or mount it via its secure dual mounting brackets.

And a wireless IR remote control (sold separately) is also available for this fixture!

Main Features

- IP65 rated with 2x 25W RGBW+UV 5-in-1 COB LEDs
- Built-in 2.4Ghz AnyFi™ wireless DMX receiver
- W-DMX™ & Skywire™ compatible
- Intelion™ lithium-ion battery system
- 3 battery power saving modes
- User-selectable 32-bit dimming curves
- Variable electronic dimming & strobe
- Built-in automated and customizable programs
- 30 degree beam angle
- Virtual color wheel effect
- RGBW+UV color mixing ability in standalone mode
- Freestanding upright or mountable via dual mounting brackets
- Standalone, master/slave, auto mode
- 5/6/8/11-channel DMX modes
- IR remote control (sold separately)
- Rugged and well-built
- Super-quiet with natural convection cooling
- Dual mounting brackets for positioning flexibility
- Flicker-free constant-current 1500HZ LED driver
- 3-pin XLR male input + 3-pin DMX In/Out splitter cable
- PowerCon™ compatible AC power input connector

Power

- Operating Voltage: 100V-264VAC, 47-63HZ
- Power Consumption: 41W, .6A, PF: .6

Light Source

- 2x 25W RGBW+UV 5-in-1 COB LEDs

Optical

- Beam Angle: 30° beam angle

Thermal

- Max. Operating Temp.: 104 degrees F (40 degrees C) ambient

Control

- Protocol: USITT DMX-512
- DMX Channels: 5/6/8/11-channel DMX
- 3-pin XLR male input + 3-pin DMX In/Out splitter cable
- Standalone, Master/Slave, Auto Mode

AnyFi™ Wireless Receiver

- W-DMX™ Receiver (Frequency Hopping Protocol)
- Skywire™ 6/7-channel Receiver Mode
- Less Than 5ms Latency
- Receiver sensitivity: -94dBm

Weight & Dimensions

- Dimensions: 13.2" (335 mm) x 4.3" (108 mm) x 7.8 inches (197 mm)
- Weight: 12.1 lbs (5.5 kg)

Warranty

- 2-year limited warranty, does not cover malfunction caused by damage to LEDs