

Meet the TOURnado™ IP Beam

It stands up to the fury of Mother Nature, and comes back looking for more!

This incredibly tough IP65 rated outdoor fixture features super bright RGBW color mixing and a tight beam angle thanks to its installed 7x 15W Red/Green/Blue/White 4-in-1 LEDs with advanced 8° optics. Since each individual LED incorporates a red, green, blue, and white chip behind a single lens, shadow artifacts and unevenness within the field are things of the past! And, like the other lights in our TOURnado™ line, it also sports a convection cooled cast aluminum housing with a tempered glass lens, watertight internal gaskets, and weatherproof power and data cable in/out connections.

You can run any of its impressive built-in programs individually or all together in auto run mode with speed control, fade, and flash settings, then even perform full RGBW color mixing either with or without DMX control. The TOURnado™ IP Beam is a perfect lighting solution for just about any type of outdoor application. It comes equipped with dual mounting brackets to add total positioning flexibility, and it has a well structured, easy to navigate LED control panel menu with 4 electronically touch sensitive navigation buttons that make programming (and button pushing) a breeze!

Set the fixture to work in standalone mode, master/slave mode, or you can control it via 5/6 or 9 channels of DMX, which means it will work just great with any lighting controller. Features include RGBW color mixing, 15 built-in static colors, auto run mode, flash/fade mode, and access to 5 user-selectable 32-bit dimming curves. These five different dimming curves allow for different amounts of steps for much smoother (and slower) dimming capabilities.

On the rear of the fixture are weatherproof power and DMX in/out connections with rubber plugs, and each fixture comes with 1* powerCON™ TRUE1 compatible AC power input cable, and an IP rated DMX signal cable.

The TOURnado™ IP Beam is available now, and of course, it is also backed by Blizzard's 2-year warranty!

Main Features

- RGBW color mixing via 7x 15W Red/Green/Blue/White 4-in-1 LEDs
- LED control panel with 4 touch sensitive electronic buttons
- Super-sharp 8° beam angle
- Variable electronic dimming & strobe
- Built-in color & chase macros via DMX
- Built-in automated programs via master/slave
- RGBW color mixing ability in standalone mode
- Convection cooled cast aluminum housing
- Dual mounting brackets for positioning flexibility
- Flicker-free constant-current 500MA LED driver
- IP rated locking power and 3-pin DMX connections
- RGBW & Strobe (5-Ch), Dimmer, RGBW & Strobe (6-Ch), & Extended with Dimmer, RGBW, Strobe, & 32-bit dimming (9-Ch) DMX Profiles

| Lux/m | Red | Green | Blue | White | All |
|-------|--------|--------|--------|--------|--------|
| 1m | 12,050 | 12,100 | 19,220 | 30,800 | 62,900 |
| 2m | 6,410 | 6,390 | 8,870 | 12,000 | 23,400 |

TOURNADO™

IP BEAM

IP65

SUITABLE FOR OUTDOOR USE



Power

- Operating Voltage: 100-264VAC, 47/63 Hertz
- Power Consumption: 82W, 1.18A, PF: .58

Light Source

- 7x 15W 4-in-1 LEDs 100,000 hours

Optical

- Beam Angle: 8 degree optics standard

Thermal

- Max. Operating Temp.: 104° F (40° C) ambient

Control

- Protocol: USITT DMX-512
- 4-button menu with LED display
- DMX Channels: 5/6/9
- Input: 3-pin XLR Male
- Output: 3-pin XLR Female
- Operating Modes: Standalone, Master/Slave, Auto Modes

Weight & Dimensions

- Width: 10.7 inches (270 mm)
- Depth: 5.7 inches (144 mm)
- Height: 8.6 inches (21.8 cm), 11.2 inches
- Weight: 11.5 lbs (5.2 kg)