



19* 15W 6-in-1 LED IP65 Rated PAR Can

Rocking someone like a hurricane? Been thunderstruck? Making it rain men? No matter what kind of tempest you bring to the stage you need the TOURNado™ WIMAX Series from Blizzard Lighting.

The TOURNado™ WIMAX EXA brings more lightning for your thunder with higher output than ever before. Get super bright RGBAW+UV color mixing from 19x 15W 7-in-1 LEDs with advanced 25° optics.

The TOURNado™ WIMAX EXA weathers almost any storm. It's IP65 outdoor rated and sports a larger natural convection cooled cast aluminum housing than previous models. It has a tempered glass lens and watertight internal gaskets. The back has outdoor rated 3-pin XLR data and AC power input/output connectors with rubber seals.

It's time to truly unleash the storm and go wireless. The built-in W-DMX™ receiver works seamlessly with any W-DMX™ product and provides ultra-stable wireless communication for more than 500 meters (line-of-sight)!

All TOURNado™ WIMAX fixtures have a 4-button control panel with an OLED display. You have total control including master/slave settings, 5 auto modes, custom programs (up to 3* 20 scene programs), fade, strobe, manual color adjustments, multiple user-selectable 32-bit dimming modes and more.

Riders on the storm, time to mount up and experience the TOURNado™ WIMAX EXA.



SUITABLE FOR OUTDOOR USE

Main Features

- Color mixing via 19x 15W RGBAW+UV 6-in-1 LEDs
- IP65 rated outdoor LED fixture
- OLED control menu with 4x touch sensitive buttons
- 25-degree beam angle
- Built-in wireless W-DMX™ receiver
- Built-in color & chase macros via DMX
- Built-in automated programs via master/slave
- Color mixing ability in standalone mode
- 6/8/12-channel DMX profiles w/32-bit dimming
- Convection cooled cast aluminum housing
- Dual mounting brackets for positioning flexibility
- Flicker-free constant-current LED driver
- IP rated locking power and 3-pin DMX connections
- Dimensions: 14x6.7x13.3 inches (355x172x337 mm)
- Weight: 17.0 lbs (7.7 kg)



Optical

Light Source: 19* high output 15-watt RGBAW+UV LEDs

Beam Angle: 25°

Flicker-free LEDs

Luminous Intensity: 4,207 Lux (390.9 fc) @ 2.5m | 1,009 Lux (93.8 fc) @ 5m



Wireless Receiver

Transmission band: 2.4Ghz ISM (2.4-2.525Ghz)

Channels: 512

Receiver sensitivity: -94dBm



Control

Protocol: USITT DMX-512

6/8/12-channel DMX modes

Standalone, master/slave, DMX modes

IP65 Seetronic 3-pin DMX input/output

4-button OLED control menu display



Power + Current

100-264VAC, 47-63 Hz

Power Consumption: 149W, 1.28A, PF: .99



Warranty + Certifications

2-year limited warranty, does not cover malfunction caused by damage to LEDs

cETLus certified



blizzardlighting.com

info@blizzardlighting.com

1.866.493.5025

1.866.493.6025