FX FALL TOPCOATS



(HARVEST, SPICED, CIDER) Safety Data Sheet (SDS)

Section 1: Product Identification

Product Identifier	Product Use
FX Fall Topcoats (Harvest, Spiced, Cider)	Professional Use Only
Manufacturer's Name	Street Address
Fuzion Gel Ltd.	10536 178 St. NW, Edmonton, AB, Canada
Date SDS Prepared	Phone Number
August 13, 2022	1 (844) 748-9324

Section 2: Hazardous Ingredients

Hazardous Ingredient	%	CAS Number	LD ₅₀ of Ingredient
Acrylates Copolymer	62	25133-97-5	Not Determined
2-Hydroxyethyl methacrylate (HEMA)	20	868-77-9	Not Determined
Trimethylbenzoyl Diphenylphosphine Oxide	4	75980-60-8	Not Determined
Pentaerythrityl Tetramercaptopropionate	8	7575-23-7	Not Determined
Silica dimethyl silyate	2.4	68611-44-9	Not Determined
Polyethylene terephthalate	3.6	25038-59-9	Not Determined

Section 3: Physical Data

Physical State	Odour & Appearance	Specific pH
Liquid	Light Odour, Mixed Colour	6.8 - 7.0
Boiling Point (°C)	N1/A	Vapour Density
N/A	N/A	N/A

Section 4: Fire & Explosion Data

Flammability Conditions	Means of Extinguishing	Flashpoint (°C)
N/A	Foam, dry chemical, C02, or dust	N/A
Autoignition Temperature (°C) Explosivity - Impact		Explosivity - Static Discharge
N/A	N/A	N/A
NFPA		
Health - 1 Flammability - 2 Physical Hazard - 1		

Section 5: Reactivity Data

Chemical Stability and Conditions	Chemical Incompatibilities
Stable under normal use & storage	Strong acids, strong oxidizing agents, bases
Reactivities and Conditions	Hazardous Decomposition Products
Avoid heat, flames, sparks, do not heat >80°c	Oxides of Carbon, Irritating organic vapours

Section 6: Toxicological Properties

Routes of Entry		
Skin, eyes, respiratory		
Effects of Acute Exposure to Produc	et	
Irritation		
Effects of Chronic Exposure to Prod	uct	
Unknown		
Exposure Limits	Irritancy	
No data	Yes	
Sensitization	Carcinogenicity	
No data	No	
Reproductive Toxicity	Teratogenicity	
No	No	
Mutagenicity	Synergistic Products	
No	No	

Section 7: Preventative Measures

Personal Protective Equipment

Impermeable gloves & clothing, safety goggles with side shields

PPE Types

See above

Engineering controls

Concentrations in air should be maintained below the lower explosive limit at all times. Make-up air should always be supplied to balance air exhausted. Electrical and mechanical equipment should be explosion-proof. Mechanical ventilation is recommended for all indoor situations to control fugitive emissions.

Leak and Spill Controls

Prevent from entering soil, ditches, sewers, waterways, and/or groundwater. Contain any spills by diking. Collect in suitable and properly labeled containers using absorbent materials and/or pumps. Apply vapour suppression foam until spill can be cleaned up Take precautionary measures against static discharge.

Waste Disposal

Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with regional regulations.

Handling Procedures

Flammable. Do not cut, drill, grind, weld or perform similar operations on or near containers. Vapours may accumulate and travel to distant ignition sources and flashback. Empty containers may contain hazardous product residues. Fixed equipment as well as transfer containers and equipment should be grounded to prevent accumulation of static charge. Hot surfaces may be sufficient to ignite liquid even in the absence of sparks or flames. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapours are gone. Do not pressurize drum containers to empty them. Avoid breathing vapours and prolonged or repeated contact with skin. Launder contaminated clothing prior to reuse. Airdry contaminated clothing in a well ventilated area before laundering. Electrostatic charges may be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (<=1 m/sec until pipe is submerged to twice it's diameter, then <=7 m/sec). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations. Extinguish any naked flames.

Storage Requirements

Store in a cool, dry, well ventilated area, away from heat and ignition sources. Bulk storage tanks should be diked. Vapours from tanks should not be released to atmosphere. Use explosion proof ventilation to prevent vapour accumulation. Keep away from aerosols, flammables, oxidizing agents and corrosives. For containers or container linings use mild steel or stainless steel

Shipping Considerations

None/unrestricted

Section 8: First Aid Measures

Inhalation

Remove person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, get immediate medical attention

Ingestion

Do not induce vomiting. Guard against aspiration into lungs by having the individual turn onto their side. Do not give anything by mouth to an unconscious person. If vomiting occurs, keep head below hips to prevent aspiration of liquid into the lungs. Seek immediate medical attention.

Skin Contact

In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Get medical attention. Remove contaminated clothing and launder before reuse.

Eye Contact

In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and receive immediate medical attention.

Section 9: SDS Preparation Information

SDS Prepared By Fuzion Gel Ltd.	Street Address 10536 178 St. NW, Edmonton, AB, Canada
Date SDS Prepared	Phone Number
August 13, 2022	1 (844) 748-9324

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.