

Section 1: Product Identification

Product Identifier	Product Use
Sculptzure	Professional Use Only
Manufacturer's Name	Street Address
Fuzion Gel Ltd.	10536 178 St. NW, Edmonton, AB, Canada
Date SDS Prepared	Phone Number
August 13, 2022	1 (844) 748-9324

Section 2: Hazardous Ingredients

Hazardous Ingredient	%	CAS Number	LD_{50} of Ingredient
Polyurethane Acrylate Prepolymer Resin	60-100	N/A	Not Available
Polyurethane Methacrylate Prepolymer Resin	10-30	N/A	Not Available
Tripropyleneglycol Diacrylate	3-7	42978-66-5	Not Available
1-Hydroxycyclohexyl Phenylketone	1-5	9947-19-3	2800 mg/kg
Benzophenone	1-5	119-61-9	2895 mg/kg

Section 3: Physical Data

Physical State	Odour & Appearance	Specific pH
Liquid	Clear or pigmented liquid	Not available
Boiling Point (°C)	Freezing Point (°C)	Vapour Density
Not available	Not available	Not available

Section 4: Fire & Explosion Data

Flammability Conditions	Means of Extinguishing	Flashpoint (°C)
Yes, extremely flammable liquid	Water, foam, CO2, Dry chemical	> 100
Autoignition Temperature (°C)	Explosivity - Impact	Explosivity - Static Discharge
Not available	No	No
NFPA		
Health: 1, Flammability: 1, Reactivity: 0, Protective Equipment: B		

Section 5: Reactivity Data

Chemical Stability and Conditions	Chemical Incompatibilities	
Stable under ambient conditions	Oxidizers, peroxides, strong acids, alkalis	
Reactivities and Conditions	Hazardous Decomposition Products	
None	Irritating and toxic gasses	

Section 6: Toxicological Properties

Routes of Entry Skin absorption, Inhalation, Ingestion	
Effects of Acute Exposure to Product	
Moderate irritation to eyes and skin near affected areas	
Effects of Chronic Exposure to Product	
The material may cause an allergic reaction for some individuals	
Exposure Limits	Irritancy
Not available	No
Sensitization	Carcinogenicity
No	No
Reproductive Toxicity	Teratogenicity
No	No
Mutagenicity	Synergistic Products
No	None

Section 7: Preventative Measures

Personal Protective Equipment

Eyewear

PPE Types

Wear protective eyewear at all times when handling this product

Engineering controls

Concentrations in air should be maintained below the lower explosive limit at all times. Make-up air should always be supplied to balance air exhausted. Electrical and mechanical equipment should be explosion-proof. Mechanical ventilation is recommended for all indoor situations to control fugitive emissions.

Leak and Spill Controls

Prevent from entering soil, ditches, sewers, waterways, and/or groundwater. Contain any spills by diking. Collect in suitable and properly labeled containers using absorbent materials and/or pumps. Apply vapour suppression foam until spill can be cleaned up Take precautionary measures against static discharge.

Waste Disposal

Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with regional regulations.

Handling Procedures

Flammable. Do not cut, drill, grind, weld or perform similar operations on or near containers. Vapours may accumulate and travel to distant ignition sources and flashback. Empty containers may contain hazardous product residues. Fixed equipment as well as transfer containers and equipment should be grounded to prevent accumulation of static charge. Hot surfaces may be sufficient to ignite liquid even in the absence of sparks or flames. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapours are gone. Do not pressurize drum containers to empty them. Avoid breathing vapours and prolonged or repeated contact with skin. Launder contaminated clothing prior to reuse. Airdry contaminated clothing in a well ventilated area before laundering. Electrostatic charges may be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (<=1 m/sec until pipe is submerged to twice it's diameter, then <=7 m/sec). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations. Extinguish any naked flames.

Storage Requirements

Store in a cool, dry, well ventilated area, away from heat and ignition sources. Bulk storage tanks should be diked. Vapours from tanks should not be released to atmosphere. Use explosionproof ventilation to prevent vapour accumulation. Keep away from aerosols, flammables, oxidizing agents and corrosives. For containers or container linings use mild steel or stainless steel

Shipping Considerations

None

Section 8: First Aid Measures

Inhalation

Remove person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, get immediate medical attention

Ingestion

Do not induce vomiting. Guard against aspiration into lungs by having the individual turn onto their side. Do not give anything by mouth to an unconscious person. If vomiting occurs, keep head below hips to prevent aspiration of liquid into the lungs. Seek immediate medical attention.

Skin Contact

In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Get medical attention. Remove contaminated clothing and launder before reuse.

Eye Contact

In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and receive immediate medical attention.

Section 9: SDS Preparation Information

SDS Prepared By	Street Address
Fuzion Gel Ltd.	10536 178 St. NW, Edmonton, AB, Canada
Date SDS Prepared	Phone Number
August 13, 2022	1 (844) 748-9324

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.