



MF SERIES OPERATING INSTRUCTIONS

900-1011	MF UV 395nm
900-1100CR	MF Tac-Fire CREE
900-1012C	MF Blue FLS 470nm <i>pictured</i>
900-1013C	MF Cyan FLS 495nm
900-1014C	MF Green FLS 525nm
900-1018	MF Infrared FLS 850nm
900-1031C	MF UV 365nm
900-1099C	MF All In One FLS



Please read the below before using your MF 1000 flashlight as it relays beneficial operating and safety information.

PHYSICAL CHARACTERISTICS:

- Aluminum 6061-T6 hard anodized housing with TPR bumpers

Model	Dimensions
All Models	Length: 11.1" (282 mm) Head Diameter: 3.9" (99 mm) Handle Diameter: 1.9" (48 mm)
Weight	3.8 lbs (1.7 kg)

LED & EXTERIOR COLOR ACCORDING TO P/N:


Model	LED Color	Exterior Color
900-1011	9 LEDs: 4 LEDs 380nm to 385nm 4 LEDs 395nm to 400nm 1 LED White CREE XR-E	Black
900-1100CR	9 White CREE XR-E LEDs	Black
900-1012C	9 LEDs 470nm <i>Blue</i>	Blue
900-1013C	9 LEDs 495nm <i>Cyan</i>	Cyan
900-1014C	9 LEDs 525nm <i>Green</i>	Green
900-1018	3 LEDs 850nm <i>Infrared</i> OSRAM OSTAR	Bronze
900-1031C	9 LEDs 365nm <i>UV</i>	Silver
900-1099C	9 LEDs: 2 LEDs 470nm <i>Blue</i> 2 LEDs 495nm <i>Cyan</i> 2 LEDs 525nm <i>Green</i> 2 LEDs 850nm <i>IR</i> 1 LED White CREE XR-E	Silver

CHARGING THE BATTERIES:

The MF Series Flashlight are Rechargeable.
Use Supplied Rechargeable Battery Cap with Rechargeable Battery Pack.



- Charge the MF using the provided charger: (100-240VAC), 50/60 Hz
- Approximate Charge Time: 4 hours
 - While connected to the AC Adaptor, the GREEN light on the rear of the MF is ON (pictured below). Its function is only to advise that you are attempting to charge.



- The AC adaptor also has a light which is GREEN when plugged into the wall. As soon as you connect it to the MF for charging, it turns RED. Full Charge is shown by non-blinking GREEN LED on the AC adaptor.

BATTERY LIFE

Battery Life is expected as follows:

P/N 900-1011, 900-1100CR, 900-1012C, 900-1013C, 900-1014C, 900-1018 & 900-1031C Only:

FULL POWER	60-75 minutes*
-------------------	----------------

P/N 900-1099C Only:

FULL POWER	4 to 6 hours (varies by mode) *
RESERVE POWER	Up to 6 hours

* Battery life may vary according to Mode Selected, Battery Quality, and prevailing Ambient Conditions.


Continuously charging (leaving the unit plugged in) could damage the Battery Pack and lead to a decreased battery life. Please disconnect the unit once it is fully charged.

OPERATIONAL MODES ACCORDING TO P/N:

MF Series Flashlights have two Operational Modes:

MODE	DESCRIPTION
1	33% Intensity
2	100% Intensity


*Light turns off between Modes

All-in-One ALS Operational Modes: P/N  900-1099C Only

MODE	DESCRIPTION
1	470nm <i>Blue</i>
2	495nm <i>Cyan</i>
3	525nm <i>Green</i>
4	850nm <i>Infrared</i>
5*	White

* Light turns Off Following Mode 5.

PRODUCT DURABILITY, ENVIRONMENTAL CONSTRAINTS & CERTIFICATIONS:



CE-EMC

Meets NFPA 1971-2007 Fire Resistant Requirements:
500°F / 260°C for 30 minutes

ACCESSORIES:

- MF Rechargeable System, P/N 600-9001
- Carry Strap, P/N 600-100

CARE/CLEANING:

Your FoxFury is a professional tool, but regular maintenance and care will maximize performance for you. As needed, wash your FoxFury using a soft washcloth, clean water and a mild soap. Be sure that the battery pack is SEALED before washing. When done, pat dry with a damp cloth.

WARNINGS: IMPORTANT

FoxFury, LLC is not responsible for the incorrect use of any FoxFury Lighting product.

- Lights are strong enough to cause damage to the human eye.
- Do not stare into LEDs for long periods of time or from a close range (less than 2 feet).
- FoxFury, LLC is not responsible for any injury or damage caused during the use of this product.
- Usage of this product must be supervised by an adult when it is being used by a minor.
- Any FoxFury product should be operated at speeds safe enough to maneuver around surrounding obstacles.
- Do not use under the influence of drugs or alcohol.
 - Flashlight weighs nearly 3.8 lbs (1.7 kg). If the flashlight falls to the ground, it may cause damage to a user or to a nearby surface.

CAUTION: Head of flashlight will get very warm or hot.

Avoid touching surface to prevent burns.

Rubber Insulators have been strategically installed to protect the user, and to protect the surfaces where the flashlight will be placed.

UV LIGHT

Avoid direct eye exposure to UV light.

Keep out of reach of children.

- The UV LED during operation radiates intense UV light.
- Do not look directly into the UV light during operation, even for a brief period. This can be harmful to the eyes due to the intensity of the UV light.
- When viewing with the UV light, please use UV filtered glasses to avoid damage by the UV light.

INFRARED (IR) LIGHT

Avoid Staring at the Light.

- While invisible to the human eye, it can cause long term damage.

LIMITED WARRANTY:

FoxFury Limited Warranty & Customer Care Information

FoxFury, LLC ("FoxFury") warrants to the purchaser of this product ("Buyer") that for a period of two years following purchase, this product will be free from defects in material and workmanship and will function in substantial compliance with FoxFury's written specifications for this product as specified in the instruction manual or on FoxFury's website located at www.foxfury.com. Buyer's exclusive remedy shall, in any case, be limited, at FoxFury's election, to: A) repair or replacement of the defective product; or B) refund of the purchase price for this product. THE FOREGOING WARRANTY IS THE ONLY WARRANTY MADE BY FOXFURY WITH RESPECT TO THIS PRODUCT. TO THE EXTENT ALLOWED BY APPLICABLE LAW, THERE ARE NO REPRESENTATIONS OR WARRANTIES OF ANY KIND BY THE FOXFURY, EXPRESS OR IMPLIED,

WITH RESPECT TO THE CONDITION OR PERFORMANCE OF THIS PRODUCT, INCLUDING, BUT NOT LIMITED TO, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

This limited warranty shall not apply if this product is not stored, handled, installed or used in strict accordance with manufacturer's specifications and instruction manuals, or which has been subject to misuse, alteration, negligence or accident.

1. The damaged part or product must be returned to FoxFury **PRIOR TO** any repair or replacement. Shipping costs are the responsibility of the claimant.
2. You must obtain a return authorization (RMA) number from FoxFury prior to returning products. FoxFury is not responsible for any damage incurred while in transit.
3. Buyer will be required to show proof of purchase – No Exceptions.
4. Any modifications to light, cable or battery pack automatically voids all warranties on this product.

All warranty inquiries should be directed to FoxFury's Customer Service Department to handle all warranty/repair-relate inquiries.

TO THE EXTENT ALLOWED BY APPLICABLE LAW: (A) IN NO EVENT, WHETHER DUE TO BREACH OF WARRANTY HEREUNDER OR ANY OTHER CAUSE WHATSOEVER, SHALL FOXFURY BE LIABLE FOR OR OBLIGATED IN ANY MANNER TO PAY CONSEQUENTIAL, INCIDENTAL OR INDIRECT DAMAGES, INCLUDING, BUT NOT LIMITED TO, LOSS OF PROFITS, COST OF SUBSTITUTE PRODUCTS AND PERSONAL INJURY OR PROPERTY DAMAGE, WHETHER SUCH CLAIM IS BASED ON CONTRACT OR TORT OR ANY OTHER THEORY OF LAW, AND (B) FOXFURY'S ONLY DUTIES IN CONNECTION WITH THE SALE OF THIS PRODUCT SHALL BE TO HONOR THE LIMITED WARRANTY SET FORTH HEREIN. TO THE EXTENT THAT THIS LIMITED WARRANTY IS INCONSISTENT WITH APPLICABLE LAW, THIS STATEMENT SHALL BE DEEMED MODIFIED TO BE CONSISTENT WITH SUCH APPLICABLE LAW.



FoxFury, LLC
Oceanside, CA 92056 USA
Toll-Free: 844-FOXFURY
Tel: 760.945.4231
Fax: 760.433.3650

Email: custserv@foxfury.com
www.FoxFury.com

All FoxFury products are designed in Oceanside, CA. All FoxFury products are manufactured with the highest quality USA and foreign parts. Products are assembled in either FoxFury's controlled plant in Asia or the USA, under strict quality control.