

FW Epoxy Pouring Medium

Page: 1

Compilation date: 23/04/2021

Revision No: 1

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: FW Epoxy Pouring Medium

CAS number: 25068-38-6
EINECS number: 500-033-5
Index number: 603-074-00-8

Product code: FW Epoxy Pouring Medium

Synonyms: EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <700)

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

### 1.3. Details of the supplier of the safety data sheet

Company name: Daler Rowney

Peacock Lane Bracknel

Berkshire RG12 8SS

United Kingdom

**Tel:** + 44 (0) 1344 461 156

Email: customer.services@daler-rowney.com

### 1.4. Emergency telephone number

Emergency tel: + 44 (0) 1344 461 156

(office hours only)

#### Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317

Most important adverse effects: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

### Label elements:

Hazard statements: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.



FW Epoxy Pouring Medium

Page: 2

Hazard pictograms: GHS07: Exclamation mark

GHS09: Environmental





Signal words: Warning

**Precautionary statements:** P264: Wash thoroughly after handling.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P321: Specific treatment (see on this label).

P332+313: If skin irritation occurs: Get medical advice or attention.

P501: Dispose of contents / container to a collection point for hazardous waste in accordance with

local, regional, national and / or international regulations.

#### 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

#### 3.1. Substances

Chemical identity: BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

CAS number: 25068-38-6

EINECS number: 500-033-5

### Section 4: First aid measures

### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

# 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

# 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.



FW Epoxy Pouring Medium

Page: 3

### Section 5: Fire-fighting measures

### 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool

containers.

#### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with

skin and eyes.

### Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking

containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

#### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal

by an appropriate method.

### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

### Section 7: Handling and storage

# 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do

not handle in a confined space. Avoid the formation or spread of mists in the air.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage

room must be impermeable to prevent the escape of liquids.

### 7.3. Specific end use(s)

Specific end use(s): No data available.

# Section 8: Exposure controls/personal protection



FW Epoxy Pouring Medium

Page: 4

8.1. Control parameters

Workplace exposure limits: No data available.

**DNEL/PNEC Values** 

**DNEL / PNEC** No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be

impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective impermeable gloves, 4 mil thick, nitrile rubber, penetration time 4-6 hours.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

### Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

#### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

## 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

# 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

## 10.4. Conditions to avoid

Conditions to avoid: Heat.

# 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

#### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

### **Section 11: Toxicological information**

# 11.1. Information on toxicological effects



FW Epoxy Pouring Medium

Page: 5

### **Toxicity values:**

Route	Species	Test	Value	Units
ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11400	mg/kg
SKN	RBT	LD50	>20	ml/kg

#### Hazardous ingredients:

#### **BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}**

ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11400	mg/kg
SKN	RBT	LD50	>20	ml/kg

#### Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

### Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

## **Section 12: Ecological information**

### 12.1. Toxicity

Ecotoxicity values: No data available.

#### 12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

### 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

# 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.



FW Epoxy Pouring Medium

Page: 6

### 12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

#### Section 13: Disposal considerations

#### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

## **Section 14: Transport information**

#### 14.1. UN number

UN number: UN3082

#### 14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

### 14.3. Transport hazard class(es)

Transport class: 9

#### 14.4. Packing group

Packing group: III

# 14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: No

## 14.6. Special precautions for user

**Special precautions:** No special precautions.

Tunnel code: E
Transport category: 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

#### **Section 16: Other information**

# Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.



FW Epoxy Hardener

Page: 7

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting

from handling or from contact with the above product.