Quiet-Flo™ Heated Blower with On/Off Air Button



Blower Operation

Air switch operation:

- 1st Press: High speed.
- 2nd Press: Med. speed.
- 3rd Press: Low speed.
- 4th Press: Wave Mode.
- 5th Press: Off.
- In Wave Mode, the blower starts at high speed, reduces to low speed, then rises to high speed. Then the cycle resumes.

Optional Heated Quite-Flo Blower

Any time the blower turns on, the heater turns on with it.

Specifications / Overview

- 120 VAC 60 Hz.
- 30 minute timer.
- Purge cycle.
- 4 Modes of operation:

Speed 3: High speed.

Speed 2: Med. speed.

Speed 1: Low speed.


Wave Mode: Speed diminishes to low, then returns to high (within 12 seconds).

- Control board mounted in blower housing.
- If the main power is interrupted while the timer is running, the system will return to standby mode when power is restored.

Timers

When the system motor is activated, a 30 minute timer is automatically started. Once the 30 minutes run-time has expired, any equipment automatically turns off.

When the blower is turned off, it waits for 15 minutes and then runs a two-minute purge cycle. A purge cycle is designed to remove standing water from the air system, which helps maintain a sanitary bath system.



^{*} See catalog or call for air switch button options.

