

GLASSWASHER AX-40 DD

Rack size 400x400mm and door clearance 300 mm



30% savings in water consumption during rinsing compared to the previous range.

3-stage filter system: surface, tank and extraction

- Keeps the washing water in optimal conditions to maintain constant washing performance.
- √ The surface filters feature an "easy-on" design and can be quickly. removed without having to disconnect the washing arms.

"Easy grip" door: new design with integrated door handle

- √ The integration of the components provides greater resistance and
- Designed to have no corners or areas that are difficult to access: prevents deposits of dirt and facilitates cleaning.
- ✓ Its ergonomic handle provides a perfect grip, even with wet hands.
- ✓ Double-walled door with safety microswitch and high quality seal
- 30 cm load capacity: high versatility for washing a wide range of glasses and even medium-sized dishes.

Warewashing, made simple

- ✓ Active Xperience: simple and intuitive use
- Dedicated cycles: selection of the ideal washing programme using
- Electronic control panel with IP65 humidity protection.

You will never WASH ALONE

- Tech-Services: our team of technicians will help you so that your machine is always ready for use.
- Design Services: tell us what your needs are and we will advise you.
- √ 60 years of experience and know-how at your disposal.

INCLUDES

- ✓ Peristaltic Detergent Pump
- √ 1 glasses basket.
- √ 1 mixed basket (plates).
- 1 small basket for cutlery.

ACCESSORIES

- Manual water softeners
- Automatic water softeners
- 400X400 mm. baskets
- ☐ Inserts & supplements
- □ High Feet Kit
- ☐ Reverse Osmosis device OS-140P
- ☐ Stand for 400x400 mm glasswashers
- Double rack kit for AX/UX-40

SALES DESCRIPTION

Sani-Control: guaranteed disinfection

Embedded bodywork and easy-grip door: hygienic and ergonomic

Exclusive Hydroblade™ washing arms: maximum effectiveness.

3-stage filtering system.

Double-walled body (partial).

Sani-Control guarantee

- GUARANTEED DISINFECTION in compliance with standard DIN
- THERMAL LOCK function: Ensures that rinsing will be carried out at the ideal temperature to disinfect the dishes.

New recessed bodywork

- Ergonomic design with rounded corners to prevent the accumulation of dirt and facilitate cleaning.
- Compact tank volume (50% water saving compared to the previous range).
- √ Embedded basket guides

Hydroblade™ washing arms

- Redesigned nozzles for greater washing performance.
- √ The "monoblock" design delivers durability and resistance to impacts.



sammic





www.sammic.co.uk

Food Service Equipment Manufacturer Unit 2. Trevanth Road Troon Industrial Park LE4 9LS - Leicester

uksales@sammic.com Tel.: +44 0116 246 1900



Project	Date
Item	Qty

Approved

PATHON/NOON TO INCHES

sammic

GLASSWASHER AX-40 DD

Rack size 400x400mm and door clearance 300 mm

SPECIFICATIONS

Basket dimensions: 400 mm x 400 mm Maximum glass height: 300 mm

Cycle duration: 90 / 120 / 180 "
Production baskets/hour: 40 / 30 / 20

Boiler capacity: 3.2 | Wash tank capacity: 9.0 | Water consumption/cycle: 2.2 |

Loading

✓ Pump: 250 W / 0.33 Hp

√ Tank: 1200 W

✓ Boiler: 2500 W

√ Total loading: 2750 W

!4Electrical supply: 230 V / 50 Hz / 1 \sim (12 A)

Electrical connection: --

External dimensions (WxDxH)

√ Width:470 mm

✓ Depth: 537 mm

✓ Height: 710 mm

Net weight: 36.5 Kg Noise level (1m.): <69 dB(A)

Crated dimensions

525 x 615 x 820 mm

AVAILABLE MODELS

1303083 Glasswasher AX-40 230/50/1 DD

* Ask for special versions availability



www.sammic.co.uk

Food Service Equipment Manufacturer Unit 2, Trevanth Road Troon Industrial Park LE4 9LS - Leicester





Project	Date
Item	Qty

Approved

	2
_	10/202
ee	110
S	29/1
<u> </u>	t P
product sheet	Incluted
٥	Ē