

Hamilton Beach
COMMERCIAL

BigRig™

Family of Immersion Blenders



Incredibly
FAST
Results

Blend, chop,
mix, puree,
and emulsify

Heavy-duty 1 Hp motor powers through soups, sauces, salsas, and salad dressings

Unique 2-position handle and ergonomic shaft grip maximize blending comfort and control

Variable speed dial has color-coded light for immediate feedback

Completely sealed stainless steel shaft easily removes for changing or cleaning

Continuous run operation for high-volume blending

High-visibility 12 ft./365cm yellow power cord

2 year warranty



Interchangeable Shaft

12"/305mm, 14"/355mm, 16"/406mm,
18"/457mm, and 21"/533mm available

For more Good Thinking® visit www.hamiltonbeachcommercial.com

NSF®

Hamilton Beach

COMMERCIAL



Detachable Stainless Steel Shaft with Ergonomic Grip

Makes it easy to hold the blender in a secure, steady position and removes for replacement or cleaning


Blend Volume Chart

- 12"/305mm shaft - up to 6 gal. (23 L)
- 14"/355mm shaft - up to 14 gal. (53 L)
- 16"/406mm shaft - up to 23 gal. (87 L)
- 18"/457mm shaft - up to 32 gal. (121 L)
- 21"/533mm shaft - up to 42 gal. (158 L)



Stainless Steel Blade with Guard

Blends, chops, purees, or emulsifies ingredients quickly



Optional 10"/25cm Whisk Accessory

Lets you whip and aerate ingredients (sold separately)



Patent-Pending Speed Dial with Color-Coded Light

Variable speed dial provides blending precision and light provides feedback about blender status

Serviceable Cord

Patent-pending design helps extend the immersion blender's life



Ergonomic Design with Easy-Touch Controls

Offers multiple hand positions for comfort



Wall Mount and Cord Holder

For neat, easy storage

IMMERSION BLENDER SERIES

SPECIFICATIONS:

	30.5" (78 cm)	32.5" (82 cm)	34.5" (88 cm)	36.5" (93 cm)	39.5" (100 cm)	19.5" (49 cm)
	8.5" (21.6 cm)	5.5" (14 cm)				4.5" (11 cm)
	HMI012	HMI014	HMI016	HMI018	HMI021	HMI02W
Shipping Weights:						
lbs	13.5	13.7	13.9	14.1	15.2	6.0
kg	6.1	6.2	6.3	6.4	7.0	2.7

Standard: unit comes with power base, stainless steel shaft, and wall-mount hanger
 Controls: Variable speed dial, trigger, power button
 Warranty: 2 year parts & labor
 Blend speeds: min. 3,000 rpm - max. 15,000 rpm

HMI (120V)	HMI-CE/-UK (230V)
120V~, 60 Hz, 750 W	220-240V~, 50-60 Hz, 750 W, IPX2