

# GLASS DOOR FREEZER COMPACT FG420R C DR G U

Product series: Compact Item number: 155422030

The HOSHIZAKI COMPACT FG420R C DR G U is a GLASS DOOR FREEZER on castors with a net usable volume of  $265\,\mathrm{Ltr.}$ 

The COMPACT series offers a rare combination: These cabinets are food-safe, space-saving, and come with excellent energy ratings for their class. With a footprint of only 59.5 x 66.7 cm, these small space storage cabinets are easy to fit in, especially when space is limited. These specifications make the series such a popular choice for those operators who do not require heavy-duty Gastronorm equipment.



Thanks to the Hoshizaki air distribution system, temperatures are correct and uniform throughout the entire cold room, ensuring perfectly food-safe temperatures at all times

### Low-Running Energy Costs

The Energy Efficiency Class of the COMPACT FG420R C DR G U is B. The COMPACT series offers a range of extremely energy-efficient refrigeration units for small spaces.

#### Comfortable Work Environment

Contributes to a healthier work environment with low noise levels 39.7 dB(A), when the compressor is running. Low heat emission due to short compressor running times.

#### Hygiene & Ergonomic Design

The COMPACT series features several design extras, implemented to simplify daily cleaning routines. One of the features for optimized operator safety is the full-height integrated handles.

#### The COMPACT FG420R C DR G U comes with:

Refrigerant: The GLASS DOOR FREEZER uses HC refrigerant R600a

Air circulation system

Right-hand hinged door

Integrated full-height door handle

Internal LED light

Reversible door

Door lock for extra security

White shelves

Automatic defrost with re-evaporation of defrost water

## **SPECIFICATIONS**

Product title	GLASS DOOR FREEZER	Energy Consumption (kWh/Year)	1,152
Temperature Range	-19/-5°C	Energy Efficiency Class Standard	ISO 23953-2019
Volume, Gross (ltr.)	343	Energy Efficiency Class	В
Net Usable Volume (ltr.)	265	Energy Efficiency Index EEI	15.9
Exterior	Stainless	Sound Level – dB(A)	39.7
Interior	White Finish	Climate Class	3 (maximum ambient temperatures of 25 °C with 60% RH)
Dimensions W x D x H (mm)	595 x 667 x 1901		<u> </u>
Weight, Packed (kg)	110	Legs / Castors	H = 100/130 mm
In a vitation (man)	50 (nahnathana)	Refrigerant (kg)	0.047
Insulation (mm)	52 (polyurethane)	CO2 equivalent (kg)	0.141
Refrigerant	R600a	CN or Tray Size (mm)	Shelf 483.8 x 433 mm
GWP	3	GN or Tray Size (mm)	Stieli 463.6 x 433 ttiiti
Ref. Capacity at -25°C (Watt)	217	Maximum number of shelves	26
Nei. Capacity at -25 C (Watt)	217	Number of shelves	5
Power Supply	230V, 50 Hz	Equipped with	Right hand hinged reversible glass door with
Connection Load (Watt)	140	Equipped with	lock, 5 white shelves, bottom shelf 484.7 (W) x 300 (D) mm, LED lighting. Exterior: Stainless. Interior: PS lining in white
		Door Type	Glass door