

GLASS DOOR REFRIGERATOR COMPACT KG420L C DR G U

Product series: Compact

Item number: 164422030

The HOSHIZAKI COMPACT KG420L C DR G U $\,$ is a GLASS DOOR REFRIGERATOR with a net usable volume of $\,$ 265 Ltr.

The COMPACT series offers a rare combination: These cabinets are food safe, space-saving, and come with excellent energy ratings for its class. With a footprint of only 59.5 x, 66.7 cm these small space storage cabinets are easy to fit in, especially when space is limited. These specifications make the series such a popular choice of those operators who do not require heavy-duty Gastronorm equipment.

Food Safety

Thanks to the Hoshizaki air distribution system, temperatures are correct and uniform throughout the entire cold room, ensuring perfectly food-safe temperatures at all times

Low-Running Energy Costs

The Energy Efficiency Class of the COMPACT KG420L C DR G U is D. The COMPACT series offers a range of extremely energy-efficient refrigeration units for small spaces.

Comfortable Work Environment

Contributes to a healthier work environment with low noise levels 39.8 dB(A), when the compressor is running. Low heat emission due to short compressor running times.

Hygiene & Ergonomic Design

The COMPACT series features several design extras, implemented to simplify daily cleaning routines. One of the features for optimized operator safety is the full-height integrated handles.

The COMPACT KG420L C DR G U comes with:

- Refrigerant: The GLASS DOOR REFRIGERATOR uses HC refrigerant R600a
- Air circulation system
- Right-hand hinged door
- Integrated full height door handle
- Internal LED light
- Reversible door
- Door lock for extra securityWhite shelves
- Automatic defrost with re-evaporation of defrost water

SPECIFICATIONS

| Product title | GLASS DOOR REFRIGERATOR | Energy consumption Ecodesign AEC (kWh/Year) | 670 |
|---|-------------------------|---|---|
| Temperature range | +1/+12°C | | |
| Volume, gross (ltr.) | 343 | Energy Efficiency Class (ISO 22041-2019) | D |
| Net usable volume (ltr.) | 265 | Energy Efficiency Index EEI | 64.1 |
| | | Sound level – dB(A) | 39.8 |
| Exterior | White Finish | Climate class | 4 |
| Interior | White Finish | Legs / Castors | H = 125 mm (C2) |
| Dimensions W x D x H (mm) | 595 x 667 x 1900 | | . , |
| Weight, packed (kg) | 99 | - Refrigerant (kg) | 0.048 |
| Insulation (mm) | 52 mm (polyurethane) | CO2 equivalent (kg) | 0.144 |
| Refrigerant | R600a | GN – Shelf size | Shelf 483.8 x 433 mm |
| | | Maximum number of shelves | 26 |
| GWP | 3 | Number of shelves | 5 |
| Refrigeration capacity at -10°C (Watt) | 122 | Equipped with | Right hand hinged reversible glass door with |
| Connection | 230V, 50 Hz | | lock, 5 white shelves, bottom shelf 484.7 (W) x 300 (D) mm, LED lighting. Exterior: White. Interior: PS lining in white |
| Connection load (Watt) | 130 | Door Type | Glass door |

