

GLASS DOOR REFRIGERATOR COMPACT KG420R C DR G U

Product series: Compact Item number: 154422030

The HOSHIZAKI COMPACT KG420R C DR G U is a GLASS DOOR REFRIGERATOR with a net usable volume of $\,265\,\mathrm{Ltr.}$

The COMPACT series offers a rare combination: These cabinets are food safe, space-saving, and come with excellent energy ratings for its class. With a footprint of only 59.5 x, 66.7 cm these small space storage cabinets are easy to fit in, especially when space is limited. These specifications make the series such a popular choice of those operators who do not require heavy-duty Gastronorm equipment.



Thanks to the Hoshizaki air distribution system, temperatures are correct and uniform throughout the entire cold room, ensuring perfectly food-safe temperatures at all times

Low-Running Energy Costs

The Energy Efficiency Class of the COMPACT KG420R C DR G U is D. The COMPACT series offers a range of extremely energy-efficient refrigeration units for small spaces.

Comfortable Work Environment

Contributes to a healthier work environment with low noise levels 39.8 dB(A), when the compressor is running. Low heat emission due to short compressor running times.

Hygiene & Ergonomic Design

The COMPACT series features several design extras, implemented to simplify daily cleaning routines. One of the features for optimized operator safety is the full-height integrated handles.

The COMPACT KG420R C DR G U comes with:

- Refrigerant: The GLASS DOOR REFRIGERATOR uses HC refrigerant R600a
- Air circulation system
- Right-hand hinged door
- Integrated full height door handle
- Internal LED light
- Reversible door
- Door lock for extra security
- White shelves
- Automatic defrost with re-evaporation of defrost water

SPECIFICATIONS

Product title	GLASS DOOR REFRIGERATOR
Temperature range	+1/+12°C
Volume, gross (ltr.)	343
Net usable volume (ltr.)	265
Exterior	Stainless
Interior	White Finish
Dimensions W x D x H (mm)	595 x 667 x 1900
Weight, packed (kg)	99
Insulation (mm)	52 mm (polyurethane)
Refrigerant	R600a
GWP	3
Refrigeration capacity at -10°C (Watt)	122
Connection	230V, 50 Hz
Connection load (Watt)	130

Energy consumption Ecodesign AEC (kWh/Year)	670
Energy Efficiency Class (ISO 22041-2019)	D
Energy Efficiency Index EEI	64.1
Sound level – dB(A)	39.8
Climate class	4
Legs / Castors	H = 125 mm (C2)
Refrigerant (kg)	0.048
CO2 equivalent (kg)	0.144
GN - Shelf size	Shelf 483.8 x 433 mm
Maximum number of shelves	26
Number of shelves	5
Equipped with	Right hand hinged reversible glass door with lock, 5 white shelves, bottom shelf 484.7 (W) x 300 (D) mm, LED lighting. Exterior: Stainless. Interior: PS lining in white
Door Type	Glass door