

Product Code: EP700HL 41-487

Single door dual temp cabinet



The EcoPro G3 range of cabinets offers a combination of cutting-edge refrigeration technology, low running costs and reliability, making them the first choice for the foodservice professional.

Features & Benefits

- Foster Shield provides advanced temperature control and hygienic design, protecting from the dangers of unsafe food storage. With air distribution optimised by CFD design technology, efficient operation is assured, even when shelves are fully loaded
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- This model offers refrigerator and freezer temperatures in the same cabinet perfect for when space is at a premium
- Market leading usable capacity, now supplied with 4 shelves as standard making your money go further holds more than a conventional fridge
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 the gold standard in performance stainless steel meaning the heaviest usage touchpoints on the product are covered
- Operates efficiently in ambient temperatures of up to 43°C

Shelving		Base Fitti	ngs		
Extra heavy duty shelving	Option	Castors 80mm	Sta	ndard	Half
4 shelves (GN2/1)	Standard	Legs 150mm	C	Option	
Refrigeration		Electrical & Serv	vice Data		Helicoil
R290 - Energy Efficient	Standard	230/50/1	Sta	ndard	
Integral Refrigeration System	Standard	Fuse Required (A)		10	
Less Condensing Unit	Option	Finish			
Specification		s/steel ext, 304 s/s door &	alu int Sta	ndard	
Gross volume (Itrs)	600	304 S/S back for island sit	ting C	ption	
Dual temp +1/+4°C 18/-21°C	Standard				
Width (mm)	700				
Depth (mm)	870				
Height (mm)	2080				

Footnotes

- Castors not available if product supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 100mm
- Depth with door open is 1500mm



The Refrigeration Experts

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.