GLASSWASHER GP-35 230/50/1 DD
Rack size 350x350mm and door clearance 240 mm.

1303033

✓ Easy access to components for repair.

INCLUDES

✓ Peristaltic Detergent Pump

SPECIFICATIONS

Basket dimensions: 350 mm x 350 mm
Maximum glass height: 240 mm

Cycle duration: 90 " / 120 " / -- "
Production baskets/hour: 45 / 30 / --

Boiler capacity: 3.2 l
Wash tank capacity: 12.7 l
Water consumption/cycle: 2.2 l

Loading

✓ Pump: 75 W / 0.1 Hp

✓ Tank: 1200 W

✓ Boiler: 2500 W

✓ Total loading: 2575 W

Electrical supply: 230 V / 50 Hz / 1 ~ (11.2 A)
Electrical connection: --

External dimensions (WxDxH)

✓ Width:420 mm

✓ Depth: 495 mm

✓ Height: 645 mm

Net weight: 30 Kg
Noise level (1m.): -- dB(A)

Crated dimensions
485 x 590 x 690 mm
Gross weight: 33 Kg.

ACCESSORIES

❑ Stands for glass- and dishwashers
❑ Manual water softeners
❑ Automatic water softeners
❑ 350X350 mm. baskets
❑ Ø360 / Ø380 mm. baskets
❑ Inserts & supplements
❑ High Feet Kit
❑ Reverse Osmosis device OS-140P

SALES DESCRIPTION

Sani-Control guarantee

✓ GUARANTEED DISINFECTION in compliance with standard DIN 10534.

✓ THERMAL LOCK function: Ensures that rinsing will be carried out at the ideal temperature to disinfect the dishes.

✓ Upper and lower washing.

✓ Construction in stainless steel AISI 304 2B.

✓ Interior with rounded finishes to prevent the accumulation of dirt.

Double filter system

✓ Maximum protection of the washing pump.

Double-walled door

✓ Double-walled door, safety microswitch and high quality seal: perfectly soundproof and watertight.

Warewashing, made simple

✓ GP Xperience: simple and intuitive use.

✓ Dedicated cycles: selection of the ideal washing programme using icons.

✓ Electronic control panel with IP65 humidity protection.

✓ 100% Tested.

Tech-friendly

✓ Tool-free extraction of diffusers and filters for maintenance and cleaning

Project		Date
Item		Qty
Approved		