GLASSWASHER GP-50 230/50/1 DD

Rack size 500x500mm and door clearance 260 mm

1303162



SALES DESCRIPTION

Sani-Control guarantee

- ✓ GUARANTEED DISINFECTION in compliance with standard DIN 10534.
- ✓ THERMAL LOCK function: Ensures that rinsing will be carried out at the ideal temperature to disinfect the dishes.
- ✓ Upper and lower washing.
- ✓ Construction in stainless steel AISI 304 2B.
- √ Interior with rounded finishes to prevent the accumulation of dirt.

Double filter system

Maximum protection of the washing pump.

Double-walled door


√ Double-walled door, safety microswitch and high quality seal: perfectly soundproof and watertight.

Warewashing, made simple

- ✓ GP Xperience: simple and intuitive use.
- ✓ Dedicated cycles: selection of the ideal washing programme using
- ✓ Electronic control panel with IP65 humidity protection.
- √ 100% Tested.

Tech-friendly

√ Tool-free extraction of diffusers and filters for maintenance and cleaning



NCLUDES

✓ Peristaltic Detergent Pump

SPECIFICATIONS

Basket dimensions: 500 mm x 500 mm Maximum glass height: 260 mm

Cycle duration: 90 " / 120 " / -- " Production baskets/hour: 45 / 30 / --

Boiler capacity: 4.5 I Wash tank capacity: 23 I Water consumption/cycle: 2.7 I

Loading

- ✓ Pump: 500 W / 0.75 Hp
- √ Tank: 1800 W
- √ Boiler: 2500 W
- √ Total loading: 3000 W

Electrical supply: $230 \text{ V} / 50 \text{ Hz} / 1 \sim (13 \text{ A})$

Electrical connection: --

External dimensions (WxDxH)

- √ Width:580 mm
- ✓ Depth: 630 mm
- ✓ Height: 710 mm

Net weight: 52 Kg

Noise level (1m.): -- dB(A)

Accessories

- ☐ Stands for glass- and dishwashers
- Manual water softeners
- Automatic water softeners
- □ 500 x 500 mm. baskets
- ☐ Inserts & supplements
- ☐ High Feet Kit
- ☐ Reverse Osmosis device OS-140P



sammic





www.sammic.co.uk

Food Service Equipment Manufacturer Unit 2, Trevanth Road Troon Industrial Park LE4 9LS - Leicester

uksales@sammic.com Tel.: +44 0116 246 1900



Project	Date
Item	Qty

Approved