



All the features of a high-end toaster... with a low-end price

The Hatco Toast-Max economy conveyor toaster offers the flexibility and performance to perfectly toast bread and buns fast – up to 300 slices per hour! Using the conveyor speed, not temperature, to determine toasting color allows for instant adjustment of toasting time.

- Long lasting serpentine metal sheathed heating elements
- 102 mm adjustable legs
- Pilot light that signals unit is in operation
- Discharge and crumb trays are removable for easy cleaning
- 4-position toast selector switch: off / toast / buns / stand-by mode
- 50 mm clearance to accommodate EU market bread products
- Easy-to-load rack with front or rear discharging
- Permanently lubricated 50/60 Hz motor
- V-shaped reflectors help capture and redirect heat











TOAST-MAX ™ CONVEYOR TOASTERS

Models TM-5, -10









Models TM-10

SPECIFICATIONS


Model	kW	Туре	Cap./Min.†	Shipping Weight
TM-5	1.3	Bread & Buns	3 slices	16kg
TM-10	1.9	Bread & Buns	6 slices	19kg

Models TM-5

SELECTOR CHART

(Based on serving 2 slices per customer.)

Number of Customers	Serving Time TM-5	Serving Time TM-10	
30	24 minutes	12 minutes	
60	48 minutes	24 minutes	
90	72 minutes	36 minutes	
120	96 minutes	48 minutes	



Product Flow

DIMENSIONS

TM-5: 290 W x 419 D x 387 H mm, Tray extends 196 mm in rear TM-10: 368 W x 420 D x 387 H mm, Tray extends 195 mm in rear

Interior Cavity Openings:

TM-5: 186 W x 50 mm H TM-10: 264 W x 50 mm H

Maximum Product Size:

245 W x 64 mm H

CORD LOCATION

Left side of back of unit near center.

PLUG CONFIGURATIONS



ELECTRIC RATING

Model	Volts	Watts	Amps	Hz
TM-5	220-240	1340-1595	6.1-6.6	50-60
TM-10	220-240	1940-2300	8.8-9.6	50-60



HATCO CORPORATION P.O. Box 340500 Milwaukee, WI 53234-0500 U.S.A. • (414) 671-6350 Int'l. Fax (414) 671-3976 • www.hatcocorp.com • E-mail: intlsales@hatcocorp.com

[†] Toasting capacity may vary by product. Toasting of coated products is not recommended.