

Fume Filtration

Lincat's fume filtration units are the ideal companion to Lynx 400 and Silverlink 600 electric appliances. The three part filter system comprises a washable aluminium mesh for removing large grease particles; a washable foam layer which absorbs fine grease particles; and a replaceable activated charcoal filter. These essential kitchen items reduce grease deposits and remove cooking odours to create a clean and fresh working environment.



L4

Features


- Powerful centrifugal fans draw cooking fumes through a three part filtration system
- · Cleansed air is expelled at top rear of unit
- Hinged top panel gives easy access for cleaning and filter maintenance
- Overheat protection system cuts power to fans in the event of a cooking appliance fire
- Suitable for use above electric appliances with a maximum depth of 600mm (Note: Not suitable for use with gas appliances.)

Lincat





1/1



Integral lighting



Technical Specifications

- Volumetric flow rate per fan: 230 m³ per hour
- Volume of air filtered per hour:
- 460 m³ (L3)*
- 690 m3 (L4)*
- Recommended mounting height above appliance: 800mm

Product Code	Description	Height (mm)		Depth (mm)		Net Weight (kg)
L3	Fume Filtration Unit	545	915	610	0.35	26
L4	Fume Filtration Unit	545	1295	610	0.45	35

 $^{^{\}ast}$ Volume of air filtered through a new unit. This will decrease as the filters are used.



QUALITY GUARANTEED

You can choose Lincat products with confidence. All products in this leaflet are backed by the reassurance of a comprehensive UK twelve months parts and labour warranty.

