



BELT DRIVEN SLICERS



GCP-250		
		139: 250 mm
· BELT DRIVEN.		- 504: 190 mm x 250 mm
		505: 0 mm - 15 mm
Blade diameter: 250mm		370: 260 mm
		306: 300 W
		445: 230 V / 50 Hz / 1 ~
· Made of special aluminium alloy, anticorrosive and hygienic.		- 448
· Belt driven professional slicer with ring, carriage lock and blade removal tool. Heavy duty, ventilated motor.		177: 580 mm
Complete with permanently attached blade sharpenig apparatus. This appliance has been designed and manufactured in compliance with 89/392/ EEC, 93/68/EEC and 73/23/EEC Directives.		180: 470 mm 172: 370 mm
<ul> <li>Please note: as a result of continuous product improvements, these specifications are subject to change without prior notice.</li> </ul>		286: 18 Kg
DEFAULT EQUIPMENT	OPTIONAL EQUIPMENT	-
DEFAULT EQUIPMENT	OPTIONAL EQUIPMENT	
AENOR		
Empresa Registrada ER-0437/1/96 UNE-EN ISO 9001		
SAMMIC, S L. (Sociedad Unipersonal) Basarte, 1 - 20720 AZKOITIA - www.sammic.com		
1935/2004/CE,2003/108/CE, 2002/95/CE; 2006/42CE/,91/368CEE,92/31CEE,2004/108/ EN-1974:1998+A1:2009 CE,93/68CEE,93/44CEE,2006/95/CE,		