

GLASSWASHER UX-40B 230/50/1 DD

Rack size 400x400mm and door clearance 300 mm

1303107



SALES DESCRIPTION

Sani-Control: guaranteed disinfection

Embedded bodywork and easy-grip door: hygienic and ergonomic

Exclusive Hydroblade™ washing arms: maximum effectiveness.

3-stage filtering system.

Double-walled body (partial).

Sani-Control guarantee

- GUARANTEED DISINFECTION in compliance with standard DIN 10534.
- THERMAL LOCK function: Ensures that rinsing will be carried out at the ideal temperature to disinfect the dishes.

New recessed bodywork

- Ergonomic design with rounded corners to prevent the accumulation of dirt and facilitate cleaning.
- Compact tank volume (50% water saving compared to the previous
- √ Embedded basket guides

Hydroblade™ washing arms

- Redesigned nozzles for greater washing performance.
- √ The "monoblock" design delivers durability and resistance to impacts.

30% savings in water consumption during rinsing compared to the previous range.

3-stage filter system: surface, tank and extraction

- Keeps the washing water in optimal conditions to maintain constant washing performance.
- √ The surface filters feature an "easy-on" design and can be quickly. removed without having to disconnect the washing arms.

"Easy grip" door: new design with integrated door handle

- √ The integration of the components provides greater resistance and
- Designed to have no corners or areas that are difficult to access: prevents deposits of dirt and facilitates cleaning.
- ✓ Its ergonomic handle provides a perfect grip, even with wet hands.
- ✓ Double-walled door with safety microswitch and high quality seal
- 30 cm load capacity: high versatility for washing a wide range of glasses and even medium-sized dishes.

Premium warewashing

- ✓ Ultra Xperience: high performance, without complications.
- Soft start: progressive start-up of the washing pump to protect
- Colour LCD Display: intuitive communication of the machine status by means of messages, colour codes and icons.
- Dedicated cycles: selection of the ideal washing programme using
- Adaptable: allows the main parameters of the machine to be adjusted to the needs of each user.
- √ TEMPERATURE DISPLAY
- √ Wash Plus+ function: increases the intensity of the wash cycle for greater cleaning performance
- Control panel with IP65 humidity protection.

You will never WASH ALONE

- Tech-Services: our team of technicians will help you so that your machine is always ready for use.
- Design Services: tell us what your needs are and we will advise you.
- √ 60 years of experience and know-how at your disposal.

NCLUDES

✓ Detergent Dispenser. √ 1 mixed basket (plates). √ 1 glasses basket. 1 small basket for cutlery.

Accessories

- Manual water softeners
- Automatic water softeners ☐ 400X400 mm. baskets
- ☐ Inserts & supplements
- High Feet Kit
- ☐ Reverse Osmosis device OS-140P
- ☐ Stand for 400x400 mm glasswashers
- Double rack kit for AX/UX-40







sammic

www.sammic.co.uk

Food Service Equipment Manufacturer Unit 2 Treventh Road Troon Industrial Park LE4 9LS - Leicester

uksales@sammic.com Tel.: +44 0116 246 1900



Project	Date
Item	Qty

Approved

PULL SAVA SHEVING TO THE SHEET SHEET

<u>გ</u>

GLASSWASHER UX-40B 230/50/1 DD

Rack size 400x400mm and door clearance 300 mm

1303107

SPECIFICATIONS

Basket dimensions: 400 mm x 400 mm Maximum glass height: 300 mm

Cycle duration: -- "/--"/--"
Production baskets/hour: --/--/--

Boiler capacity: 4.5 I Wash tank capacity: 9 I

Consumption and savings

Water consumption/cycle: 1.9 | Automatic saving mode in: 25 ' Automatic switch-off: 120 '

Loading

✓ Pump: 250 W / 0.33 Hp

√ Tank: 1200 W

✓ Boiler: 2500 W

√ Total loading: 2750 W

Electrical supply: $230 \text{ V} / 50 \text{ Hz} / 1 \sim (12 \text{ A})$

External dimensions (WxDxH)

√ Width:470 mm

✓ Depth: 540 mm

✓ Height: 710 mm

Net weight: 39.5 Kg Noise level (1m.): <69 dB(A)

Crated dimensions

525 x 615 x 820 mm Gross weight: 45.5 Kg.



www.sammic.co.uk

Food Service Equipment Manufacturer Unit 2, Trevanth Road Troon Industrial Park LE4 9LS - Leicester

uksales@sammic.com Tel.: +44 0116 246 1900



	Project	Date
	Item	Qty

Approved