

Vesta H2, Athena H2, Melody II Manual Addendum

Recommended Method for Manually Adjusting Power Settings

While AutoAdjust automatically provides very fine real-time adjustments to the pulse width, you can also manually adjust the power to best suit your unique water quality and desired performance requirements. By manually changing the power-steps for each Alkaline and Acidic level, you can change the main power settings, making bigger and more impactful changes in performance. There are 4 Power Levels (1-4). Power Level 1 is the lowest and Power Level 4 the highest. Follow this procedure to adjust the Power Levels:

- 1. Start with unit plugged in, water flow turned off..
- 2. Simultaneously press and hold the Alkaline 1 and Alkaline 2 buttons for 3—5 seconds, until the screen looks like Fig. 1.



Fig. 1

3. Press and release the Alkaline 2 button 6 times. The display should now look like Fig. 2



Fig. 2

4. Each time the Acidic 1 button is pressed, the display will cycle through the alkaline and acidic levels, first in Forward polarity and then in Reverse polarity. (refer to Fig. 3a, 3b, and chart 3c)

5. Pressing and releasing the acidic 2 button will change the power step (indicated on the display by the digit on the right.)






Fig. 3a Fig. 3b

Level	Forward Polarity Displayed As:	Reverse Polarity Displayed As:
Alkaline 1	1	11
Alkaline 2	2	12
Alkaline 3	3	13
Alkaline 4	4	14
Alkaline 5	5	15
Acidic 1	6	16
Acidic 2	7	17

Fig. 3c

- 6. When setting the power step for a particular level, for best results, be sure to set the power step to the same setting for <u>both</u> the forward and reverse polarity.
- 7. When all levels are set as desired, simultaneously press and release the Alkaline 1 and Alkaline 2 buttons to return the display to stand by.