

# 2019 - 2022 RANGER HUD INSTALL GUIDE

## STEP 1

Plug the connector from the kit into the Rangers OBDII port.

*\*The port should be located under the steering column on the left side. \**



## STEP 2

Run the wire from the connector along with the side panel of the truck to the dashboard of the truck.

*\*It is helpful to use a pry tool or a flathead screwdriver. \**

The red line in the picture below shows where to tuck the wire when running it to the dashboard.







# STEP 3

Once the wire is run up this panel tuck it under the plastic trim piece seen in the photos below.





## STEP 4

Continue to hide the wire by tucking it in between the plastic dash piece shown below.



*\*If you have any excess wire, you can tuck it down in between the plastic dash piece and the windshield.\**





## STEP 5

Now that the wire is run to the front of the dash, connect the wire to the HUD unit, then based off of preference decide where you would like to mount the unit. Once you have decided where you would like to mount the unit, use the included prep wipes to clean the surface where it will be mounted.






Then remove the protective covering from the 3m adhesive on the bottom of the unit and firmly press down on the unit for 20-30 seconds to mount the unit to the dash.





## STEP 6

Make sure that the kit is on so that you can see the numbers displayed on the windshield, then take the reflective film that comes with the kit and stick it on the windshield where the numbers are reflecting to enhance the display of the kit.



Text for support: 706-214-2618

Visit our site to chat: [www.F150LEDs.com](http://www.F150LEDs.com)  
or email [CustomerSupport@F150LEDs.com](mailto:CustomerSupport@F150LEDs.com)

