

Important Safety Issues:

- This product must be installed by a qualified electrician according to AS/NZS 3000.
- Ensure all electrical mains are disconnected before any installation. .
- Modification of this product will void any warranty.
- Havit Lighting does not take responsibility for wrong installation, incorrect use, or use of installation material that does not belong to the system.
- Aluminium and 304SS fittings must not be installed within 5km of any salt water environments.
- All o-rings and seals must be in place correctly to maintain warranty
- This form may be updated at any time due to product improvements, please check online installation form for most current version.

Steps for Installation:

- 1. Make sure that the electrical circuit is free of voltage (master switch off)
- 2. Loosen allen screws on side of base and separate mounting bracket from fitting.
- 3. Install the backing plate securely using appropriate screws for application.
- 4. Adjust cable to desired length and remove excess.
- 5. Connect the cable: Use wire with earth, connect earth first then positive and then neutral
- 6. Reattach fitting to base and tighten allen screws.
- 7. Fitting is preset to 3000k, To change loosen allen screws at top of pendant
- 8. Slide switch located inside to desired colour temperature
- 9. Reattach Pendant and tighten alen screws.
- 10. All connections must be carried out carefully, inspect all contacts before switching back on the electric circuit.

Must be installed by a licensed electrician

Contact Details:		Warranty Terms & Conditions*	Additional Information
143 Beauchamp Road Matraville NSW 2036 Australia	Tel: 02 9381 8300 Fax: 02 9666 8881 Email: sales@havit.com.au Web: www.havit.com.au		