

50 Metre Rolls

- LED flexible strip light 50m roll
- Dimmable
- Peel and stick backing for initial placement
- Beam angle 120 degrees
- All LED strip must be installed using anti-static measures and on an aluminium heat dissipating surface for warranty purposes (HV9705-1003, HV9705-1603 or HV9705-2003)
- Supplied with 25x easy connect tails



3000K

IMAGE	PART NUMBER	SMD	IP RATING	LED PER METRE	LUMENS PER METRE	VOLTAGE	WATTAGE PER METRE	MAX LENGTH	CUTTING INCREMENT	SIZE WXH
	HV9723-IP20-60-3K-50M	3528	IP20	60	390lm	12v DC	4.8w/m	5m	50mm	8x2mm
	HV9723-IP20-120-3K-50M	3528	IP20	120	780lm	12v DC	9.6w/m	5m	25mm	8x2mm

WARRANTY VOID IF MAXIMUM CUT LENGTH EXCEEDS 5 METRES

4000K

IMAGE	PART NUMBER	SMD	IP RATING	LED PER METRE	LUMENS PER METRE	VOLTAGE	WATTAGE PER METRE	MAX LENGTH	CUTTING INCREMENT	SIZE WXH
	HV9723-IP20-60-4K-50M	3528	IP20	60	410lm	12v DC	4.8w/m	5m	50mm	8x2mm
	HV9723-IP20-120-4K-50M	3528	IP20	120	820lm	12v DC	9.6w/m	5m	25mm	8x2mm

WARRANTY VOID IF MAXIMUM CUT LENGTH EXCEEDS 5 METRES

5500K

IMAGE	PART NUMBER	SMD	IP RATING	LED PER METRE	LUMENS PER METRE	VOLTAGE	WATTAGE PER METRE	MAX LENGTH	CUTTING INCREMENT	SIZE WXH
	HV9723-IP20-60-5K-50M	3528	IP20	60	430lm	12v DC	4.8w/m	5m	50mm	8x2mm
	HV9723-IP20-120-5K-50M	3528	IP20	120	860lm	12v DC	9.6w/m	5m	25mm	8x2mm

WARRANTY VOID IF MAXIMUM CUT LENGTH EXCEEDS 5 METRES

All LED strip must be installed on an aluminium heat dissipating surface



All low voltage products that specify an input of 12v or 24v DC must be used with a suitable LED driver, refer to pages 267 - 274
Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to page 334