

Auto



Y420301

3 Ton Long Reach Trolley Jack
(Hydraulic)



Model: Y420301

Product: 3 Ton long reach trolley jack

Description: Ideal for servicing truck fleets, buses, farm machinery, heavy construction equipment and other vehicles that require a low starting point and relatively high reach.

Winntec Premium Series Trolley Jacks are designed and built to the highest standards especially for extreme heavy-duty lifting.

Manufactured using high quality materials and constructed in accordance with the latest and most advanced techniques.

Features:	Benefits:
3-Ton Capacity	This trolley jack is capable of lifting vehicles and loads weighing up to 3 tons, making it suitable for a wide range of vehicles and equipment.
Foot operated pump	Efficient lifting
Long Reach	The "long reach" feature means that it has an extended lifting arm or reach, allowing you to access hard-to-reach lifting points under vehicles or equipment with low ground clearance.
Easy and simple to use	You just wheel it under your vehicle to the safest lifting point and then activate the lifting mechanism by pumping the handle socket with an attached handle. A hydraulic jack is easy to use and requires little physical effort to produce the tremendous lifting force that can safely raise your car off the ground.
Easy to Maneuver	The long jack can be moved around and below a vehicle with ease and precision due to the fact it has wheels/castors on the front and rear. The wheels contain ball bearings which allow them to swivel up to 360 degrees, thereby enabling you to get the jack into the most awkward of spaces with minimal effort.
Safe and Stable	The jack is designed for safe car lifting and stability. Stability is gained through the base size of the trolley. The wheels can also help keep the jack in the correct position to prevent it from leaning over the way some other jacks do. You must never, however, rely on a trolley jack only to keep a vehicle raised to work under it - these are for raising only, not bearing weight for a period of time. You should always place jack stands below a vehicle after lifting it off the ground. It's also crucial to ensure these jacks are only used on a solid and level surface.

Solid and Robust	The trolley jack is a heavy-duty workhorse that is built to last. The solid build of the jack means it can stand up to all the bumps and knocks it will encounter in any automotive repair garage or other location.
Premium European design	Recognizing the demand for high performance work shop products, Winntec sourced the best quality components and developed a range of premium work shop equipment which offers excellent value for money. Choosing Winntec means choosing certainty in terms of quality, functionality and after sales service. It's the experience which makes the difference !
Safe and Stable	The jack is designed for safe car lifting and stability. Stability is gained through the base size of the trolley. The wheels can also help keep the jack in the correct position to prevent it from leaning over the way some other jacks do. You must never, however, rely on a trolley jack only to keep a vehicle raised to work under it - these are for raising only, not bearing weight for a period of time. You should always place jack stands below a vehicle after lifting it off the ground. It's also crucial to ensure these jacks are only used on a solid and level surface.
Wheels and Casters	Comes with wheels and casters, making them easy to maneuver and position under the vehicle or load.
Saddle and Lifting Pad	Comes with a saddle and lifting pad, which provide a stable and secure contact point with the load. Some models may have adjustable saddle heights for added versatility.
Handle	A handle or lever is used to pump the hydraulic fluid and lift the load. Long handle for added leverage.
Safety Features	Overload protection to prevent overloading and a release valve for controlled lowering of the load.
Compact Design	Despite its lifting capacity, trolley jacks are relatively compact and can be easily stored when not in use.
	Efficient Lifting: The hydraulic operation of the trolley jack makes lifting heavy loads efficient and requires less physical effort compared to manual jacks
	Versatility: The 3-ton capacity makes it suitable for lifting a wide range of vehicles, including cars, SUVs, and light trucks. It can also be used for various industrial applications.

	Accessibility: The long reach feature allows you to access lifting points that may be difficult to reach with standard jacks, making it useful for vehicles with low ground clearance.
	Stability: The saddle and lifting pad provide a stable and secure contact point with the load, reducing the risk of accidents during lifting.
	Maneuverability: The wheels and casters make it easy to position the trolley jack precisely where you need it, improving overall usability.
	Time-Saving: Using a hydraulic trolley jack can save you time and effort when performing maintenance tasks or repairs on vehicles and equipment.
	Durable: These jacks are typically built to be durable and withstand heavy use, making them a long-lasting investment.
	Safety: Safety features like overload protection and controlled lowering enhance the safety of using the trolley jack, reducing the risk of accidents or damage.
Training available	Technicians can be professionally trained to use the equipment and get the maximum benefit from it.
1 year warranty	The machine will be repaired if there are any factory faults and can be replaced if required.
Spares available	Should you have a breakdown you will not have to wait for your equipment to be repaired. If there is anything we don't have, we fly it in directly from the Suppliers.
Operational videos	Technicians can learn how to operate the equipment by watching a video, which is easier and more simple than written instructions.

Important notice!

- Trolley jacks are not a long-term support to lift vehicles.
- Jack stands/trestles to be used with trolley jacks as they are designed to hold weight of the vehicle for extended periods - as per SANS71 & Driven Machinery ACT.
- The load must be supported by a load bearing structure.

Technical information	
Min height	130mm
Max height	600mm
Width	325mm
Length	1400mm
Height	1330mm
Weight	65kg

