

0318



LEAK STOPPER RUBBERIZED ROOF PATCH Data Sheet

- Stops roof leaks instantly
- Lasts 2-3x longer than other patches
- Fiber reinforced
- Flexes to prevent cracking
- Highest penetrating repair

WHAT IS IT? Leak Stopper® is a revolutionary advancement in roof patching and repair. This long lasting rubberized repair is specially formulated to penetrate deep into damaged areas and stop roof leaks instantly! The secret is Penetrex™, a unique penetrating oil that reaches deep into the crack and forms a complete seal. With the addition of liquid rubber, this flexible, high performance plastic cement provides a superior water-tight bond that will stop problem leaks for good.

WHAT IT DOES... Stops roof leaks instantly.

WHAT IS NEEDED TO COMPLETE THE JOB? Trowel, putty knife, gloves and reinforcing fabric.

PREP THE AREA... Surfaces must be clean, free of surface rust and loose material.

HOW TO APPLY.... Use trowel to spread across damaged surface of roof. Embed reinforcing fabric after first layer and apply second layer on top of fabric.

HOW MUCH DO I NEED?... Covers approximately 3 sq. ft. per quart.

DO's and DON'Ts... Do apply in exterior applications only. Do wear protective clothing. Don't apply to plastic, EPDM, Hypalon or similar type of synthetic rubber roof system. If there is a question on compatibility, test a small section first before application to entire surface area.

FOR BEST RESULTS... It is highly recommended to reinforce the repair with a strip of **Universal Patching Fabric**. Work material to an even consistency over and into the area to be repaired approximately 1/8" to 1/2" thick, two or three inches beyond the problem area. Embed fabric into the cement and cover with a second layer of cement. Form a feathered edge with cement where chimney's, vent pipes, and other projections meet the roof line. **DO NOT EXPOSE DIRECT HEAT/FLAMES OR THIN.** Best used when surface temperatures are between 50° and 120 F. In colder weather (50° and below), product should be stored in heated room (70° to 80°F.) at least 24 hours prior to application to promote ease of application. Product formulated to be used year round.

PRECAUTIONS: Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and can secure and upright. Do not allow can to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100°F. Do not reuse empty containers. Do not use in drinking water or food systems. **KEEP FROM FREEZING.**

HOW TO CLEAN-UP... Clean tools and spills with paint thinner or mineral spirits.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Weight Per Gallon, lbs.	8.2-8.7 lbs.
Residue by Evaporation, %	80 min.
Flexibility	Good. Stretches to resist cracks
Combustible Solvents	Mineral Spirits
Consistency	Trowel
Cure Time (at recommended coverage rate)	4-8 hrs to set - 24-48 hrs to cure depending on surface & weather
Application Temperature	50°-120°F
Flammability (Flash pt. °F solvent)	105°
Clean-up Tools	Paint thinner, mineral spirits

Approx. Shipping Weights: (Note: All approx. weights include container.)

1 gallon (3.8L)	9 lbs.
(6) 1 gallon containers/case	54 lbs.
55 gallons (18.9L)	44 lbs.

**CAUTION!: COMBUSTIBLE.
HARMFUL OR FATAL IF SWALLOWED.
KEEP OUT OF REACH OF CHILDREN.
FOR EXTERIOR USE ONLY.
USE WITH ADEQUATE VENTILATION.**

Do not get in eyes or on skin or clothing. Do not breathe fumes. Keep away from flames, such as a pilot light, and any object that sparks, such as electric motor. Wear safety glasses and chemical resistant gloves.

PETROLEUM ASPHALT	CAS # 8052-42-4
CLAY	CAS # 1332-58-7
MINERAL SPIRITS	CAS # 8052-41-3
CELLULOSE FIBER	CAS # 9004-34-6
POLYMER BINDER	CAS # PROPRIETARY

Eye and skin irritant. In case of contact with eyes, flush with plenty of clean, room temperature water. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid contact with skin and breathing vapor. If swallowed, do not induce vomiting. Call physician immediately. Seal container when not in use.

CALIF. PROP. 65 • WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. Use proper protection and adequate ventilation, when using product.

VOC/VOS - 250 g/L max (2.07 lbs./gal.)

COMPLIANCE: ASTM 6511, TYPE I

Asbestos free product. US PATENT PENDING

WARRANTY AND DISCLAIMER:

For limited warranty and disclaimer information, contact the Gardner-Gibson, Inc. corporate office at 1-800-237-1155 or www.gardner-gibson.com.

© 2009 Gardner-Gibson, Inc.
Manufactured by:
Gardner-Gibson, Inc.,
P.O. Box 5449, Tampa, FL 33675
www.gardner-gibson.com

See MSDS for more info



Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardner-gibson.com