

0338



LEAK STOPPER CLEAR RUBBERIZED ROOF PATCH Data Sheet

- Provides “invisible” patch
- Stops leaks instantly
- Flexes to prevent cracking
- Goes on white - dries clear
- Outlasts other repairs
- Stays clear longer-won't yellow!

USE ON THESE ROOF SURFACES: Asphalt Shingle, Slate, Tile, Metal, & Wood Shake Roofs. **ALSO SEALS TO AND AROUND:** Skylights, Wood, Glass, Stucco, Brick, Stone, Gutters, Chimneys and Siding.

WHAT IS IT? This advanced clear sealant has outstanding adhesion to a variety of surfaces, and provides a long lasting rubberized seal for almost any application. Great for sealing around decorative or visible areas where a noticeable patch is not desirable. This premium formula has outstanding UV resistance, stays clear and will not “yellow or cloud” over time like other products. It is ideal for repairing cracks in exterior or interior applications where clear elastic seal is desired. Product is water based, and will have a cloudy white appearance when applied, but dries clear. Can be painted if needed.

WHAT IT DOES: Seals cracks to stop water leaks, or seal air drafts.

WHAT IS NEEDED TO COMPLETE THE JOB? Putty knife, trowel, gloves.

PREP THE AREA: Surfaces must be clean and dry, and free of dirt, rust and other material.

HOW TO APPLY: Use trowel/ putty knife to spread patch across or into crack, seam, hole or area where leak is, or may occur.

HOW MUCH DO I NEED? One quart covers 8 sq. ft. when applied 50 mil thick.

DO's and DON'Ts: Apply in interior or exterior applications. Wear protective gloves.

FOR BEST RESULTS: Use product on a clear warm day when temperatures are above 65°F. Work product to an even consistency over the area to be sealed. Use a trowel to spread over repair if needed. Product should be allowed to dry at least 24 hours before exposure to rain.

PRECAUTIONS: Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. **DO NOT** store at temperatures above 100°F. **DO NOT** reuse empty containers. **KEEP FROM FREEZING.** Close container when not in use. **DO NOT** reuse empty containers. Do not use on EPDM or some single ply membranes. If there is any question regarding compatibility with any surface, test a small section first. Do not use in drinking water or food systems.

HOW TO CLEAN-UP: Clean tools with soap and water when wet.

© 2009 Gardner-Gibson, Inc.
Manufactured by:
Gardner-Gibson, Inc.P.O. Box 5449, Tampa, FL 33675
www.gardner-gibson.com

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

| | |
|---|---------------------------|
| Weight Per Gallon, lbs. | 7.7-7.9 lbs. |
| Residue by Evaporation, % | 70 min. |
| Combustible Solvents | Mineral Spirits |
| Consistency | Spray or Brush |
| Cure Time (50% Relative Humidity, 70°F) | 4-8 hours |
| Full Cure (50% Relative Humidity, 70°F) | 7-14 days |
| Application Temperatures | 50°-120°F |
| Flammability | 105°F |
| Clean-up Tools | Mineral Spirits, Kerosene |

Approx. Shipping Weights: (Note: All approx. weights include container.)

| | |
|---------|----------|
| 1 quart | 2.5 lbs. |
|---------|----------|

CAUTION!: CONTENTS MAY BE HARMFUL. KEEP OUT OF REACH OF CHILDREN.

Do not swallow. Do not get in eyes or on skin or clothing. Do not breathe fumes. Wear safety glasses and chemical resistant gloves.

| | |
|---|---------------------|
| Acrylic Polymer | CAS # Non hazardous |
| 2,2,4 - Trimethyl-1,3-pentanediol Monoisobutyrate | CAS # 25265-77-4 |
| 2-Amino-2-methyl-1-propanol | CAS # 124-68-5 |

Use only with adequate ventilation. Eye and skin irritant. In case of contact with eyes, flush with plenty of clean, room temperature water. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid contact with skin and breathing vapor. If swallowed, do not induce vomiting. Call physician immediately.

VOC/VOS: 32 g/L of material

CALIF. PROP. 65 • WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. Use proper protection and adequate ventilation, when using product.

WARRANTY AND DISCLAIMER: Gardner-Gibson, Inc., warrants this product to give satisfactory results when our directions are followed in its use and application. Any claims made, with original sales receipt, will be based on a prorated basis. In no event however shall the manufacturer be liable for an amount in excess of the purchase price of the product used. If not completely satisfied, return to place of purchase for a refund.

See SDS for more info



Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardner-gibson.com