



0339

LEAKSTOPPER CLEAR Data Sheet

- Provides "invisible" patch
- Stops leaks instantly
- Flexes to prevent cracking
- Goes on white - dries clear
- Outlasts other repairs

USE ON THESE ROOF SURFACES: Asphalt Shingle, Slate, Tile, Metal, & Wood Shake Roofs. ALSO SEALS TO AND AROUND: Skylights, Wood, Glass, Stucco, Brick, Stone, Gutters, Chimneys.

WHAT IS IT? This advanced clear sealant has outstanding adhesion to a variety of surfaces, and provides a long lasting rubberized seal for almost any application. Great for sealing around decorative or visible areas where a noticeable patch is not desirable. This premium formula has outstanding UV resistance, stays clear and will not "yellow or cloud" over time like other products. It is ideal for repairing cracks in exterior or interior applications where clear elastic seal is desired. Product is water based, and will have a cloudy white appearance when applied, but dries clear. Can be painted if needed.

WHAT IT DOES: Seals cracks to stop water leaks, or seal air drafts.

WHAT IS NEEDED TO COMPLETE THE JOB? Caulking gun, trowel, gloves.

PREP THE AREA: Surfaces must be clean and dry, and free of dirt, rust and other material.

HOW TO APPLY: Apply from caulk tube, and completely fill area to be sealed.

HOW MUCH DO I NEED? Provides approximately 25 lineal feet of 1/4" bead.

DO's and DON'Ts: Apply in interior or exterior applications. Wear protective gloves. Not intended for EPDM, Hypalon or other type of synthetic roofing membrane. If there is a question of product compatibility, test a small section first.

FOR BEST RESULTS: Use product on a clear warm day when temperatures are above 65°F. Work product to an even consistency over the area to be sealed. Use a trowel to spread over repair if needed. Product should be allowed to dry at least 24 hours before exposure to rain.

PRECAUTIONS: Protective clothing and eyewear should be used during application of these products. When transporting this product, do not transport on passenger seats or inside the passenger compartment of any vehicle. DO NOT store at temperatures above 100°F. DO NOT allow product to freeze. Seal partially used container. DO NOT reuse empty containers. Not for use on EPDM or some single ply membranes.

HOW TO CLEAN-UP: Clean tools with soap and water when wet.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Weight Per Gallon, lbs.	8.8 lbs.
Solids by Weight	62%
Solids by Volume	59%
Viscosity	300,000 cps
Elongation	900%
Tensile Strength (ASTM D-2370)	90 psi
Adhesion to Polyurethane Foam	good
Consistency	smooth paste
Full Cure (50% Relative Humidity, 70°F)	24-48 hours (depending on thickness)
Application Temperature	55°-100°F
Flammability	No (water-based)
Clean-up Tools	Soap and warm water

Approx. Shipping Weights: (Note: All approx. weights include container.) 10.1 fl. oz. tubes. 12 tubes per case: 10 lbs.

CAUTION: KEEP OUT OF THE REACH OF CHILDREN.

For exterior use only. Contains petroleum based products. Keep away from heat, sparks and open flame. Use only with adequate ventilation. Eye and skin irritant. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid contact with skin and breathing vapor. If swallowed, do not induce vomiting. Call physician immediately. Seal container when not in use. Do not use drinking water or food systems.

VOC 21 g/L

INGREDIENTS: MINERAL SPIRITS, ACRYLIC POLYMER

CAS# 8052-41-3, CAS# Proprietary

WARRANTY AND DISCLAIMER: Gardner-Gibson, Inc. warrants this product to give satisfactory results when our directions are followed in its use and application. Any claims made, with original sales receipt, will be based on a prorated basis. In no event however shall the manufacturer be liable for an amount in excess of the purchase price of the product used. If not completely satisfied, return to place of purchase for a refund.

See MSDS for more info



Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449 Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardnerasphalt.com