



# 037 Wet-R-Dri® All-Season Asphalt Patch

- Stops Roof Leaks
- Adheres In Wet Or Dry Condition
- Thick Trowel Grade
- Great For Basic Repairs
- Fiber Reinforced

**Gardner® Wet-R-Dri® All-Season Asphalt Patch** is an all weather, asphalt based patching compound designed to repair cracks, seams and holes in roofing materials. It also works great in new construction and in setting flashings, drip edges and roofing material edges. It seals damaged areas and gives a layer of waterproof protection. Use on roofs around skylights, vents, exhaust pipes, chimneys, valleys, and in the construction or repair of flashings, roll roofing and shingles. Also excellent for use as a heavy duty below grade and underground water-proofer, and damp-proofer.

**PREPARATION:** Surfaces must be clean and free of surface rust and loose material. You will need trowel, reinforcing fabric, safety glasses and gloves.

**APPLICATION:** Apply generously with a trowel or putty knife. Work material to an even consistency over and into the area to be repaired approximately 1/8" to 1/2" thick, two or three inches beyond the problem area. It is highly recommended to reinforce the repair with a strip of Universal Patching Fabric. Embed fabric into the cement and cover with a second layer of cement. Form a feathered edge with cement where chimney's, vent pipes, and other projections meet the roof line. **DO NOT APPLY DIRECT HEAT/FLAMES OR THIN.** Apply when surface temperatures are between 50° and 120°F. In colder weather (50° and below), product should be stored in heated room (70° to 80°F) at least 24 hours prior to application to promote ease of application. Product formulated to be used year round. Allow product to cure a minimum of 30-60 days prior to application of reflective coating.

**COVERAGE RATE:** Covers approximately 12 sq. ft. per gallon when applied 1/8" thick.

**PRECAUTIONS:** For exterior use only. Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100° F. Do not use on EPDM, TPO, PVC or other rubber/synthetic surfaces. If there is any question regarding compatibility, test a small section first. Protect building inlet ventilation from product fumes. This manufacturer also disclaims liability for flat surface application where poor drainage or ponding water may prevail. Do not reuse empty containers. Do not use in drinking water or food systems. Protect from freezing.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
0379-GA	10 fl.oz.	2" x 2" x 11.5"	10 fl.oz.	1 lb.	12/crtn.	025056037909
0371-GA	1 gal.	6.75" x 6.75" x 7.75"	3.6 qt / 3.4 L	9 lbs.	6/case	025056037107
0378-GA	1 qt.	4.30" x 4.30" x 4.90"	29 fl.oz. / 858 mL	2.5 lbs.	12/case	025056037800
0375-GA	5 gal.	12" x 12" x 14.75"	4.75 gal / 18 L	55 lbs.	1 ea.	025056037503

**www.gardner-gibson.com**  
**Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449**  
**Phone: (813) 248-2101**