



FIBERED ROOF & FOUNDATION COATING Data Sheet

- Dries faster than solvent based
- Low odor, water clean-up
- Weatherproofing protection
- Seals above & below grade

DESCRIPTION: Gardner® Roof & Foundation Coating is a liquid applied, fibered, asphalt based coating. It is a low solvent formula, designed to penetrate and seal worn roof surfaces, foundation block walls, above or below grade and other masonry roof surfaces. Coating will weatherproof and help seal and protect surfaces. Can also be used to seal and protect underground wood footings and metal surfaces. Dries black in color. **PREPARATION:** Remove all dust, dirt, and debris. Patch all cracks or seams with Gardner Wet-R-Dri Roof Cement. Remove all rust or loose paint from metal surfaces. May be applied to slightly damp surfaces, but do not apply to wet surfaces or if rain is expected within 24 hours. Product can be coated with a reflective coating 7 days after initial application. On foundations apply only over cured concrete and masonry.

HOW TO APPLY: Use brush or paint roller to spread across surface.

COVERAGE RATE: This 5-gallon pail covers 350 sq.ft., per coat, over masonry and roof surfaces, depending on texture and porosity of surface. Two coats are recommended for best results.

CLEAN UP: Tools should be cleaned with citrus-based tar cleaner or water, when wet.

FOR BEST RESULTS ON ROOFS: After this coating has dried for approx. 2 weeks, apply a white or aluminum reflective coating for longest life expectancy.

PRECAUTIONS: Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100°F. This manufacturer also disclaims liability for flat surface application where poor drainage or ponding water may prevail. Do not reuse empty containers. Do not use in EPDM, Hypalon or PVC surfaces. Do not use on single ply or synthetic roofs. If there is any question regarding compatibility, test a small section first. Do not use in drinking water or food systems. Do not allow product to freeze.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Weight Per Gallon, lbs.	8.2-8.6 lbs.
Residue by Evaporation, %	40 min.
Combustible Solvents	None
Consistency	Spray or Brush
Cure Time (50% Relative Humidity, 70°F)	4-8 hours
Full Cure (50% Relative Humidity, 70°F)	7-14 days
Application Temperatures	50°-120°F
Flammability	Waterbased
Clean-up Tools	Water

Approx. Shipping Weights: (Note: All approx. weights include container.)

1 gallon (3.4L)	8.4 lbs.
5 gallons (18.9L)	42 lbs.

CAUTION!
MAY BE HARMFUL OR FATAL IF SWALLOWED.
KEEP OUT OF REACH OF CHILDREN.
FOR EXTERIOR USE ONLY.
USE WITH ADEQUATE VENTILATION.

Contains petroleum based products. Keep away from heat, sparks, and open flame. Eye, skin and respiratory irritant. In case of contact with eyes, flush with plenty of clean, room temperature water. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid prolonged breathing of vapor or spray mist. In case of irregular or stopped breathing, administer oxygen and/or give artificial respiration. Get medical attention immediately. Contact with skin should be followed by washing with soap and water. If swallowed, do not induce vomiting. Call physician immediately. Seal container when not in use.

CALIF. PROP. 65 • WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. Use proper protection and adequate ventilation, when using product.

VOC/VOS - 20 g/L Maximum
 ASPHALT C.A.S.# 8052-42-4
 CLAY C.A.S.# 1332-58-7
 Product is asbestos free.
 PATENT PENDING

© 2009 Gardner-Gibson, Inc.
 Manufactured by:
 Gardner-Gibson, Inc.P.O. Box 5449, Tampa, FL 33675
 www.gardner-gibson.com

See SDS for more info

Limited Warranty: Gardner-Gibson, Inc. warrants that this product, when applied in accordance with our written directions in applications recommended by us as suitable for the product, is free of defects in material and workmanship for a period of 12 months from the date of purchase. If you notify us of such a defect and provide adequate proof of purchase during this warranty period, we will replace the defective product at no cost to you. This limited warranty is the sole and exclusive remedy for any such defective product. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER EXPRESSED OR IMPLIED WARRANTIES, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR ANY PARTICULAR USE OR PURPOSE, AND GARDNER-GIBSON, INC. WILL IN NO EVENT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449
 Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardner-gibson.com