



0525

DRIVEASEAL II BLACKTOP DRIVEWAY FILLER SEALER Data Sheet

DESCRIPTION: Driveaseal II Blacktop Filler Sealer is an economical asphalt pavement coating designed to seal surfaces in good condition. This coating will restore a black finish to asphalt surfaces. Surfaces must be in good repair prior to applying this product. NOT intended for high traffic areas. DO NOT USE ON CONCRETE, FLAG-STONE, BRICK OR CLAY SURFACES.

PREPARATION: Driveways must be cleaned with Gardner® Driveway Kleen™ spray on cleaner & degreaser before sealcoating. For oil stains, apply Driveway Kleen liberally and scrub into surface to penetrate oil spots. This step promotes proper bonding and will help prevent adhesion failures. Repair cracks and holes with Crack Stopper™ Rubberized Crack Filler & Patching products for longest lasting results. Sweep surface clean and rinse thoroughly or air blow the surface free of remaining dust and debris. Do not allow puddling of water.

FOR BEST RESULTS: Apply during the summer, in the morning hours of a clear warm day. Temperatures should be a minimum of 65°F and rising, but not above 90°F. While product can be applied during other times, these are the optimum ranges that provide superior results. Also, apply brush strokes perpendicular to the street entrance, this hides application imperfections. If possible, use pails containing the same batch code stamp on the top of the lid. Remember to mix all buckets to a uniform consistency, and when using multiple buckets, blend the end of one bucket with the beginning of the next to prevent shade variances. Do not apply on newly laid pavements until at least one full summer's season of weathering has occurred. Best when applied in the early morning on a clear day when air and pavement temperatures are above 60°F and rising. Do not apply if rain or heavy dew is expected within 24 hours. Allow to cure 24-48 hours before vehicle traffic.

APPLICATION: Mix well. Apply with brush/squeegee applicator. If pavement gets hotter than 85°F, mist with water to cool surface so sealer does not dry too fast. However, do not allow water to puddle. Apply sealer in thin coats, as two thinner layers adhere better than one thick one. Do not apply to steeply sloped surfaces, 20° incline or more, as this may present a slip hazard. If slope is in question, test small area first before applying to entire area. Note: newly paved surfaces must cure at least 12 months before applying sealer. Pour a ribbon of material across one end of driveway, working in a cross pattern, brush sealer into driveway surface to fill all pores. Allow first coat to dry to touch (4-8 hrs.) before applying second coat KEEP TRAFFIC OFF FOR 24-48 HOURS.

COVERAGE RATE: A five gallon pail will cover 300-375 sq. ft. Do not apply on newly laid or patched pavements until at least one full summer's season of weathering has occurred.

CLEAN-UP: Soap & water when wet, or orange citrus cleaner when dry.

PRECAUTIONS: Protective clothing and eyewear should be used during application of these products. KEEP FROM FREEZING. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100°F. This manufacturer also disclaims liability for flat surface application where poor drainage or ponding water may prevail. Do not reuse empty containers. Do not use in drinking water or food systems.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Weight Per Gallon, lbs.	9.2 - 9.6 lbs.
Residue by Evaporation, %	36 ± 1.0
Combustible Solvents	None
Consistency	Brush, Roller or Squeegee
Cure Time (50% Relative Humidity, 70°F)	2 hours
Full Cure (50% Relative Humidity, 70°F)	24-48 hours
Application Temperatures	65°-100°F
Flammability	N/A waterbased
Clean-up Tools	Soap & water when wet Mineral spirits when dry

Approx. Shipping Weights: (Note: All approx. weights include container.)

4.75 gallons (18L)	49 lbs.
55 gallons (208.2L)	540 lbs.

CAUTION!: HARMFUL OR FATAL IF SWALLOWED.
KEEP OUT OF REACH OF CHILDREN.
FOR EXTERIOR USE ONLY.
USE WITH ADEQUATE VENTILATION.

Contains petroleum based products. Keep away from heat, sparks and open flame. Eye and skin irritant. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid contact with skin and breathing vapor. If swallowed, do not induce vomiting. In case of eye contact, wash with plenty of clean, room temperature water. Call physician immediately. Seal container when not in use.

VOC: 10 g/L

Asphalt CAS # 8052-42-4 Clay CAS # 1332-58-7
Water CAS # 7732-18-5 Sand CAS # 14808-60-7
Product is asbestos free • PATENT PENDING

CALIF. PROP. 65 • WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. Use proper protection and adequate ventilation, when using product.

WARRANTY AND DISCLAIMER: Gardner-Gibson, Inc. warrants this product to give satisfactory results when our directions are followed in its use and application, for a period of 2 years from the date of purchase. In no event however shall the manufacturer be liable for an amount in excess of the purchase price of the product used. For this guarantee to be valid, only products produced by Gardner-Gibson may be used for repair. This warranty is only for residential (single family) homes. Two coats must be applied. Not applicable on commercial parking lots. If product wears away before the warranty period, a refund will be made based on the prorated cost vs. the life of the product.

©2009 Gardner-Gibson, Inc.
Manufactured by: Gardner-Gibson, Inc., PO Box 5449, Tampa, Florida 33675
www.gardner-gibson.com

See MSDS for more info



Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardner-gibson.com