



0551

BLACKTOP DRIVEWAY CRACK FILLER Data Sheet

- Fills Cracks Up to 3/8"
- Easy Pour Spout

DESCRIPTION: Blacktop Driveway Crack Filler is liquid filling compound, designed to repair cracks in asphalt pavements. It is formulated to seep deep into the crack and seal the opening from moisture. Its finish keeps water from getting under pavement which causes further deterioration. Annual maintenance is always recommended.

PREPARATION: Remove loose dust, dirt, and debris from cracks using a stream of water or air. Let dry. No standing water should be in the crack when application is made. (Crack Filler may be applied to slightly damp surfaces.) Apply only when temperature is 55°F and rising and rain is NOT expected for 24 hours.

APPLICATION: For exterior use only. Mix contents by turning container over and back for one to two minutes to assure uniform consistency. Invert spout in the cap as illustrated. Cut spout tip to 1/8 inch opening, or as desired. Let crack filler flow from spout into crack using pressure on sides of container to control flow. This product will fill cracks up to 3/8" inch wide. In large cracks shrinkage may be evident, and additional applications of crack filler may be required. To prevent tracking of crack filler, sprinkle fine sand over the surface of the cracks immediately after applying crack filler.

COVERAGE RATE: One gallon fills 200 linear feet of 1/4" x 1/4" cracks.

BEST TO ALLOW REPAIR TO DRY at least one week, during good weather, before applying any driveway coating or sealer.

CLEAN UP: Clean tools and equipment with water immediately after use. Dried crack filler may be removed with citrus cleaner.

PRECAUTIONS: Do not freeze. Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and jug is secure and upright. Do not allow jug to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100°F. Do not reuse empty containers. Do not use in drinking water or food systems. Dispose of properly.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Weight Per Gallon, lbs.	9.1-9.3 lbs.
Residue by Evaporation, %	45min.
Combustible Solvents	None
Consistency	Pourable
Cure Time (at recommended coverages)	4-8 hours to set, 24-48 hrs. to full cure depending on weather
Application Temperatures	50° -120°F
Flammability	N/A
Clean-up Tools	Soap and water when wet Mineral spirits when cured

Approx. Shipping Weights: (Note: All approx. weights include container.)

1 gallon (3.8L)	9.6 lbs.
(6) 1 gallons	65 lbs.

**CAUTION!: HARMFUL OR FATAL IF SWALLOWED.
KEEP OUT OF REACH OF CHILDREN.
FOR EXTERIOR USE ONLY.
USE WITH ADEQUATE VENTILATION.**


Contains petroleum based products. Keep away from heat, sparks and open flame. Eye and skin irritant. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid contact with skin and breathing vapor. If swallowed, do not induce vomiting. In case of eye contact, wash with plenty of clean, room temperature water. Call physician immediately. Seal container when not in use.

CALIF. PROP. 65 • WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. Use proper protection and adequate ventilation, when using product.

VOC: 10 g/L

ASPHALT C.A.S. #8052-42-4
CLAY C.A.S. #1332-58-7
WATER C.A.S. #7732-18-5
This product is asbestos free.
PATENT PENDING

©2009 Gardner-Gibson, Inc.
Manufactured by: Gardner-Gibson, Inc.
P.O. Box 5449, Tampa, FL 33675
www.gardner-gibson.com



WARRANTY AND DISCLAIMER:

For limited warranty and disclaimer information, contact the Gardner-Gibson corporate office at 1-800-237-1155.

See SDS for more info

Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardner-gibson.com