



Section 1 - Product and Company Identification

Material Name * 1329 Neoprene Flashing Cement
Product Code * 1329-GA,
Product Description * Black Liquid.
Product Use * Black Roof Sealant
Synonyms * Black Roof Patching Cement

Manufacturer * Gardner Gibson
4701 E. 7th Avenue
Tampa, FL 33605
United States
www.gardner-gibson.com
Please use "Contact Us" form on the website

Telephone
Technical * 813-248-2101
Emergency * 800-424-9300
Emergency * 703-527-3887

Preparation Date * 5/1/2015
Last Revision Date * 5/1/2015

Section 2 - Hazards Identification

Emergency Overview

[Empty box for emergency overview details]

DANGER

FLAMMABLE LIQUID AND VAPOR
Causes mild skin irritation. Harmful if swallowed.

Prevention Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash thoroughly after handling.

Response IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention.

Storage/Disposal Store in a closed container. Do not allow product to freeze. Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.



Flammable liquid and vapor.
Harmful in contact with skin or if inhaled.
Causes serious eye irritation.
Causes skin irritation.
Suspected of causing cancer if inhaled.
May be fatal if swallowed and enters airways.
May cause respiratory irritation.
May cause damage to organs through prolonged or repeated exposure if inhaled. (ears)

CAUTION - May cause eye and skin irritation on contact.

Physical Form

* Liquid

Color

* Black Liquid.

Odor

* Paint-Like Odor.

Flash Point

* 81 F(27.2 C)

OSHA(HCS2012)

* FLAMMABLE LIQUIDS - Category 3
ACUTE TOXICITY: SKIN - Category 4
ACUTE TOXICITY: INHALATION - Category 4
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
CARCINOGENICITY: INHALATION - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE): INHALATION [ears] - Category 2
ASPIRATION HAZARD - Category 1

WHMIS

* Class D - Poisonous and Infectious Materials - Division 2 - Subdivision B



GHS

* FLAMMABLE LIQUIDS - Category 3
ACUTE TOXICITY: SKIN - Category 4
ACUTE TOXICITY: INHALATION - Category 4
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
CARCINOGENICITY: INHALATION - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE): INHALATION [ears] - Category 2
ASPIRATION HAZARD - Category 1

NFPA:

Health : 2

Flammability: 3

Reactivity: 0

Personal Protection: G

Potential Health Effects

Inhalation

- Acute (Immediate)** * Inhalation of vapors or mists may cause central nervous system depression, light-headedness, headache, nausea and loss of coordination.
- Chronic (Delayed)** * Under normal conditions of use, no health effects are expected.

Skin

- Acute (Immediate)** * May cause irritation.
- Chronic (Delayed)** * Repeated and prolonged exposure to the skin may cause dermatitis.

Eye

- Acute (Immediate)** * Likely to cause eye irritation, burning, tearing, etc. on contact with the eyes. If swelling and irritation persist, seek medical attention.
- Chronic (Delayed)** * Direct contact may cause slight to moderate irritation.

Ingestion

- Acute (Immediate)** * May cause irritation. May affect the nervous system. May be harmful or fatal if swallowed.
- Chronic (Delayed)** * Repeated and prolonged exposure may cause gastrointestinal disturbances including diarrhea, nausea, and vomiting.

| Carcinogenic Effects | | | |
|----------------------|----------|----------|-----|
| | CAS | IARC | NTP |
| Ethyl Benzene | 100-41-4 | Group 2B | |

Section 3 - Composition/Information on Ingredients

| Hazardous Components | | | | | |
|----------------------|------------------|-----------|----------------------------------------------------------------|---------------------------------------------------|----------|
| Chemical Name | Identifiers | %(weight) | LD50/LC50 | Classifications According to Regulation/Directive | Comments |
| Xylene | CAS: 1330-20-7 | 32.0% | ORAL (LD50): Acute: 4300 mg/kg [Rat]. 2119 mg/kg | | |
| Thermoplastic Rubber | CAS: 132778-07-5 | 10.0% | Oral, rat: LD50 = 2,000 mg/kg | | |
| Hydrocarbon Resin | CAS: 68131-77-1 | 10.0% | Oral, rat: LD50 = >1260 mg/kg | | |
| Mica | CAS: 12001-26-2 | 2.0% | | | |
| Calcium Carbonate | CAS: 1317-65-3 | 26.0 | | | |
| Kaolin Clay | CAS: 1332-58-7 | 8.0 | | | |
| Carbon Black | CAS: 1333-86-4 | 8.0 | Oral, rat: LD50 = >15400 mg/kg; Skin, rabbit: LD50 = >3 gm/kg; | | |
| Ethyl Benzene | CAS: 100-41-4 | 3.0 | Oral, rat: LD50 = 4,100 mg/kg | | |
| Chlorinated Paraffin | CAS: 63449-39-8 | 1.0 | | | |

| Non-Hazardous Components | | | | | |
|--------------------------|-------------|-----------|-----------|---------------------------------------------------|----------|
| Chemical Name | Identifiers | %(weight) | LD50/LC50 | Classifications According to Regulation/Directive | Comments |
| | | | | | |

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

Section 4 - First Aid Measures

| | |
|-------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Inhalation | * IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If signs/symptoms continue, get medical attention. |
| Skin | * Rinse skin immediately with plenty of water for 15-20 minutes. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. |
| Eye | * If eye irritation persists: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| Ingestion | * If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. |

Section 5 - Fire Fighting Measures

| | |
|-------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extinguishing Media | * LARGE FIRE: Water spray, fog or regular foam. SMALL FIRES: Dry chemical, CO2, water spray or regular foam. |
| Unsuitable Extinguishing Media | * No data available. |
| Firefighting Procedures | * Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Keep unauthorized personnel away. |
| Unusual Fire and Explosion Hazards | * Product containers may rupture when exposed to extreme heat. Precautions should be taken to prevent release of materials. |
| Hazardous Combustion Products | * Non-combustible, substance itself does not burn but may decompose upon heating to produce toxic fumes. |
| Protection of Firefighters | * Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible. |
| Flash Point | * > 81 F(> 27.2 C) CC (Closed Cup) |

Section 6 - Accidental Release Measures

| | |
|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Personal Precautions | * Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. |
| Emergency Procedures | * Isolate the area and contain the spilled material. Persons not wearing the appropriate PPE should be removed from the area until the spill is cleaned up. |
| Environmental Precautions | * Avoid run off to waterways and sewers. |
| Containment/Clean-up Measures | * Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use appropriate Personal Protective Equipment (PPE) |
| Prohibited Materials | * Avoid contact with strong oxidizing agents and acids. |

Section 7 - Handling and Storage

| | |
|-----------------|--------------------------------------------------------------------------------------|
| Handling | * KEEP OUT OF THE REACH OF CHILDREN! Keep containers tightly closed when not in use. |
|-----------------|--------------------------------------------------------------------------------------|

| | |
|---------------------------------------------------|------------------------------------------------------------------------------------------------------------------|
| Storage | * Avoid extreme temperatures and freezing. Keep container/package tightly closed and in a well-ventilated place. |
| Special Packaging Materials | * Not Applicable. |
| Incompatible Materials or Ignition Sources | * Avoid contact with strong oxidizing agents and acids. |

Section 8 - Exposure Controls/Personal Protection

Personal Protective Equipment

| | | | | | |
|-------------------|---|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
| Pictograms | * |  |  |  |  |
|-------------------|---|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|

Respiratory * When used with adequate ventilation, a respirator is not normally required. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge or supplied air respirator. This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

Eye/Face * Wear ANSI approved safety glasses with side shields or safety goggles.

Hands * Wear chemical resistant gloves with repeated or prolonged exposure.

Engineering Measures/Controls * Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Use precaution to protect building intake from fumes and vapors created outdoors.

| Exposure Limits/Guidelines | | | | | |
|--------------------------------|--------|-----------------------------------------|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| | Result | Canada Ontario | Mexico | NIOSH | OSHA |
| Xylene (1330-20-7) | TWAs | 250 mg/m ³ | Not established) | 100 ppm | 100 ppm |
| Ethyl Benzene (100-41-4) | TWAs | | | 100 ppm | 100 ppm |
| Hydrocarbon Resin (68131-77-1) | TWAs | | | | 10 mg/m ³ |
| Carbon Black (1333-86-4) | TWAs | 10 mg/m ³ TWAEV (total dust) | 10 mg/m ³ TWA (as Ti) | 3.5 mg/m ³ TWA; 0.1 mg/m ³ TWA (as PAH, carbon black in presence of polycyclic aromatic hydrocarbons) 1750 mg/m ³ IDLH | 3.5 mg/m ³ TWA |
| Calcium carbonate (1317-65-3) | TWAs | Not established | 10 mg/m ³ TWA | 10 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable dust) | 15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction) |

Section 9 - Physical and Chemical Properties

| Material Description | | | |
|----------------------|--------------------|------------------------|--------------------------------------|
| Physical Form | Liquid | Appearance/Description | Black liquid with heavy consistency. |
| Color | Black Liquid. | Odor | Paint-Like Odor. |
| Taste | No data available. | Particulate Type | Not relevant |
| Particulate Size | Not relevant | Aerosol Type | Not relevant |
| Odor Threshold | No data available | | |
| General Properties | | | |

| | | | |
|-------------------------------------|---------------------------------|----------------------------------------------------|-------------------|
| Boiling Point | 212 to 245 F(100 to 118.3333 C) | Melting Point | No data available |
| Decomposition Temperature | No data available | Heat of Decomposition | Not relevant |
| pH | 8 @ 25 C(77 F) | Specific Gravity/Relative Density | 1.27 Water=1 |
| Density | 10.56 lbs/gal @ 25 C(77 F) | Bulk Density | No data available |
| Water Solubility | Soluble 0 % @ 25 C(77 F) | Solvent Solubility | Not relevant |
| Viscosity | 165,000 cps. @ 25 C(77 F) | | |
| Volatility | | | |
| Vapor Pressure | 5.3 mmHg (torr) @ 20 C(68 F) | Vapor Density | > 1 Air=1 |
| Evaporation Rate | < 1 Ether = 1 | VOC (Wt.) | No data available |
| VOC (Vol.) | 400 g/L | Volatiles (Wt.) | No data available |
| Volatiles (Vol.) | No data available | | |
| Flammability | | | |
| Flash Point | 81 F(27.2 C) | Flash Point Test Type | CC (Closed Cup) |
| UEL | No data available | LEL | No data available |
| Autoignition | No data available | Self-Accelerating Decomposition Temperature (SADT) | Not relevant |
| Heat of Combustion (ΔH_c) | Not relevant | Burning Time | Not relevant |
| Flame Duration | Not relevant | Flame Height | Not relevant |
| Flame Extension | Not relevant | Ignition Distance | Not relevant |
| Environmental | | | |
| Half-Life | Not relevant | Octanol/Water Partition coefficient | Not relevant |
| Coefficient of Water | Not relevant | Bioaccumulation Factor | Not relevant |
| Bioconcentration Factor | Not relevant | Biochemical Oxygen Demand BOD/BOD5 | Not relevant |
| Chemical Oxygen Demand | Not relevant | Persistence | Not relevant |
| Degradation | Not relevant | | |

Section 10 - Stability and Reactivity

| | |
|-----------------------------------------|---------------------------------------------------|
| Stability | * Stable under normal temperatures and pressures. |
| Hazardous Polymerization | * Hazardous polymerization not indicated. |
| Conditions to Avoid | * Excessive heat and freezing. |
| Incompatible Materials | * Strong oxidizers and acids. |
| Hazardous Decomposition Products | * No known issues under normal usage conditions. |

Section 11 - Toxicological Information

| Component Name | CAS | Data |
|----------------------------|-------------|---------------------------------------------------------------------------------------------|
| Xylene (32%) | 1330-20-7 | Acute Toxicity: ORAL (LD50): Acute: 4300 mg/kg [Rat]. 2119 mg/kg |
| Thermoplastic Rubber (10%) | 132778-07-5 | Acute Toxicity: Oral, rat: LD50 = 2,000 mg/kg |
| Hydrocarbon Resin (10%) | 68131-77-1 | Acute Toxicity: Oral, rat: LD50 = >1260 mg/kg |
| Carbon Black (8%) | 1333-86-4 | Acute Toxicity: orl-rat TDLo:60 gm/kg; Irritation: skn-hmn 300 ug/3D-I MLD |
| Ethyl Benzene (3%) | 100-41-4 | Acute Toxicity: Oral, rat: LD50 = 4,100 mg/kg |

| | |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Other Component Information | * IARC has concluded that the following chemicals in this product are carcinogenic to humans(Group 1): ACGIH has designated the following chemicals in this product as suspected |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

human carcinogens (A2): silica, quartz. NTP has listed the following chemicals in this product as known human carcinogens: Risk of cancer depends on duration and level of exposure to this product as a dust or aerosol mist.

Section 12 - Ecological Information

| | |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Ecological Fate | * No data available. |
| Persistence/Degradability | * No data available. |
| Bioaccumulation Potential | * No data available. |
| Mobility in Soil | * No data available. |
| Other Information | * Do not allow product exposure to the ground or into any waterway. Do not allow entry into municipal sewer systems. |

Section 13 - Disposal Considerations

| | |
|----------------|-----------------------------------------------------------------------------------------------------------------------|
| Product | * Dispose of content and/or container in accordance with local, regional, national, and/or international regulations. |
|----------------|-----------------------------------------------------------------------------------------------------------------------|

Section 14 - Transportation Information

DOT - United States - Department of Transportation - Shipping Name: UN1263 PG II.

TDG - Canada - Transportation of Dangerous Goods - Shipping Name: Not Restricted.

IMO/IMDG - International Maritime Transport Shipping Name: Not Regulated.

International Air Transportation Association – UN1263 PG II

Section 15 - Regulatory Information

SARA Hazard Classifications * Acute, Chronic

| State Right To Know | | | | | |
|----------------------|-------------|-----|-----|-----|-----|
| Component | CAS | MA | MN | NJ | PA |
| Xylene | 1330-20-7 | Yes | Yes | Yes | Yes |
| Thermoplastic Rubber | 132778-07-5 | No | No | No | No |
| Hydrocarbon Resin | 68131-77-1 | No | No | No | No |
| Mica | 12001-26-2 | Yes | Yes | Yes | Yes |
| Calcium Carbonate | 1317-65-3 | No | No | No | No |
| Kaolin Clay | 1332-58-7 | Yes | Yes | Yes | Yes |
| Carbon Black | 1333-86-4 | Yes | Yes | Yes | Yes |
| Ethyl Benzene | 100-41-4 | Yes | Yes | Yes | Yes |
| Chlorinated Paraffin | 63449-39-8 | No | No | No | Yes |

| Inventory | | | |
|-----------|-----|-----------|------|
| Component | CAS | EU EINECS | TSCA |
| | | | |

| | | | |
|----------------------|-------------|-----|-----|
| Xylene | 1330-20-7 | Yes | Yes |
| Thermoplastic Rubber | 132778-07-5 | No | No |
| Hydrocarbon Resin | 68131-77-1 | No | No |
| Mica | 12001-26-2 | Yes | Yes |
| Calcium Carbonate | 1317-65-3 | Yes | Yes |
| Kaolin Clay | 1332-58-7 | No | No |
| Carbon Black | 1333-86-4 | Yes | Yes |
| Ethyl Benzene | 100-41-4 | Yes | Yes |
| Chloronated Paraffin | 63449-39-8 | No | Yes |

Canada

Labor

Canada - WHMIS - Classifications of Substances

| | | | |
|---------------|-----------|-----|-----|
| ●Carbon Black | 1333-86-4 | 2% | D2A |
| Xylene | 1330-20-7 | 32% | B2 |
| Kaolin Clay | 1332-58-7 | 8* | D2a |
| Ethyl Benzene | 100-41-4 | 3% | D2a |

United States

Environment

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

| | | | |
|---------------|-----------|-----|------------|
| ●Carbon Black | 1333-86-4 | 2% | Not Listed |
| Xylene | 1330-20-7 | 32% | Listed |
| Ethyl Benzene | 100-41-4 | 3% | Listed |

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

| | | | |
|---------------|-----------|-----|--------|
| ●Xylene | 1330-20-7 | 32% | Listed |
| Ethyl Benzene | 100-41-4 | 3% | Listed |

United States - Rhode Island

Labor

U.S. - Rhode Island - Hazardous Substance List

| | | | |
|---------------|-----------|-----|--------|
| Xylene | 1330-20-7 | 32% | Listed |
| Ethyl Benzene | 100-41-4 | 3% | Listed |

Other Information

* WARNING: This product contains a chemical known to the State of California to cause cancer.

Section 16 - Other Information

Preparation Date * 5/1/2015

Last Revision Date * 5/1/2015

Disclaimer/Statement of Liability * This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or

completeness. It is the users responsibility to verify the suitability and completeness of such information for particular use. Gardner-Gibson does not accept liability for any loss or damage that may occur from the use of this information.