

# FLAME STOPPER™

# 3629-5-61 5000

## Flexible Intumescent Sealant

- UL Classified R25418
- Meets NFPA Class A and complies with ICC IRC 2000
- Intumescent: blocks fire, smoke & fumes room to room & floor to floor
- Ideal for through-penetrations of floors, and walls
- Suitable for concrete joints & HVAC ducts
- Smooth, consistent bead

**Flame Stopper™ 5000** is an Advanced Flexible Intumescent Acrylic Latex firestop sealant designed to seal surfaces with or without movement. It “intumesces” or expands when exposed to extreme heat, cutting off the spread of fire around pipes and through-penetrations. Stops the spread of toxic fumes and smoke during a building fire.

Consult specific UL Fire Resistance Directory system drawings for “F” and “T” ratings and uses. Dries to a red flexible seal. Will not crack or deteriorate where vibrations occur. Apply in interior or exterior applications and can be painted.

**Specifications:** Tested to UL 1479/ASTM E 814 standards. Meets the criteria for fire, smoke, and draftstop requirements as defined in all major building codes. Consult specific UL® Fire Resistance Directory system drawings for “F” and “T” ratings and uses.

**Use on:** All horizontal and vertical joints, “through-penetrations” in floors and walls, drywall, insulation, concrete joints and HVAC systems. Seals around all wire cables, PVC pipe, plumbing fixtures and other exposed materials.

**How to apply:** Trim nozzle to desired bead size. Apply generously to a clean, dust free surface (above 45 °F) with caulk gun in one continuous bead. Tool in place, if needed, before product skins over.

**Coverage:** Provides approximately 30 linear feet of 1/4" bead per 10 fl.oz. tube.

**Clean up:** Clean up with soap and water when sealant is wet.

**Precautions:** Protective clothing, gloves and eyewear should be used during application of this product. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not use in drinking water or food systems. For longest life, store in controlled environment, 35 °F - 80 °F. Do not store in direct sunlight. Protect from freezing.

**First Aid:** For any overexposure or if skin irritation develops, seek immediate medical attention after first aid is given. Should contact be made with eyes, rinse cautiously with clean, room temperature water for 5 to 10 minutes. Should skin contact occur, wash with soap and water. Do not use solvents to clean the skin. Should ingestion occur, call physician immediately. Do not induce vomiting.

**Warranty:** All products shown to be defective in manufacture, will be replaced free of charge. Since the use of these products is beyond the manufacturer’s control, we can not assume any risk of liability for results obtained, nor can we accept damages in excess of the purchase price of the product.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
3629-5-61	10 fl.oz.	2" x 2" x 11.5"	10 fl.oz. / 296 mL	1.3 lbs.	12/crtn.	758706362952

[www.gardner-gibson.com](http://www.gardner-gibson.com)  
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449  
Phone: (813) 248-2101