

7565



PRO 7™ BLACKTOP DRIVEWAY FILLER-SEALER Data Sheet

- Easy! No mixing, better finish
- Protects & beautifies
- Renews! Rejuvenates aged asphalt
- Durable! Rubberized for strength

DESCRIPTION: GARDNER® PRO 7™ delivers excellent lasting protection and a like-new finish for all asphalt and blacktop.

GARDNER PRO 7 is ideal for new aged asphalt and restores new life to old worn pavement. It fills small cracks for an even finish, and provides durable protection against damaging sun and rain. Gardner's trademark Gel formula virtually eliminates stirring and ensures a more consistent finish, making your sealing project faster and easier!

Read and follow all directions before beginning project.

PREPARING THE SURFACE: New asphalt must cure at least six months and/or one full summer season before applying sealcoat. Clean driveway first with DRIVEWAY KLEEN™ spray-on cleaner to ensure adhesion. Scrub oil spots with DRIVEWAY KLEEN and a brush. Repair cracks and fill holes with appropriate CRACK STOPPER™ crack fillers. Fill large potholes with REPAVE permanent pothole patch. Repairs must cure according to manufacturer instructions before sealing.

CONDITIONS: Before sealing, surface and air must be at least 65°F and rising, but below 90°F. Do not apply patch or sealer if rain or colder temperatures are expected within 36 hours. Do not use on surfaces with greater than 20° slope.

FIRST COAT: After preparing the surface and rinsing thoroughly, apply sealer to the damp pavement. Stir in any water that has separated inside the pail. Pour out 1/4 of the container across blacktop and spread product with brush or squeegee, the entire coat going in the same direction, from the highest end of the drive to the lowest. Complete each coat in one continuous wet application to prevent uneven color or sheen, working in small areas at a time and moving across the surface. Do not allow to puddle.

SECOND COAT: After the first coat is fully dry, apply a second thin coat in the opposite direction. This second coat ensures voids are filled & sealed, and deters uneven coverage, tracking and drying problems. When using more than one pail, blend sealers together for the best finish consistency.

HOW MUCH TO APPLY: For driveways in average condition, apply 350 sq. ft. per 5 gallon pail in two thin coats. Coverage varies based the surface condition and texture.

DRY TIME (based on 75°F, clear sunny skies, and humidity < 35%): For foot traffic, allow 4-5 hours after application. For vehicle traffic, allow 24-48 hours. Temperature, wind, sunlight, applied thickness, and humidity affect dry time.

CLEAN-UP: Until dried, clean tools with warm water and soap. Clean up dried product with a citrus based cleaner.

PRECAUTIONS: Do not thin, mix or blend this product with any other product. Use protective clothing and eyewear when using these products, to avoid skin irritation. When transporting this product, ensure the lid is completely sealed and the pail upright and secure: allowing pail to tumble may cause it to leak. Do not transport inside the passenger compartment of any vehicle. Transport in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. **CLOSE CONTAINER WHEN NOT IN USE.** Do not reuse empty containers. Use caution not to track onto linoleum floors, which are subject to household traffic stains, including asphalt driveway sealers; consult the linoleum manufacturer for suggestions. Do not use in drinking water or food systems. **KEEP FROM FREEZING.**

DISPOSAL: Dispose of in an environmentally acceptable manner. Container is recyclable if cleaned immediately. Do not pour excess product in drains or watercourses.

See SDS for more info

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Weight Per Gallon, lbs.	10.2 - 10.6 lbs.
Residue by Evaporation, %	48 ± 1.0
Combustible Solvents	None
Consistency	Brush, Roller or Squeegee
Cure Time (50% Relative Humidity, 70°F)	2 hours
Full Cure (50% Relative Humidity, 70°F)	24-48 hours
Application Temperatures	65°-90°F
Flammability	N/A waterbased
Clean-up Tools	Soap & water when wet Mineral spirits when dry

Approx. Shipping Weights: (Note: All approx. weights include container.)

5 gallons (18.9L)	54 lbs.
-------------------	---------

CAUTION! HARMFUL OR FATAL IF SWALLOWED FOR EXTERIOR USE ONLY USE WITH ADEQUATE VENTILATION KEEP OUT OF REACH OF CHILDREN

Contains petroleum based products. Keep away from heat, sparks and open flame. Eye and skin irritant. If contact with eyes, wash with plenty of clean, room temperature water. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid contact with skin and breathing vapor. In case of skin contact: wash thoroughly with soap and water. If swallowed, do not induce vomiting. Call physician immediately.

CALIF. PROP. 65 · CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ.) WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. Use proper protection and adequate ventilation, when using product.

VOC: less than 6 g/L

Asphalt	C.A.S.# 8052-42-4	Clay	C.A.S.# 1332-58-7
Fillers	C.A.S.# 14808-60-7	Latex	C.A.S.# 9003-55-8
Product is asbestos free			
PATENT PENDING			

Copyright © 2009 Gardner-Gibson, Inc., All Rights Reserved.
Manufactured by Gardner-Gibson, Inc., P.O. Box 5449, Tampa, FL 33675

WARRANTY AND DISCLAIMER: Gardner Pro 7 will maintain a protective film on your driveway surface for a period of seven (7) years from date-of-purchase when applied according to all label instructions. If the product proves to be defective within 7 years of date of purchase, with your original retail receipt, it shall be replaced or refunded on a prorated basis. Gardner-Gibson will not be liable for areas affected by ponding water, poor drainage, or snow removal. Failures due to acts of God, fire, structural defects or causes beyond our control are excluded from this guarantee and we are not responsible for labor or other costs incurred in the original or any replacement application. Except as stated above, we make no warranties or guarantees, express or implied, and none should be inferred. For this guarantee to be valid, only products produced by Gardner-Gibson may be used for repair. This warranty is only for residential (single family) homes. Two coats must be applied. Not applicable on commercial parking lots. If product wears away before the warranty period, a refund will be made based on the prorated cost vs. the life of the product.

Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardner-gibson.com