



# 018 Fiber Coat+ Rubberized Premium Asphalt Coating

- Ideal for Coating Worn Roofs
- Tough Flexible Finish Resists Cracking
- Heavy Duty Coating for Roofs and Foundations
- Fast Dry/Low Tack Formula
- Low Odor, Water Cleanup

**Gardner® FIBER COAT+** is a premium rubberized asphalt coating for renewing worn out roofs and foundations. This unique blend of asphalt and rubber provides great strength and flexibility for lasting protection to roofs, masonry surfaces and metal. Fiber reinforced coating will bridge small cracks to provide a crack resistant layer of protection. Ideal to use as a base coat before applying reflective roof coatings. For exterior foundations, **Fiber Coat+** dampproofs and preserves below grade surfaces including masonry, wood and metal. Can be used on a variety of surfaces and is low odor and water cleanup.

**PREPARATION:** Surfaces must be cleaned, free of dust, surface rust and loose material. If possible, power wash surface before applying coating. Use brush or 3/4" nap roller to spread coating across roof. Wear protective clothing. Don't apply to wet surfaces.

**APPLICATION:** Apply on a clear warm day with no rain expected for 24 hours. Apply when surface temperatures are between 60° and 120 °F. MIXING MAY BE REQUIRED TO ENSURE PRODUCT UNIFORMITY. DO NOT APPLY DIRECT HEAT/FLAMES OR THIN. Allow product to cure a minimum of 15 days prior to application of reflective coating, if used as a roof coating.

**COVERAGE RATE:** Covers approximately 50 sq. ft. per gal/per coat. Two coats are recommended.

**PRECAUTIONS:** Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100 °F. Do not use on EPDM, TPO, PVC or other rubber/synthetic surfaces. If there is any question regarding compatibility, test a small section first. Protect building inlet ventilation from product fumes. This manufacturer also disclaims liability for flat surface application where poor drainage or ponding water may prevail. Do not reuse empty containers. Do not use in drinking water or food systems. Protect from freezing.

**CLEAN-UP:** Clean tools or spills with paint thinner or mineral spirits.

**WARRANTY AND DISCLAIMER:** Gardner-Gibson, Inc. warrants this product to give satisfactory results when our directions are followed in its use and application, for a period of 12 months from the date of purchase. In no event however shall the manufacturer be liable for an amount in excess of the purchase price of the product used. If not completely satisfied, return to place of purchase for a refund.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
0181-GA	1 gal.	6.75" x 6.75" x 7.75"	3.6 qt. / 3.4 L	9 lbs.	6/case	025056018113
0185-GA	5 gal.	12" x 12" x 14.75"	4.75 gal / 18 L	47 lbs.	1 ea.	025056018557

[www.gardner-gibson.com](http://www.gardner-gibson.com)  
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449  
Phone: (813) 248-2101