



036 Roll Roofing Adhesive Liquid Roof Glue

- Use With Roll Roofing
- Great Adhesive & Bonding Strength
- Fibered Reinforced

Gardner® ROLL ROOFING ADHESIVE is a liquid applied, brushable, asphalt based adhesive, designed to bond sheets of roll roofing and also adds additional waterproofing protection to the roof surface. No Heating Needed.

WHAT IS NEEDED TO COMPLETE THE JOB? Brush, gloves and roll roofing material.

PREPARATION: Surfaces must be clean, free of surface rust and loose material. Apply on a clear warm day with no rain forecasted for 24-36 hours. MIXING MAY BE REQUIRED TO ENSURE PRODUCT UNIFORMITY. DO NOT APPLY DIRECTLY TO HEAT/FLAMES. DO NOT THIN. Apply when surface temperatures are between 50° and 120 °F. In colder weather (50 °F and below), product should be stored in heated room (70° to 80 °F) at least 24 hours prior to application to promote ease of application. Product formulated to be used year round.

APPLICATION: Use brush to spread across surface of roof and roll the rolls of roofing material into wet adhesive.

PRECAUTIONS: Apply in exterior applications only. Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills Do not store at temperatures above 100 °F. This manufacturer also disclaims liability for flat surface application where poor drainage or ponding water may prevail. Do not reuse empty containers. Do not use in drinking water or food systems. Seal container when not in use. Don't apply to wet or damp surfaces. Do not use on EPDM, TPO, PVC or other rubber/synthetic surfaces. If there is any question regarding compatibility, test a small section first. Protect from freezing.

COVERAGE RATE: Covers approx. 40 - 45 sq. ft. per gallon.

HOW TO CLEAN-UP: Clean tools with mineral spirits or paint thinner.

WARRANTY AND DISCLAIMER: Gardner-Gibson, Inc. warranties this product to give satisfactory results when our directions are followed in its use and application, for a period of 12 months from the date of purchase. In no event however shall the manufacturer be liable for an amount in excess of the purchase price of the product used. If not completely satisfied, return to place of purchase for a refund.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
0361-GA	1 gal.	6.75" x 6.75" x 7.75"	3.6 qt / 3.4 L	8.5 lbs.	6/case	025056036100
0365-GA	5 gal.	12" x 12" x 14.75"	4.75 gal / 18 L	45 lbs.	1 ea.	025056036506

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101