## gardner

## Wet-R-Dri® Ultra Rubberized Premium Roof Leak Repair

- Stops Roof Leaks Instantly
- Elastic Seal for Longest Life
- Seals Cracks and Splits in any Weather
- Repairs Mod-Bit or Traditional Roofs
- Heavy Duty Flashing Grade

Gardner® WET-R-DRI® Ultra Premium Roof Leak Repair is our best quality roof cement. This highly flexible product can be used year round in any weather condition to stop and seal leaks. This high performance product provides an exceptionally long lasting seal, formulated to repair cracks, seams and holes in roofing materials. It is also designed to be used in new construction and in setting flashings, drip edges and other roofing edges. It seals and provides a rubberized layer of waterproofing protection. Dries black.

Use on roofs around skylights, vents, exhaust pipes, chimneys, valleys, and in the construction or repair of flashings, roll roofing and shingles. Great for repairs and installation of Mod-Bit membranes, or on laminate shingles. Also excellent for use as a heavy duty below grade and underground waterproofer, and dampproofer.

**PREPARATION:** Trowel, reinforcing fabric and safety glasses, are recommended for application. Apply generously with a trowel or putty knife. Surfaces must be clean and free of surface rust and loose material. Apply in exterior applications only. Wear protective clothing, gloves and safety glasses.

**APPLICATION:** It is highly recommended to reinforce the repair with a strip of Universal Patching Fabric. Work material to an even consistency over and into the area to be repaired approximately 1/8" to 1/2" thick, two or three inches beyond the problem area. Embed fabric into the cement and cover with a second layer of cement. Form a feathered edge with cement where chimney's, vent pipes, and other projections meet the roof line. DO NOT APPLY DIRECT HEAT/FLAMES OR THIN. Apply when surface temperatures are between 50° and 120 °F. In colder weather (50 °F and below), product should be stored in heated room (70° to 80 °F.) at least 24 hours prior to application to promote ease of application. Product formulated to be used year round. Allow product to cure a minimum of 30 - 60 days prior to application of reflective coating.

COVERAGE RATE: One gallon covers approximately 12 sq. ft. when applied 1/8" thick.

**HANDLING AND STORAGE PRECAUTION:** When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100 °F. Do not use on EPDM, TPO, PVC or other rubber/synthetic surfaces. If there is any question regarding compatibility, test a small section first. This manufacturer also disclaims liability for flat surface application where poor drainage or ponding water may prevail. Protect from freezing.

CLEAN-UP: Clean tools with paint thinner or mineral spirits.

**WARRANTY AND DISCLAIMER:** Gardner-Gibson, Inc. warranties this product to give satisfactory results when our directions are followed in its use and application, for a period of (15) fifteen years from the date of purchase. Warranty is dependent upon using reinforcing fabric as described in application instructions. At discretion of manufacturer, if product does not perform as stated for the time period, product will be replaced or refunded on a prorated amount. In no event however shall the manufacturer be liable for an amount in excess of the purchase price of the product used. If not completely satisfied, return to place of purchase for a refund.

| AVAILABLE SIZES |           |                       |                   |             |           |              |
|-----------------|-----------|-----------------------|-------------------|-------------|-----------|--------------|
| PRODUCT CODE    | UNIT SIZE | UNIT DIMENSIONS       | FILL LEVEL        | UNIT WEIGHT | PACK      | UPC          |
| 0399-GA         | 10 fl.oz. | 2" x 2" x 11.5"       | 10 fl.oz./ 296 mL | 1 lbs.      | 12/case   | 025056039903 |
| 0391-GA         | 1 gal.    | 6.75" x 6.75" x 7.75" | 3.6 qt / 3.4 L    | 9 lbs.      | 6/case    | 025056039118 |
| 0393-GA         | 2.75 gal. | 13.3" x 13.3" x 12"   | 2.75 gal./ 10.4 L | 27 lbs.     | 36/pallet | 025056039309 |