



Gard-Lock

Mineral surface self-stick leak protection for use under shingles, tile, slate and shakes.

Gardner® Gard-Lock is a self-adhered modified asphalt underlayment for roofs. It is ideal to use in leak-prone areas and around roof edges or across the entire roof surface for maximum waterproofing protection. It is designed to seal and protect the roof deck, while also preventing leaks caused by wind driven rain and ice damming. This premium asphalt membrane is reinforced with fiberglass for superior stability and strength. Gard-Lock is specifically designed with adhesion promoters to provide better adhesion over a variety of temperature ranges. Installers appreciate the non-skid safe walking surface and the easy peel and stick application feature.

- Helps prevent leaks at common problem areas (eaves & rakes, valleys, chimney, vents, ect.)
- Adheres to plywood, OSB, concrete & gypsum
- Lap Seal technology for tight seams
- Meets Northern building codes, helping prevent eave leaks from ice damming

Preferred by pro's because:

- Lays flatter for an improved look
- Safe, Non-skid surface
- High tack membrane with E-Z release film
- Nail self-sealing to prevent leaks

Approvals:

Miami-Dade
(NOA 17-0427.10),
FBC#23128.1,
UL Classified,
ASTM D1970 & AC188,
90 day exposure rated

