



750 Sta-Kool® Basic Acrylic

- White finish protects roofs
- Can help lower cooling costs
- Expands and contracts up to 200%

GARDNER® STA-KOOL® Basic Acrylic is a flexible coating that resists cracking & peeling. The coating provides protection by helping to reflect the sun's heat and UV rays. This helps to cool roof surfaces, reduce interior heat gain and lowers cooling costs*.

PREP: Pressure wash surfaces for best results. All surfaces must be clean and dry. Rusty metal must be treated and primed. Repair all leaks and cracks with White Roof Patch and Repair Fabric in accordance with patching instructions. Surfaces previously coated with aluminum, asphalt or tar coatings, should be allowed to cure for a minimum of one summer season prior to coating with this product.

APPLICATION: Surface and air temperatures must be over 50 °F and rising. DO NOT apply if heavy dew or rain is expected within 24 - 48 hours. Apply in morning hours on a clear, sunny day. Use 3/4" nap exterior paint roller to apply one coat over all seams and joints. Wait 1-2 hours, then apply two (2) uniform coats over entire surface. Apply second coat perpendicular to first coat. Allow at least 24 hours between coats and 24 - 48 hours for full curing. DO NOT apply to areas where ponding water will exist. Not for use on EPDM or some single ply membranes. Roofs must have proper ventilation.

COVERAGE RATE: Approximately 50 - 75 sq. ft. per gal. per coat. Total Coverage for two (2) coat application is 25 - 35 sq. ft. per gallon.

CLEAN-UP: Clean tools with soap and water.

PRECAUTIONS: Protect from freezing. Protective clothing, gloves and eyewear should be used during application. During transport, ensure that lid is tight and pail secure and upright. DO NOT allow pail to tumble as this will cause lid to loosen and leakage may occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. DO NOT reuse empty containers. Do not use on EPDM, TPO, PVC or other rubber/synthetic or single ply roofs. If there is any question regarding compatibility, test a small section first. Do not use in drinking water or food systems. Store unused product in a controlled environment, 55 °F - 80 °F. Do not store in direct sunlight.

WARRANTY AND DISCLAIMER: Gardner-Gibson warrants product to be free of material defects for a period of 5 years, the "Warranty Period", from the date of purchase. Product must be applied in accordance with the proper application procedures, and for the intended use as stated on the label. Proper preparation and drying conditions must be observed to achieve correct results. Should a product not perform as stated, Gardner-Gibson shall, within its sole discretion and upon receipt of purchaser's timely written notice within the Warranty Period, provide replacement product to repair the affected area or prorate a portion of the purchase price of the defective product based on the claim period. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company below to request a refund with purchase receipt. There are no warranties which extend beyond the description on the face hereof. THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY GARDNER-GIBSON TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
SK-7505	5 gal.	12" x 12" x 14.75"	5 gal. / 18.9 L	52 lbs.	1 ea.	025056750563

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101